Electronics Letters

VOLUME 16, 1980

THE INSTITUTION OF ELECTRICAL ENGINEERS

Electronics Letters

THE INSTITUTION OF ELECTRICAL ENGINEERS

ELECTRONICS LETTERS is published fortnightly.* Price £8·00 ($18·00) per issue; annual subscription in UK £77·00, overseas £108·00 ($240·00). Second-class postage paid at New York, NY. All copies for North America are sent by air freight to New York. Airmail direct to subscriber at an additional charge of £20·00. Available also in a concurrent microfiche edition at the same subscription rate as for the printed edition. The subscription for combined paper and microfiche is £95 (UK), overseas £144.

* Except in December when only one issue is published. There are 25 issues each year

All subscription inquiries and orders should be sent to the Publication Sales Department, IEE, Station House, Nightingale Road, Hitchin, Herts. SG5 1RJ, England. Telephone Hitchin 53331 (s.t.d. 0462 53331), Telex 26117

Contributions should be addressed to the Executive Editor, *Electronics Letters*, Publishing Department, Institution of Electrical Engineers, PO Box 8, Southgate House, Stevenage, Herts. SG1 1HQ, England
There is no page charge

All other correspondence, including advertisements, should be sent to: IEE Publishing Department, PO Box 8, Southgate House, Stevenage, Herts. SG1 1HQ, England. Telephone Stevenage 3311 (s.t.d. 0438 3311), Telex 261176, Telegrams Voltampere Stevenage, England. The telephone number of the IEE London office is 01–240 1871, Telex 261176

The advantages of rapid publication given by *Electronics Letters* are nullified if subscribers are subject to excessive delays in the receipt of the journal. The Executive Editor would be grateful to learn of any difficulties subscribers may experience

This publication is copyright under the Berne Convention and the International Copyright Convention. All rights reserved. Apart from any copying under the UK Copyright Act 1956, part 1, section 7, whereby a single copy of an article may be supplied, under certain conditions, for the purposes of research or private study, by a library of a class prescribed by the UK Board of Trade Regulations (Statutory Instruments, 1957, no. 868), no part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means without the prior permission of the copyright owners. Permission is, however, not required to copy abstracts of papers or articles on condition that a full reference to the source is shown

The IEE appreciates that, on certain occasions, it could be very useful for organisations to be able to make copies of articles and papers. An IEE licensing arrangement exists whereby organisations entering into an agreement are legally entitled to make up to ten copies of an IEE paper or article. Full details may be obtained from the IEE Publishing Department at the above address

The appearance of the code at the bottom of an article in this journal indicates the copyright owner's consent that copies of the article may be made in the USA for personal or internal use, or for the personal or internal use of specific clients. This consent is given on the condition, however, that the copier pay the stated per-copy fee through the Copyright Clearance Center, Inc. for copying beyond that permitted by Sections 107 or 108 or the US Copyright Law. This consent does not extend to other kinds of copying, such as copying for general distribution, for advertising or promotional purposes for creating new collective works or for resale. Payment is also required for copying of articles published before 1979

The IEE is not as a body responsible for the opinions expressed by individual authors

The IEE is a member of the Association of Learned & Professional Society Publishers

Publishing Department:

PO Box 8
Southgate House
Stevenage
Herts. SG1 1HQ
England

Secretary of the IEE:

H.H.W. Losty

Director of Publishing:

D.S. Hopper

Editor in Chief:

J. D. St. Aubyn

Managing Editor:

B. Dunkley

Executive Editor:

P. Mitchell

Graphics Manager:

M. C. Partridge

EDITORS

P. J. B. Clarricoats *(London)*
E. A. Ash *(London)*

Advertisement Department:

IEE
PO Box 8
Southgate House
Stevenage
Herts. SG1 1HQ
England

© 1980: The Institution of Electrical Engineers

The Institution of Electrical Engineers, Savoy Place, London WC2R 0BL, England

Typeset in England by:
Santype International Ltd
Netherhampton Road
Salisbury
Wilts. SP2 8PS

Printed in England by:
C. F. Hodgson & Son Ltd
50 Holloway Road
London N7 8JL

Electronics Letters

INDEX VOLUME 16, 1980

Author index

A

Abbashi, S.A., and Brunnschweiler, A. Correction of spreading resistance data obtained from bevelled shallow junctions 507

Abdul-Jauwad, S., and Bennett, J.C. see Bennett, J.C.

Abram, R.A., and Goodfellow, R.C. Coupling efficiency calculations on an integrated l.e.d./sphere-lens source for optical fibres 14

Abuelma'atti, M.T., and Gardiner, J.G. Deduction of amplifier phase transfer characteristic from measured a.m./p.m. conversion-coefficient characteristic 298

Accatino, L., and Angelucci, A. Differential measurement technique for evaluating microstrip line attenuation 427 e791

Adams, A.R. Calculations of the intrinsically higher temperature stability of electronic devices made from quaternary alloys 177

Adams, A.R., Tatham, H.L., Hayes, J.R., El-Sabbahy, A.N., and Greene, P.D. Evidence for alloy scattering from pressure-induced changes of electron mobility in $In_{1-x}Ga_xAs_yP_{1-y}$ 560

Adams, A.R., Hayes, J.R., and Greene, P.D. see Hayes, J.R.

Adams, A.R., Stubkjaer, K., Suematsu, Y., Asada, M., and Arai, S. see Stubkjaer, K.

Adams, M.J., Ramskov Hansen, J.J., and Ankiewicz, A. see Ramskov Hansen, J.J.

Adams, M.J., Ramskov Hansen, J.J., Ankiewicz, A., and Sladen, F.M.E. see Ramskov Hansen, J.J.

Adams, M.J., Sasaki, I., and Payne, D.N. see Sasaki, I.

Adant, J.M., and Delogne, P. Television demodulator receiving signals by satellite 401

Adkins, L.R., and Glass, H.L. Propagation of magnetostatic surface waves in multiple magnetic layer structures 590

Aebi, V., Cooper, C.B., Ludowise, M.J., and Moon, R.L. see Cooper, C.B.

Agarawal, R.P., and Sinha, S.N. see Sinha, S.N.

Ahmad, K., Smith, D.R., Hooper, R.C., Jenkins, D., Mabbitt, A.W., and Nicklin, R. see Smith, D.R.

Ahmed, H., McMahon, R.A., Dobson, R.M., and Speight, J.D. see McMahon, R.A.

Ahmed, H., Shah, N.J., Sanders, I.R., and Singleton, J.F. see Shah, N.J.

Ahmed, K.U. Integrated bandpass filters 424 e525

Ahmed, K.U., and Singh, H.R. Integrated nonuniform thin-film bandpass filter 277

Ainslie, B.J., Day, C.R., Rush, J., and Beales, K.J. Optimised structure for preparing long ultra-low-loss single-mode fibres 692

Aitchison, C.S., and Sarhadi, M. see Sarhadi, M.

Al Hossri, N., Lacroix, G., and Marchegay, Ph. see Lacroix, G.

Alcaim, A., Turner, L.F., and Frangoulis, E. see Turner, L.F.

Alder, C.J., Cattell, A., Dexter, K., Dixon, M., and Kirton, J. Bulk and junction effects in d.c. electroluminescent ZnS: Cu, Mn powder panels 571

Allnatt, J.W. Subjective assessment method for television digital codecs 450

Allnatt, J.W., and White, T.A. see White, T.A.

Amann, M.-C., Kuschmider, A., and Boeck, J. Optical memory readout by superluminescent diode with integrated photodetector 58

Ambikairajah, E., and Carey, M.J. Technique for performing multiplication on a 16-bit microprocessor using an extension of Booth's algorithm 53

Ambikairajah, E., Carey, M.J., and Tattersall, G. Estimating the pitch period of voiced speech 464

Anand, Y., Christou, A., and Day, H. Ideality and noise figure characteristics of r.f. sputtered millimetre GaAs diodes 581

Anand, Y., Christou, A., Anderson, W.T. Jr., Davey, J.E., and Bark, M.L. see Christou, A.

Ananda Mohan, P.V. Novel active filters using amplifier pole 378 e683

Andersen, E.F. Differential propagation delay in optical multifibre cables 389

Anderson, A.P., Marie, K.H.S., and Bennett, J.C. see Marie, K.H.S.

Anderson, R.J., Liu, Y.Z., Deyhimy, I., and Tomasetta, L.R. see Liu, Y.Z.

Anderson, W.T. Jr., Christou, A., Davey, J.E., Bark, M.L., and Anand, Y. see Christou, A.

Andersson, T., Lindström, C., Tihanyi, P., and Torphammar, P. see Lindström, C.

Ando, H., Kanbe, H., Susa, N., and Nakagome, H. see Kanbe, H.

Angelucci, A., and Accatino, L. see Accatino, L.

Ankiewicz, A., Ramskov Hansen, J.J., and Adams, M.J. see Ramskov Hansen, J.J.

Ankiewicz, A., Ramskov Hansen, J.J., Adams, M.J., and Sladen, F.M.E. see Ramskov Hansen, J.J.

Ankri, D., and Scavennec, A. Design and evaluation of a planar GaAlAs-GaAs bipolar transistor 41

Antar, Y.M.M., Hendry, A., Schlesak, J.J., Olsen, R.L., and Bérubé, R.C. Ice-crystal depolarisation measurements at 28.6 GHz with simultaneous 16.5 GHz polarisation diversity radar observations 808

Aono, Y., Higashisaka, A., and Hasegawa, F. Effects of capacitance at crossover wirings in power GaAs m.e.s.f.e.t.s. 417

Aoyama, T., Minowa, J., Fujii, Y., Nagata, Y., and Doi, K. see Minowa, J.

Arai, S., Asada, M., Suematsu, Y., Itaya, Y., Tanbun-ek, T., and Kishino, K. New 1.6 μm wavelength GaInAsP/InP buried heterostructure lasers 349

Arai, S., Stubkjaer, K., Suematsu, Y., Asada, M., and Adams, A.R. see Stubkjaer, K.

Arazi, B. Connection between primitive generators of $GF(2^n)$ 223

Arcelli, C., Cordella, L.P., and Levialdi, S. More about a thinning algorithm 51 e240

Armand, M., Chevrier, J., and Linh, N.T. Microwave power amplification with InP f.e.t.s. 906

Arnaud, J., and Rousseau-Leberre, M. Bandwidth of distorted multimode waveguides excited by laser sources 34

Arnaud, J., and Barthelemy, A. see Barthelemy, A.

Arnaud, J., Facq, P., and Fournet, P. see Facq, P.

Arnbak, J. E.I.R.P. allocation for a nonlinear satellite channel with multiple transmit beams and carriers e75

Arnbak, J., Van Ommeren, M.J.S., and Herben, M.H.A.J. see Van Ommeren, M.J.S.

Arnold, N., Daembkes, H., and Heime, K. I.C.-compatible completely planar GaAs m.e.s.f.e.t.s. by selective diffusion 923

Asada, M., Arai, S., Suematsu, Y., Itaya, Y., Tanbun-ek, T., and Kishino, K. see Arai, S.

Asada, M., Stubkjaer, K., Suematsu, Y., Arai, S., and Adams, A.R. see Stubkjaer, K.

Asatani, K., Sato, K., Maki, K., and Miki, T. Fibre optic analogue transmission experiment for high-definition television signals using semiconductor laser diodes 536

Asatani, K., and Sato, K. see Sato, K.

Asatani, K., and Watanabe, R. see Watanabe, R.

Ash, E.A., Dieulesant, E., and Rakouth, H. Generation of surface acoustic waves by means of a c.w. laser 470

Ash, E.A., Dürr, W., and Sinclair, D.A. see Dürr, W.

Ash, E.A., and Sinclair, D.A. see Sinclair, D.A.

Askerov, S.G., and Luukkala, M. see Luukkala, M.

Aucoin, T.R., Malik, R.J., Ross, R.L., Board, K., Wood, C.E.C., and Eastman, L.F. see Malik, R.J.

Auffret, R., Pophillat, L., and Kervarrec, Y. Field measurement set for attenuation and bandwidth of optical links 798

B

Baack, C., Elze, G., Enning, B., and Walf, G. Modal noise and optical feedback in high-speed optical systems at 0.85 μm 592

Badawi, M.H., Sealy, B.J., and Clegg, J.B. Redistribution of chromium in semi-insulating GaAs: Cr during laser annealing 554

Badertscher, G., Salathe, R.P., and Luthy, W. Ohmic contacts on n-GaAs produced by laser alloying of Ge films 113

Badreddin, E., and Mansour, M. Model reduction of discrete-time systems using the Schwarz canonical form 782

Bahl, I.J., Stuchly, S.S., and Stuchly, M.A. New microstrip slot radiator for medical applications 731

Bahr, A.J. Microwave detection of third-order nonlinearities in fatigue cracks 150

Bajpai, S.N., and Srivastava, N.C. Magnetostatic bulk wave propagation in a multi-layered structure 269

Bakken, P.M., and Maseng, T. E.I.R.P. allocation in single-destination f.d.m.a. satellite communication systems 6 e75

Ball, P.R., and Culshaw, B. Intermode phase scanning for recovering phase-modulated signals on multimode optical fibres 259

Ballman, A.A., Leheny, R.F., Nahory, R.E., Pollack, M.A., Beebe, E.D., DeWinter, J.C., and Martin, R.J. see Leheny, R.F.

Balston, D.M., and Mason, D.C. see Mason, D.C.

Banjongjit, S., Thajchayapong, P., and Puangpool, M. see Thajchayapong, P.

Bar-Chaim, N., Katz, J., Margalit, S., and Yariv, A. see Katz, J.

Bark, M.L., Christou, A., Anderson, W.T. Jr., Davey, J.E., and Anand, Y. see Christou, A.

Barker, R.W.J., and Hart, B.L. Novel submicroamper current-source design technique for monolithic circuits 609

Barnes, P.A., Dutta, N.K., and Nelson, R.J. see Dutta, N.K.

Barrell, K.F., and Pask, C. Leaky ray correction factors for elliptical multimode fibres 532
Barth, H., Freyer, J., and Kasper, E. see Freyer, J.
Barthelemy, A., and Arnaud, J. Adiabatic method for fibres with nonseparable index profiles 193
Barthelemy, A., and Piasecki, J. see Piasecki, J.
Bartley, N.R., Stein, R.A., and Bruton, L.T. see Stein, R.A.
Bastida, E.M., and Fanelli, N. Interdigitated coplanar directional couplers 645
Batchelor, B.G., and Marlow, B.K. see Marlow, B.K.
Beales, K.J., Ainslie, B.J., Day, C.R., and Rush, J. see Ainslie, B.J.
Bedair, S.S., and Sobhy, M.I. Approximate solution for propagation modes on lossy multiconductor transmission lines in inhomogeneous media 914
Beebe, E.D., Leheny, R.F., Nahory, R.E., Pollack, M.A., Ballman, A.A., DeWinter, J.C., and Martin, R.J. see Leheny, R.F.
Behar, D., Kino, G.S., Bowers, J.E., and Olaisen, H. Storage correlator as an adaptive inverse filter 130
Behar, D., Olaisen, H., Kino, G.S., Corl, D., and Grant, P.M. Use of a programmable filter for inverse filtering 88
Beker, S., and Cohen, A. see Cohen, A.
Beneking, H., Filensky, W., and Ponse, F. Bit synchronisation in Gbit/s range using dual gate GaAs m.e.s.f.e.t.s. 543
Beneking, H., Filensky, W., and Ponse, F. Multi/demultiplexing in Gbit/s range using dual gate GaAs m.e.s.f.e.t.s. 551
Beneking, H., Grote, N., Roth, W., and Svilans, M.N. GaAs-GaAlAs phototransistor/laser light amplifier 602
Beneking, H., Filensky, W., and Ponse, F. see Filensky, W.
Bennett, J.C., and Abdul-Jauwad, S. Effective data collection aperture in long-wavelength imaging systems 696
Bennett, J.C., Marie, K.H.S., and Anderson, A.P. see Marie, K.H.S.
Bennetts, R.G., and Nanda, N.K. see Nanda, N.K.
Benz, K.W., Renz, H., Weidlein, J., and Pilkuhn, M.H. see Renz, H.
Bergh, R.A., Kotler, G., and Shaw, H.J. Single-mode fibre optic directional coupler 260
Bernard, J., Frey, J., Lee, K.F., and Gibbons, J.F. Micrometre-gate m.e.s.f.e.t.s. on laser-annealed polysilicon 297
Berry, R.W., Malyon, D.J., and Smith, D.W. see Malyon, D.J.
Berth, M., Martin, G.M., and Venger, C. see Martin, G.M.
Bérubé, R.C., Antar, Y.M.M., Hendry, A., Schlesak, J.J., and Olsen, R.L. see Antar, Y.M.M.
Besomi, P., and Wessels, B.W. Deep level defects in Au/ZnSe Schottky diodes 794
Bhagavatula, V.A., Love, W.F., Keck, D.B., and Westwig, R.A. Refracted power technique for cutoff wavelength measurement in singlemode waveguides 695
Bianco, B., Corana, A., Gogioso, L., Ridella, S., and Parodi, M. Open-circuited coaxial lines as standards for microwave measurements 373
Bickley, W.P., Eddolls, D.V., and Maher, E.F. Extrinsic photoconductivity in platinum-doped silicon 898
Biey, M., and Premoli, A. Transfer functions with equiripple passband and very low Q-factor for economical active filters (Comment) 74
Birch, J.R. Free space video detection of harmonic content of 100 GHz impatt oscillator 799
Bird, T.S. Asymptotic behaviour of TE_{11} mode coupling in circular apertures 529
Bistritz, Y. Mixed complete Padé model reduction: a useful formulation for closed loop design 563
Bistritz, Y. Mixed time/frequency domain approach to model reduction (Comment) 189
Black, P.W., Rosiewicz, A., Gray, M.H., Irven, J., and Titchmarsh, J.G. see Rosiewicz, A.
Board, K., and Darwish, M. see Darwish, M.
Board, K., Eastman, L.F., Stall, R., Woodard, D., Dandekar, N., Wood, C.E.C., and Shur, M.S. see Eastman, L.F.
Board, K., Malik, R.J., Aucoin, T.R., Ross, R.L., Wood, C.E.C., and Eastman, L.F. see Malik, R.J.
Bodea, M., Silard, A., and Luca, M. see Silard, A.
Boeck, J., Amann, M.-C., and Kuschmider, A. see Amann, M.-C.
Bon, M., and Konczykowska, A. see Konczykowska, A.
Bonnafe, J., Castagne, M., Romestan, J., De Murcia, M., and Fillard, J.P. Shallow trap spectroscopy in InP: Fe 313
Bonnet, M., Hirtz, J.P., Duchemin, J.P., Hirtz, P., de Cremoux, B., and Pearsall, T. see Hirtz, J.P.
Bonnet, M., Hirtz, J.P., Larivain, J.P., Duchemin, J.P., and Pearsall, T.P. see Hirtz, J.P.
Borissov, M., Grantcharov, K., Detchev, D., Spassov, L., and Yossifov, E. see Grantcharov, K.
Botez, D., and Connolly, J.C. Low-threshold high-T_o constricted double heterojunction AlGaAs diode lasers 942
Bowers, J.E., Behar, D., Kino, G.S., and Olaisen, H. see Behar, D.
Bradshaw, A. High-gain decentralised control of interconnected dynamical systems 216
Braine, M.R., and Nouri, M. see Nouri, M.
Brandon, P.S., and Kwok, P.C.K. see Kwok, P.C.K.
Brandt, G.B., and Gottlieb, M. see Gottlieb, M.
Bransalov, K.P., Strashilov, V.L., and Hinkov, V.P. see Strashilov, V.L.
Brezovich, I.A., and Chakraborty, D.P. see Chakraborty, D.P.
Brezovich, I.A., Young, J.H., and Wang, M.-T. see Young, J.H.
Brickell, F., Westcott, B.S., and Stevens, F.A. see Westcott, B.S.
Brinkmeyer, E. Backscattering in single-mode fibres 329
Bromba, M.U.A., and Ziegler, H. Explicit formula for filter function of maximally flat nonrecursive digital filters 905
Brooks, R. 7B8B balanced code with simple error detecting capability 458
Brown, A.K. Crosspolarisation characteristics of linear comb-line microstrip antennas 743
Brugger, U.W., Von Grünigen, D.C., and Moschytz, G.S. see Von Grünigen, D.C.
Brugger, U.W., Von Gruningen, D.C., and Hosticka, B.J. see VonGruningen, D.C.
Brunnschweiler, A., and Abbashi, S.A. see Abbashi, S.A.
Bruton, L.T., Haslett, J.W., and Rao, M.K.N. see Haslett, J.W.
Bruton, L.T., Stein, R.A., and Bartley, N.R. see Stein, R.A.
Buettner, H.M. Compact directional V.H.F. antennas 938
Bull, C.J., and Neill, T.R. see Neill, T.R.
Bunks, C., and Preis, D. see Preis, D.
Burrus, C.A., Campbell, J.C., Dentai, A.G., and Ferguson, J.F. see Campbell, J.C.
Burrus, C.A., Lee, T.P., and Cho, A.Y. see Lee, T.P.
Burrus, C.A., Lee, T.P., and Dentai, A.G. see Lee, T.P.
Burrus, C.A., Lee, T.P., Dentai, A.G., and Ogawa, K. see Lee, T.P.

C

Cahill, R., and Parker, E.A. Effect of edge region on crosspolar performance of dichroic plate 710
Calleja, E., Martinez, J., and Piqueras, J. see Martinez, J.
Campbell, J.C., Dentai, A.G., Burrus, C.A., and Ferguson, J.F. High sensitivity InP/InGaAs heterojunction phototransistor 713
Capasso, F., Logan, R.A., Foy, P.W., Sumski, S., and Manchon, D.D. Low leakage current and saturated reverse characteristic in broad-area InGaAsP diodes 241
Capasso, F., Logan, R.A., Hutchinson, A., and Manchon, D.D. InGaAsP/InGaAs heterojunction p-i-n detectors with low dark current and small capacitance for 1.3 - 1.6 μm fibre optic systems 893
Carayannis, G., Kalouptsidis, N., and Manolakis, D. Efficient algorithm for determination of a.r. part of a.r.m.a. model 656
Carey, M.J., and Ambikairajah, E. see Ambikairajah, E.
Carey, M.J., Ambikairajah, E., and Tattersall, G. see Ambikairajah, E.
Carpentier, M.P., and Dos Santos, A.F. Validity of the quasi-tem approximation for the modes supported by a horizontal wire above ground 85
Casares-Giner, V., and Garcia-Lopez, J.A. see Garcia-Lopez, J.A.
Casey, Jun, H.C., Cho, A.Y., Radice, C., and Foy, P.W. see Cho, A.Y.
Caspers, F. Precision time-domain measurement system 29
Castagne, M., Bonnafe, J., Romestan, J., De Murcia, M., and Fillard, J.P. see Bonnafe, J.
Castera, J.P., and Hartemann, P. Adjustable magnetostatic surface-wave multistrip directional coupler 195
Cathelin, M., Durand, G., Gavant, M., and Rocchi, M. 5 GHz binary frequency division on GaAs 535
Cattell, A., Alder, C.J., Dexter, K., Dixon, M., and Kirton, J. see Alder, C.J.
Cattermole, K.W., and Munoz Rodriguez, D. see Munoz Rodriguez, D.
Cattermole, K.W., and Sundara Murthy, K.M. see Sundara Murthy, K.M.
Caulton, M., Rosen, A., and Martinelli, R.U. see Rosen, A.
Chakraborti, N.B., Kumar, N., and Mukherjee, A.K. see Kumar, N.
Chakraborty, D.P., and Brezovich, I.A. A source of thermocouple error in radiofrequency electric fields 853
Chandross, E.A., Melliar-Smith, C.M., Lazay, P.D., Pasteur, G.A., and Wood, D.L. see Melliar-Smith, C.M.
Chang, C.Y., Chen, T.C., and Han, K.W. see Chen, T.C.
Chaplart, J., Delagebeaudeuf, D., Delescluse, P., Etienne, P., Laviron, M., and Linh, N.T. see Delagebeaudeuf, D.
Chapman, C.W., and Judd, G.W. Measurement of s.a.w. device stripe/period ratio using optical diffraction 952
Chapman, R., and Durrani, T.S. see Durrani, T.S.
Charef, M., Zimmermann, J., Fauquembergue, R., and Constant, E. see Zimmermann, J.
Chassay, G., and Saillard, J. Analysis of r.c.s. diagram of target in Tchebyshev polynomial space 652
Chatterjee, A.K., Smith, D.R., Rejman, M.A.Z., Wake, D., and White, B.R. see Smith, D.R.
Chen, F.S. Simultaneous feedback control of bias and modulation currents for injection lasers 7
Chen, T.C., Chang, C.Y., and Han, K.W. Stable reduced-order Padé approximants using stability-equation method 345
Chen, Z., Das, S.R., and Dai, Y.L. see Das, S.R.
Chengyi, W. Improved framing circuit and its performance evaluation 144
Chevrier, J., Armand, M., and Linh, N.T. see Armand, M.
Chida, K., Moriyama, T., Fukuda, O., Sanada, K., Inada, K., and Edahiro, T. see Moriyama, T.
Chida, K., Nakahara, M., Hanawa, F., Sudo, S., and Horiguchi, M. see Nakahara, M.
Chida, K., Suda, H., and Nakahara, M. see Suda, H.
Chida, K., Sudo, S., Kawachi, M., and Edahiro, T. see Sudo, S.
Chin, A.K., and Temkin, H. see Temkin, H.

Chin, R., Holonyak, N. Jun., Stillman, G.E., Tang, J.Y., and Hess, K. Impact ionisation in multilayered heterojunction structures 467
Chin, R., Milano, R.A., and Law, H.D. Schottky barrier height of Au on n-type $Ga_{1-x}Al_xSb$ ($0.0 \leq x \leq 0.65$) 626
Ching, P.C., and Goodyear, C.C. L.M.S. algorithm for sequentially adapting all-zero digital filters in modified cascade form 270
Cho, A.Y., Casey, Jun, H.C., Radice, C., and Foy, P.W. Influence of growth conditions on the threshold current density of double-heterostructure lasers prepared by molecular-beam epitaxy 72
Cho, A.Y., Lee, T.P., and Burrus, C.A. see Lee, T.P.
Cho, A.Y., Morkoc, H., Witkowski, L.C., Drummond, T.J., Stanchak, C.M., and Streetman, B.G. see Morkoc, H.
Chowdhury, S.K., and Das, N. see Das, N.
Christou, A., Anderson, W.T. Jr., Davey, J.E., Bark, M.L., and Anand, Y. High performance millimetre Ge-GaAs mixer diode for low l.o. power applications 254
Christou, A., Anand, Y., and Day, H. see Anand, Y.
Chu, P.L. Calculation of impulse response of multimode optical fibre 429
Chu, P.L., and Peri, D. Holographic measurement of refractive-index profile of optical fibre preform 876
Chu, P.L., and Peri, D. see Peri, D.
Chubachi, N., Kushibiki, J., and Sannomiya, T. see Kushibiki, J.
Cichocki, A. Synthesis of nonlinear functions using continued fraction expansion 431
Citerne, J. Higher-mode cutoff in elliptical dielectric waveguides (Comment) 13
Citerne, J., and Sachse, K. see Sachse, K.
Clarke, R.J., and Ismail, M.G.B. see Ismail, M.G.B.
Clarricoats, P.J.B., and Elliott, R.D. see Elliott, R.D.
Clarricoats, P.J.B., and Parini, C.G. see Parini, C.G.
Clegg, J.B., Badawi, M.H., and Sealy, B.J. see Badawi, M.H.
Cochrane, P., and Kitchen, J.A. Novel supervisory channel for fibre optic transmission systems 624
Cohen, A., and Beker, S. L.P.C. speech recognition with random reference correlation 885
Cohen, L.G., Gloge, D., and Ogawa, K. see Gloge, D.
Coimbra, M.L., and Podcameni, A. see Podcameni, A.
Cole, T.W. New class of one-bit digital autocorrelator 86
Collins, P.Q., and Gelsthorpe, R.V. see Gelsthorpe, R.V.
Colquhoun, A., Kohn, E., and Rabe, W.J. GaAs varactors for linear tuning characteristics 736
Combemale, Y., d'Auria, L., Moronvalle, C., and Jacques, A. see d'Auria, L.
Commanges, D., and Monsion, M. see Monsion, M.
Conduit, A.J., Hartog, A.H., and Payne, D.N. Spectral- and length-dependent losses in optical fibres investigated by a two-channel backscatter technique 77
Connolly, J.C., and Botez, D. see Botez, D.
Connor, F.R. New commutated Doppler microwave landing system 365
Conradi, J., and Few, I.S. Frequency dependence of Rayleigh backscattering in bidirectional optical systems at 0.83 and 1.3 μm 414
Conradi, J., Kim, H.B., and Maciejko, R. see Kim, H.B.
Constant, E., Zimmermann, J., Fauquembergue, R., and Charef, M. see Zimmermann, J.
Cooper, C.B., Ludowise, M.J., Aebi, V., and Moon, R.L. Use of trimethylantimony and trimethylarsenic for organometallic v.p.e. growth of $GaAs_{1-y}Sb_y$ and $Ga_{1-x}In_xAs$ 20
Cooper, C.B., Saxena, R.R., and Ludowise, M.J. O.M. V.P.E. growth of AlGaSb and AlGaAsSb 892
Corana, A., Bianco, B., Gogioso, L., Ridella, S., and Parodi, M. see Bianco, B.
Cordella, L.P., Arcelli, C., and Levialdi, S. see Arcelli, C.
Corl, D., Behar, D., Olaisen, H., Kino, G.S., and Grant, P.M. see Behar, D.
Corsini, G., and Dalle Mese, E. see Dalle Mese, E.
Cory, H., and Leviatan, Y. Reflection coefficient optimisation at feed of parabolic antenna fitted with vertex plate 945
Costa, B., Sordo, B., Menaglia, U., Piccari, L., and Grasso, G. Attenuation measurements performed by backscattering technique 352
Court, R.A. Alternative burst transmission technique for digital telephone reticulation 583
Crowley, J.D., Sowers, J.J., Janis, B.A., and Fank, F.B. High efficiency 90 GHz InP Gunn oscillators 705
Cruz, J., and Simpson, R.S. Error rate performance for s.f.s.k. with cochannel and intersymbol interference 515
Culshaw, B., and Kingsley, S.A. Thermal phase noise in coherent optical-fibre systems 97
Culshaw, B., and Ball, P.R. see Ball, P.R.
Cung, T.T., Lecours, M., and Huynh, H.T. Influence of multipath fading in 4Φ-C.P.S.K. systems 733
Curtis, J.P., and Plumb, R.G. see Plumb, R.G.
Czarczynski, W., and Znamirowski, Z. see Znamirowski, Z.

D

d'Auria, L., Combemale, Y., Moronvalle, C., and Jacques, A. High index microlenses for GaAlAs laser-fibre coupling 322
Da Rocha, V.C. Jun., and Wolfenson, M. see Wolfenson, M.
Daembkes, H., Arnold, N., and Heime, K. see Arnold, N.
Dagakis, K., Mantakas, C., and Papadopoulos, G. New technique for channel synchronisation in time division multiplexing 944
Dähne, C., and Harmer, A.L. Bistable optical fibre switch 647
Dai, Y.L., Das, S.R., and Chen, Z. see Das, S.R.
Daikoku, K., and Yamada, K. see Yamada, K.
Daino, B., De Marchis, G., and Piazzolla, S. Analysis and measurement of modal noise in an optical fibre 675
Dakss, M.L., and Kim, B. Effects of fibre propagation loss on diode-laser-fibre coupling 421
Dakss, M.L., and Kim, B. Simple self-centring technique for mounting microsphere coupling lens on a fibre 463
Dalle Mese, E., and Corsini, G. Adaptive Kalman filter equaliser 547
Dalpadado, R.N.G., and Shirae, K. Magnetic noise controlled by electric current through core 103
Damen, T.C., and Duguay, M.A. Optoelectronic regenerative pulser 166
Damen, T.C., Lin, C., Liu, P.L., Eilenberger, D.J., and Hartman, R.L. see Lin, C.
Dandekar, N., Eastman, L.F., Stall, R., Woodard, D., Wood, C.E.C., Shur, M.S., and Board, K. see Eastman, L.F.
Dandridge, A., Miles, R.O., and Giallorenzi, T.G. Diode laser sensor 948
Dandridge, A., Tveten, A.B., Sigel, G.H. Jr., West, E.J., and Giallorenzi, T.G. Optical fibre magnetic field sensors 408
Dandridge, A., Tveten, A.B., Davis, C.M., and Giallorenzi, T.G. see Tveten, A.B.
Darby, B.J., Gunton, D.J., Lewis, M.F., and Newton, C.O. Efficient miniature s.a.w. convolver 726
Darwish, M., and Board, K. Switching in m.i.s.m. and m.i.s.i.m. structures 577
Das, N., and Chowdhury, S.K. Microstrip rectangular resonators on ferrimagnetic substrates 817
Das, S.R., Chen, Z., and Dai, Y.L. Easily testable sequential machines with extra inputs and extra outputs 119
Davey, J.E., Christou, A., Anderson, W.T. Jr., Bark, M.L., and Anand, Y. see Christou, A.
Davies, D.E.N., and Vakil, S.M. Field probe for measuring both amplitude and phase of antenna radiation patterns 873
Davies, L.W., Lam, Y.W., and Green, M.A. see Lam, Y.W.
Davis, C.M., Tveten, A.B., Dandridge, A., and Giallorenzi, T.G. see Tveten, A.B.
Daws, D.C., and Jones, E.V. Hardware-efficient bit sequential adders and multipliers using mode-controlled logic 434
Day, C.R., Ainslie, B.J., Rush, J., and Beales, K.J. see Ainslie, B.J.
Day, H., Anand, Y., and Christou, A. see Anand, Y.
De Albuquerque, A.A., and Lind, L.F. see Lind, L.F.
de Cremoux, B., Hirtz, J.P., Duchemin, J.P., Hirtz, P., Pearsall, T., and Bonnet, M. see Hirtz, J.P.
De Jersey, D.E. Imaginary Smith chart for evanescent-mode structures 93
De Marchis, G., Daino, B., and Piazzolla, S. see Daino, B.
De Murcia, M., Bonnafe, J., Castagne, M., Romestan, J., and Fillard, J.P. see Bonnafe, J.
Del Alamo, J., Eguren, J., and Luque, A. see Eguren, J.
Delagebeaudeuf, D., Delescluse, P., Etienne, P., Laviron, M., Chaplart, J., and Linh, N.T. Two-dimensional electron gas m.e.s.f.e.t. structure 667
Delescluse, P., Delagebeaudeuf, D., Etienne, P., Laviron, M., Chaplart, J., and Linh, N.T. see Delagebeaudeuf, D.
Delogne, P., and Adant, J.M. see Adant, J.M.
Delogne, P., and Sobieski, P. see Sobieski, P.
Dennis, M.R., and Fox, M. see Fox, M.
Dentai, A.G., Campbell, J.C., Burrus, C.A., and Ferguson, J.F. see Campbell, J.C.
Dentai, A.G., Lee, T.P., and Burrus, C.A. see Lee, T.P.
Dentai, A.G., Lee, T.P., Burrus, C.A., and Ogawa, K. see Lee, T.P.
Depey, M., and Roulston, D.J. see Roulston, D.J.
Detchev, D., Grantcharov, K., Borissov, M., Spassov, L., and Yossifov, E. see Grantcharov, K.
Devlin, W.J. R.F. sputtered Au-Mo contacts to n-GaAs 92
Dewey, R.J. High-gain flat-plate phase-monopulse antenna 30
DeWinter, J.C., Kaminow, I.P., Nahory, R.E., Pollack, M.A., and Stulz, L.W. see Kaminow, I.P.
DeWinter, J.C., Leheny, R.F., Nahory, R.E., Pollack, M.A., Ballman, A.A., Beebe, E.D., and Martin, R.J. see Leheny, R.F.
Dexter, K., Alder, C.J., Cattell, A., Dixon, M., and Kirton, J. see Alder, C.J.
Deyhimy, I., Liu, Y.Z., Anderson, R.J., and Tomasetta, L.R. see Liu, Y.Z.
Dharmadasa, I.M., Roberts, G.G., and Petty, M.C. Cadmium telluride/Langmuir film photovoltaic structures 201
Dieulesaint, E., Mattiocco, F., and Royer, D. see Mattiocco, F.
Dieulesant, E., Ash, E.A., and Rakouth, H. see Ash, E.A.
Digiuseppe, N.J., Olsen, G.H., and Zamerowski, T.J. see Olsen, G.H.
Dixon, M., Alder, C.J., Cattell, A., Dexter, K., and Kirton, J. see Alder, C.J.
Dobrovolsky, A.A., Lemanov, V.V., Sherman, A.B., Gal'Perin, Yu.M., and Kozub, V.I. Nonlinear interaction of s.a.w.s. in piezoelectric crystals with secondary electrons 243
Dobrovolsky, A.A., Sherman, A.B., and Lemanov, V.V. see Sherman, A.B.
Dobson, R.M., McMahon, R.A., Ahmed, H., and Speight, J.D. see McMahon, R.A.
Doerbeck, F.H., Yuan, H.T., and McLevige, W.V. see Yuan, H.T.

Dohsen, M., Kato, Y., Kasahara, J., and Watanabe, N. see Kato, Y.
Doi, K., Minowa, J., Fujii, Y., Nagata, Y., and Aoyama, T. see Minowa, J.
Donaghy, F., Sabine, P.V.H., and Irving, D. see Sabine, P.V.H.
Doring, K. -H., and Seebald, E. High transformation ratio for impedance matching with a radial line 50
Dos Santos, A.F., and Carpentier, M.P. see Carpentier, M.P.
Drajić, D., and Petrović, G. Power spectra of d.p.s.k. signals for data transmission 251
Drajić, D., and Petrović, G. Power spectra of HDBn signals 289
Drummond, T.J., Morkoc, H., Witkowski, L.C., Stanchak, C.M., Cho, A.Y., and Streetman, B.G. see Morkoc, H.
Duchemin, J.P., Hirtz, J.P., Hirtz, P., de Cremoux, B., Pearsall, T., and Bonnet, M. see Hirtz, J.P.
Duchemin, J.P., Hirtz, J.P., Larivain, J.P., Pearsall, T.F., and Bonnet, M. see Hirtz, J.P.
Duguay, M.A., and Damen, T.C. see Damen, T.C.
Durand, G., Cathelin, M., Gavant, M., and Rocchi, M. see Cathelin, M.
Durney, C.H., Massoudi, H., and Iskander, M.F. see Massoudi, H.
Dürr, W., Sinclair, D.A., and Ash, E.A. High resolution acoustic probe 805
Durrani, T.S., and Chapman, R. I.I.R. digital filter design using constrained optimisation techniques 843
Durvaux, M. Filters using digital techniques to improve operation of a fast digital phasemeter 447
Dutta, N.K., Nelson, R.J., and Barnes, P.A. Temperature dependence of threshold and electrical characteristics of InGaAsP-InP d.h. lasers 653
Dutta Roy, S.C., and Kapur, N. see Kapur, N.

E

Eastman, L.F., Stall, R., Woodard, D., Dandekar, N., Wood, C.E.C., Shur, M.S., and Board, K. Ballistic electron motion in GaAs at room temperature 524
Eastman, L.F., Malik, R.J., Aucoin, T.R., Ross, R.L., Board, K., and Wood, C.E.C. see Malik, R.J.
Eastman, L.F., and Shur, M.S. see Shur, M.S.
Eastman, L.F., Stall, R.A., Wood, C.E.C., and Kirchner, P.D. see Stall, R.A.
Ebato, T., Kajiwara, T., and Kobayashi, S. Mechanical fibre optic switching using p.v.d.f. bimorph 829
Ebisawa, F., Nakagawa, K., and Takeshima, M. see Nakagawa, K.
Edahiro, T., Kawachi, M., Sudo, S., and Nagai, H. Transmission characteristics of 116.3 km and 65.1 km graded-index v.a.d. fibres at 1.55 μm and 1.3 μm 478
Edahiro, T., Moriyama, T., Fukuda, O., Sanada, K., Inada, K., and Chida, K. see Moriyama, T.
Edahiro, T., Okamoto, K., Sasaki; Y., Miya, T., and Kawachi, M. see Okamoto, K.
Edahiro, T., Sudo, S., Kawachi, M., and Chida, K. see Sudo, S.
Edahiro, T., Tomaru, S., and Kawachi, M. see Tomaru, S.
Eddolls, D.V., Bickley, W.P., and Maher, E.F. see Bickley, W.P.
Eguren, J., Del Alamo, J., and Luque, A. Optimisation of p^+ doping level of n^+-p-p^+ bifacial b.s.f. solar cells by ion implantation 633
Eickhoff, W. In-line fibre-optic polariser 762
Eilenberger, D.J., Lin, C., Liu, P.L., Damen, T.C., and Hartman, R.L. see Lin, C.
Ektare, A.B., and Mital, D.P. Multiplexer logic circuit design using cubical complexes 495 e718
Ektare, A.B., and Mital, D.P. Probabilistic approach to multiplexer logic circuit design 686
El-Dokany, I., El-Konyaly, E.H., and Sobaih, A. see El-Konyaly, E.H.
El-Konyaly, E.H., Sobaih, A., and El-Dokany, I. Solution of $X=A_1X+XA_2+D$, $X(O)=C$ and receding horizon problem 657
El-Masry, E.I. Strays-insensitive active switched-capacitor biquad 480
El-Sabbahy, A.N., Adams, A.R., Tatham, H.L., Hayes, J.R., and Greene, P.D. see Adams, A.R.
Elliott, R.D., and Clarricoats, P.J.B. Corrugated waveguide monopulse feed 324
Elze, G., Baack, C., Enning, B., and Walf, G. see Baack, C.
Emerson, N.G., and Sealy, B.J. Laser annealing of low dose Se-implanted GaAs studied by d.l.t.s. 512
Emura, M., Fukui, Y., and Yoneda, S. New frequency division circuit using b.b.d. 530
Emura, M., Fukui, Y., and Yoneda, S. Sampled-data recursive integrator for ultra-low-frequency wideband phase shifter 330
Eng, S.T., and Tell, R. see Tell, R.
Eng, S.T., and Torphammar, P. see Torphammar, P.
Engan, H., Ingebrigtsen, K.A., and Rønnekleiv, A. Design of s.a.w. convolver for processing m.s.k. modulated waveforms 908
Enning, B. Retiming circuit for n.r.z. signals in 1.12 Gbit/s optical transmission system 815
Enning, B., Baack, C., Elze, G., and Walf, G. see Baack, C.
Eriksrud, M., Lauritzen, S., and Ryen, N. Backscatter attenuation measurements in graded index fibres 877
Etienne, P., Delagebeaudeuf, D., Delescluse, P., Laviron, M., Chaplart, J., and Linh, N.T. see Delagebeaudeuf, D.
Ettinger, G.M., and Shooter, L.T. Continuously variable solid state delay circuits 857
Evans, F.J., and Schizas, C. see Schizas, C.
Eve, M. Bandwidth of long monomode fibre links in the presence of weak mode coupling 80
Eykhoff, P. System identification: approach to a coherent picture through template functions 502

F

Faber, W. Terminations for magnetostatic waves 452
Facq, P., Fournet, P., and Arnaud, J. Observation of tubular modes in multimode graded-index optical fibres 648
Fallmann, W., Olcaytug, F., and Riedling, K. see Olcaytug, F.
Faltin, L. Time scale independent signal transmission 439
Fanelli, N., and Bastida, E.M. see Bastida, E.M.
Fank, F.B., Crowley, J.D., Sowers, J.J., and Janis, B.A. see Crowley, J.D.
Farence, J., Guillon, P., and Garault, Y. see Guillon, P.
Farnell, G.W., and Jen, C.K. Planar acoustic microscope lens using Rayleigh to compressional conversion 541
Farrell, P.G., and Makarious, A.H. see Makarious, A.H.
Faruque, S.M., Vlach, J., and Viswanathan, T.R. Switched-capacitor biquads based on switched-capacitor transconductance 63
Fauquembergue, R., Zimmermann, J., Charef, M., and Constant, E. see Zimmermann, J.
Favennec, P.N., Henry, L., Gauneau, M., L'Haridon, H., and Pelous, G. Open ampoule diffusion in InP 832
Favre, F., and Le Guen, D. High frequency stability of laser diode for heterodyne communication systems 709
Feldmann, M., and Henaff, J. New charge transfer recursive filter 585
Feldmann, M., and Henaff, J. see Henaff, J.
Ferguson, J.F., Campbell, J.C., Dentai, A.G., and Burrus, C.A. see Campbell, J.C.
Fernando, K.V.M., and Nicholson, H. Double-sided least-squares problem with diagonal constraints 82
Fernando, K.V.M., and Nicholson, H. Hierarchical and parallel processing structure of two-dimensional systems 274
Few, I.S., and Conradi, J. see Conradi, J.
Fiddyment, P.J., Westbrook, L.D., and Robson, P.N. see Westbrook, L.D.
Fidler, J.K. Pole sensitivity of all-pole lowpass LC ladder networks 856
Filensky, W., Ponse, F., and Beneking, H. Applications of dual-gate GaAs m.e.s.f.e.t.s. for fast pulse shape regeneration systems 214
Filensky, W., Beneking, H., and Ponse, F. see Beneking, H.
Fillard, J.P., Bonnafe, J., Castagne, M., Romestan, J., and De Murcia, M. see Bonnafe, J.
Flemming, M.A. Compact microstrip bandpass filter using both λ/2 and λ/4 resonators 915
Flood, J.E., and Fonseca, J.M. Improved digital automatic gain control for p.c.m. signals 589
Flood, J.E., and Fonseca, J.M. New digital automatic gain control for p.c.m. signals 96
Fonseca, J.M., and Flood, J.E. see Flood, J.E.
Förg, P.N., and Freyer, J. Ka-band self-oscillating mixers with Schottky Baritt diodes 827
Foster, S.J., and Redwood, M. Narrow-band frequency discriminator using two monolithic crystal filters 104
Fouad Hanna, V. Finite boundary corrections to coplanar stripline analysis 604
Fournet, P., Facq, P., and Arnaud, J. see Facq, P.
Fox, M., and Dennis, M.R. Index matching fluids for long wavelengths (1.2-1.6 μm) fibre-optic applications (Comment) 651
Foy, P.W., Capasso, F., Logan, R.A., Sumski, S., and Manchon, D.D. see Capasso, F.
Foy, P.W., Cho, A.Y., Casey, Jun, H.C., and Radice, C. see Cho, A.Y.
France, P.W. Novel proof-tester for optical glass fibres 117
Frangakis, G. Fast binary logarith, computing circuit for binary numbers less than one 574
Frangoulis, E., Turner, L.F., and Alcaim, A. see Turner, L.F.
Fray, C., Khayata, N., and Papiernik, A. Reflection and radiation of flanged circular dielectric rod 740
Freeman, W., and Hebden, S.M. Properties of a simple noise-sequence generator 55
Frey, J., Bernard, J., Lee, K.F., and Gibbons, J.F. see Bernard, J.
Freyer, J., Kasper, E., and Barth, H. Pulsed V-band m.b.e. Si Impatt diodes 865
Freyer, J., and Förg, P.N. see Förg, P.N.
Fuchigami, T., Kojima, N., Ohmura, M., Tomita, N., and Yamamoto, H. New star quad symmetrical cable 204
Fujii, Y., Minowa, J., Nagata, Y., Aoyama, T., and Doi, K. see Minowa, J.
Fujii, Y., Watanabe, R., and Nosu, K. see Watanabe, R.
Fujisawa, K., Yamamoto, Y., Hagiwara, Y., and Iwai, T. see Yamamoto, Y.
Fukuda, O., Moriyama, T., Sanada, K., Inada, K., Edahiro, T., and Chida, K. see Moriyama, T.
Fukuda, Y., Inoue, T., and Ueno, F. see Inoue, T.
Fukui, Y., Emura, M., and Yoneda, S. see Emura, M.
Fursin, G.I. Modulating transistor: a new class of semiconductor device 662
Fursin, G.I., and Skorik, V.A. see Skorik, V.A.

Furuya, K., Kubota, M., Oohara, T., and Suematsu, Y. see Kubota, M.
Furuya, K., Sakakibara, Y., Utaka, K., and Suematsu, Y. see Sakakibara, Y.

G

Gagnepain, J.J., Planat, M., Theobald, G., and Siffert, P. see Planat, M.
Gaitanis, N., and Halatsis, C. Negative fail-safe sequential circuits 615
Gal'Perin, Yu.M., Dobrovolsky, A.A., Lemanov, V.V., Sherman, A.B., and Kozub, V.I. see Dobrovolsky, A.A.
Garault, Y., Guillon, P., and Farence, J. see Guillon, P.
Garber, F.D., and Pursley, M.B. Optimal phases of maximal length sequences for asynchronous spread-spectrum multiplexing 756
Garcia-Lopez, J.A., and Casares-Giner, V. Optimum antenna separation for space diversity in l.o.s. radio links over flat ground 717
Gardiner, J.G., and Abuelma'atti, M.T. see Abuelma'atti, M.T.
Gardner, K., and Johnson, P.T. Automatic aperture performance measurement for high speed analogue-digital convertors 741
Garrigues, M., Pedron, T.P., Lanteri, J.P., and Urgell, J.J. see Pedron, T.P.
Gauneau, M., Favennec, P.N., Henry, L., L'Haridon, H., and Pelous, G. see Favennec, P.N.
Gaur, P.B.L., and Prasad, V.C. see Prasad, V.C.
Gavant, M., Cathelin, M., Durand, G., and Rocchi, M. see Cathelin, M.
Gelin, Ph., Toutain, S., and Legier, J.F. New analytical model for rectangular image guide 442
Gelsthorpe, R.V., and Collins, P.Q. Increasing power input to a single solar power satellite rectenna by using a pair of satellites 311
Gen-ei, K., Ito, H., and Inaba, H. see Ito, H.
Gentil, P. Simple method for evaluating electronic properties at silicon-sapphire interface 617
Gertner, E.R., and Williams, G.M. see Williams, G.M.
Ghanderi, M.B., and Temes, G.C. see Temes, G.C.
Gharavi, H. Block adaptive prediction of colour television signals 226
Ghatak, A.K., Pal, B.P., and Kumar, A. see Pal, B.P.
Ghobrial, S.I. Effect of hydroscopic water on dielectric constant of dust at X-band 393
Ghobrial, S.I., and Jervase, J.A. see Jervase, J.A.
Giallorenzi, T.G., Dandridge, A., and Miles, R.O. see Dandridge, A.
Giallorenzi, T.G., Dandridge, A., Tveten, A.B., Sigel, G.H. Jr., and West, E.J. see Dandridge, A.
Giallorenzi, T.G., Tveten, A.B., Dandridge, A., and Davis, C.M. see Tveten, A.B.
Gibbons, J.F., Bernard, J., Frey, J., and Lee, K.F. see Bernard, J.
Gibbs, A.J., Nicholson, G., and Potter, P.G. Barrage technique for measurement of p.c.m. regenerator section loss limits 814
Gielkens, F.J.J., Herben, M.H.A.J., and Middelkoop, R. see Herben, M.H.A.J.
Glass, H.L., and Adkins, L.R. see Adkins, L.R.
Gloge, D. Effect of chromatic dispersion on pulses of arbitrary coherence e240
Gloge, D., Ogawa, K., and Cohen, L.G. Baseband characteristics of long-wavelength l.e.d. systems 366
Gobet, Cl.-A., and Knob, A. Noise generated in switched capacitor networks 734
Gogioso, L., Bianco, B., Corana, A., Ridella, S., and Parodi, M. see Bianco, B.
Goodfellow, R.C., and Abram, R.A. see Abram, R.A.
Goodman, J.W., Rawson, E.G., and Norton, R.E. see Rawson, E.G.
Goodman, K., and Zurada, J. see Zurada, J.
Goodyear, C.C., and Ching, P.C. see Ching, P.C.
Gotoh, H., Hamasaki, Y., Katoh, M., and Takeuchi, S. see Hamasaki, Y.
Gottlieb, M., and Brandt, G.B. Integrated optic a.d. convertor based on bulk acousto-optic interaction 359
Graffeuil, J., Sautereau, J.F., Tantrarongroj, K., and Rossel, P. see Sautereau, J.F.
Grant, P.M., Behar, D., Olaisen, H., Kino, G.S., and Corl, D. see Behar, D.
Grantcharov, K., Borissov, M., Detchev, D., Spassov, L., and Yossifov, E. Investigations on a new force-frequency measuring gauge 71
Grasso, G., Costa, B., Sordo, B., Menaglia, U., and Piccari, L. see Costa, B.
Grau, G.K., and Leminger, O.G. see Leminger, O.G.
Grau, G.K., and Sauter, E.G. see Sauter, E.G.
Gray, M.H., Rosiewicz, A., Irven, J., Titchmarsh, J.G., and Black, P.W. see Rosiewicz, A.
Green, M.A., Lam, Y.W., and Davies, L.W. see Lam, Y.W.
Greene, P.D., Adams, A.R., Tatham, H.L., Hayes, J.R., and El-Sabbahy, A.N. see Adams, A.R.
Greene, P.D., Hayes, J.R., and Adams, A.R. see Hayes, J.R.
Groen, H.B. Line coding and burst transmission in the local network 165
Grote, N., Beneking, H., Roth, W., and Svilans, M.N. see Beneking, H.
Guillon, P., Garault, Y., and Farence, J. Dielectric resonator dual modes filter 646
Gulyaev, Yu. V., Kotelyansky, I.M., Medved, A.V., and Mishkinis, R.A. S.A.W. monolithic acoustoelectronic oscillator 114
Gunton, D.J. Combined triple-transit and bulk-wave suppression in s.a.w. delay line 149 e240
Gunton, D.J., Darby, B.J., Lewis, M.F., and Newton, C.O. see Darby, B.J.
Guryanov, B. Transient response of sample-and-hold circuits 123
Guttmann, J., and Weidel, E. see Weidel, E.

H

Ha, Y.K., and Witten, I.H. Stability of linear predictive descriptions of curves used in handwriting 909
Haddon, J., Lo, P., Moulsley, T.J., and Vilar, E. Spectra of amplitude scintillations in X-band satellite downlink 619
Haddon, J., Lo, P., Moulsley, T.J., and Vilar, E. Statistical intensity of amplitude scintillations on earth-space X-band link 546
Hafich, M., Kawanishi, H., Lenz, B., and Petersen, P. see Kawanishi, H.
Haga, H., Izutsu, M., and Sueta, T. see Izutsu, M.
Hagiwara, Y., Yamamoto, Y., Iwai, T., and Fujisawa, K. see Yamamoto, Y.
Halatsis, C., and Gaitanis, N. see Gaitanis, N.
Hall, P.S. New wideband microstrip antenna using log-periodic technique 127
Halme, S.J., Saijonmaa, J., and Sharma, A.B. see Saijonmaa, J.
Halme, S.J., Sharma, A.B., and Saijonmaa, J. see Sharma, A.B.
Hamasaki, Y., Gotoh, H., Katoh, M., and Takeuchi, S. OPSEF: An optical sensor for measurement of high electric field intensity 406
Han, K.W., Chen, T.C., and Chang, C.Y. see Chen, T.C.
Hanawa, F., Sudo, S., Kawachi, M., and Nakahara, M. Fabrication of completely OH-free v.a.d. fibre 699
Hanawa, F., Nakahara, M., Chida, K., Sudo, S., and Horiguchi, M. see Nakahara, M.
Hang, C.C. Effect of dead time on closed-loop regulation 133
Hannington, G. Improvements to binary floating-point digital differential analysers 337
Harada, T., Watanabe, R., Nosu, K., and Kita, T. see Watanabe, R.
Harmer, A.L., and Dähne, C. see Dähne, C.
Harris, D.J., and Teo, T.M. Measurement of extinction cross-section of single particles at 100 GHz 500
Harris, J.J., and Woodcock, J.M. Low noise GaAs varactor and mixer diodes prepared by molecular beam epitaxy 317
Harrop, P., and Tsironis, C. see Tsironis, C.
Hart, B.L. Current mirror saturation sensing technique 927
Hart, B.L. Early voltage uniqueness test for bipolar junction transistors 703
Hart, B.L., and Barker, R.W.J. see Barker, R.W.J.
Hartemann, P., and Castera, J.P. see Castera, J.P.
Hartman, R.L., Lin, C., Liu, P.L., Damen, T.C., and Eilenberger, D.J. see Lin, C.
Hartog, A.H., Conduit, A.J., and Payne, D.N. see Conduit, A.J.
Hasegawa, F., Aono, Y., and Higashisaka, A. see Aono, Y.
Hasegawa, F., and Higashisaka, A. see Higashisaka, A.
Hashimoto, K., Okada, K., Shibata, T., and Nagaki, Y. see Okada, K.
Hashimoto, K., Sano, K., and Okada, K. see Sano, K.
Hashimoto, K-Y., Yoshida, M., Yamaguchi, M., and Kogo, H. Stress dependences of longitudinal wave velocity in magnetostrictive metallic-glass ribbon 425
Hashimoto, M. Cutoff frequencies of vector wave modes in cladded inhomogeneous optical fibre 806
Hashimoto, M. Vector wave characteristics of radially inhomogeneous waveguide modes 494
Haslett, J.W., Rao, M.K.N., and Bruton, L.T. Monolithic v.c.c.s. for high-frequency RC active filters 175 e444
Hauth, W. Applications of scattering matrix for development of microwave mixers 501
Hayes, J.R., Adams, A.R., and Greene, P.D. Mobility of holes in the quaternary alloy $In_{1-x}Ga_xAs_yP_{1-y}$ 282
Hayes, J.R., Adams, A.R., Tatham, H.L., El-Sabbahy, A.N., and Greene, P.D. see Adams, A.R.
Haykin, S., Reilly, J., and Taylor, D. New realisation of maximum likelihood receiver for low-angle tracking radar 288
Healey, P., and Hensel, P. Optical time domain reflectometry by photon counting 631
Hebden, S.M., and Freeman, W. see Freeman, W.
Heime, K., Arnold, N., and Daembkes, H. see Arnold, N.
Heime, K., and Tegude, F.J. see Tegude, F.J.
Henaff, J., and Feldmann, M. S.A.W. implementation of whitening filters for satellite digital communications 124
Henaff, J., and Feldmann, M. see Feldmann, M.
Hendry, A., Antar, Y.M.M., Schlesak, J.J., Olsen, R.L., and Bérubé, R.C. see Antar, Y.M.M.
Henry, L., Favennec, P.N., Gauneau, M., L'Haridon, H., and Pelous, G. see Favennec, P.N.
Hensel, P., and Healey, P. see Healey, P.
Henshall, G.D., and Thompson, G.H.B. see Thompson, G.H.B.
Herben, M.H.A.J., Middelkoop, R., and Gielkens, F.J.J. Stationary phase method for far-field computation of defocused reflector antennas 519
Herben, M.H.A.J., Van Ommeren, M.J.S., and Arnbak, J. see Van Ommeren, M.J.S.
Herbst, D., and Hosticka, B.J. Novel bottom-plate stray-insensitive voltage inverter switch 636
Hershey, J.E. Implementation of mitre public key cryptographic system 930
Herwig, R. Ion beam oxidation of Nb-based Josephson junctions 850

Hesketh, T. Disturbance rejection and multivariable self-tuning controllers 404
Hess, K., Chin, R., Holonyak, N. Jun., Stillman, G.E., and Tang, J.Y. see Chin, R.
Hess, K., Shichijo, H., and Stillman, G.E. see Shichijo, H.
Hickin, J. Approximate aggregation for linear multivariable systems 518
Hickin, J. Mixed time/frequency domain approach to model reduction (Comment) 338
Hicks, R.G., and Khan, P.J. Numerical technique for determining pumped nonlinear device waveforms 375
Higashiguchi, M., Hotate, K., Yoshida, Y., and Niwa, N. see Hotate, K.
Higashisaka, A., and Hasegawa, F. Estimation of fringing capacitance of electrodes on s.i. GaAs substrate 411
Higashisaka, A., Aono, Y., and Hasegawa, F. see Aono, Y.
Higuchi, H., Murotani, T., Oomura, E., Namizaki, H., and Susaki, W. see Murotani, T.
Hikita, M., Kinoshita, Y., Kojima, H., and Tabuchi, T. Resonant s.a.w. filter using surface shear wave mode on $LiTaO_3$ substrate 446
Hikita, M., Kinoshita, Y., Kojima, H., and Tabuchi, T. Sidelobe suppression of s.a.w. resonant filter using twin-turn reflectors 784
Hikita, M., Kojima, H., Kinoshita, Y., and Tabuchi, T. see Kojima, H.
Hill, D.R. Circularly polarised radiation from narrow wall slots in rectangular waveguide 559
Hill, D.R. Reduction of sidelobes in uniformly excited arrays with element pattern control 134
Hinkov, V.P., Strashilov, V.L., and Bransalov, K.P. see Strashilov, V.L.
Hirose, Y., and Ogura, Y. Model for return-beam-induced noise generation in GaAlAs semiconductor lasers 202
Hirtz, J.P., Duchemin, J.P., Hirtz, P., de Cremoux, B., Pearsall, T., and Bonnet, M. $Ga_xIn_{1-x}As_yP_{1-y}/InP$ d.h. laser emitting at 1.15 μm grown by low-pressure metalorganic c.v.d. 275
Hirtz, J.P., Larivain, J.P., Duchemin, J.P., Pearsall, T.P., and Bonnet, M. Growth of $Ga_{0.47}In_{0.53}As$ on InP by low-pressure m.o. c.v.d. 415
Hirtz, P., Hirtz, J.P., Duchemin, J.P., de Cremoux, B., Pearsall, T., and Bonnet, M. see Hirtz, J.P.
Hodgart, M.S., Szajnowski, W.J., and Stephens, K.G. see Szajnowski, W.J.
Hoh, K. Photoacoustic effect in laser annealing 931
Holonyak, N. Jun., Chin, R., Stillman, G.E., Tang, J.Y., and Hess, K. see Chin, R.
Hooper, R.C., Smith, D.R., Ahmad, K., Jenkins, D., Mabbitt, A.W., and Nicklin, R. see Smith, D.R.
Horiguchi, M., Nakahara, M., Chida, K., Hanawa, F., and Sudo, S. see Nakahara, M.
Horiguchi, M., Sudo, S., Okazaki, H., and Nakahara, M. see Sudo, S.
Hosticka, B.J., and Herbst, D. see Herbst, D.
Hosticka, B.J., von Gruningen, D.C., and Brugger, U.W. see von Gruningen, D.C.
Hotate, K., Yoshida, Y., Higashiguchi, M., and Niwa, N. Rotation detection by optical fibre laser gyro with easily introduced phase-difference bias 941
Huertas, J.L. Circuit implementation of current conveyor 225
Huertas, J.L., and Rodriguez-Vazquez, A. see Rodriguez-Vazquez, A.
Hullett, J.L., and Jeffery, R.D. see Jeffery, R.D.
Humbel, W.D., and Meiksin, Z.H. see Meiksin, Z.H.
Hutchinson, A., Capasso, F., Logan, R.A., and Manchon, D.D. see Capasso, F.
Huynh, H.T., Cung, T.T., and Lecours, M. see Cung, T.T.

I

Ibrahim, M.F., Parsons, J.D., and Samuel, R.J. see Parsons, J.D.
Iga, K., and Miller, B.I. C.W. operation of GaInAsP/InP laser with chemically etched mirror 830
Iga, K., and Miller, B.I. GaInAsP/InP laser with monolithically integrated monitoring detector 342
Ilumoka, A., and Spence, R. Statistical approach to reduction of circuit performance variability 761
Imoto, N., Kawana, A., Miya, T., and Tsuchiya, H. see Kawana, A.
Inaba, H., Ito, H., and Gen-ei, K. see Ito, H.
Inaba, H., Ito, H., and Ogawa, Y. see Ito, H
Inaba, H., Ito, H., and Yokoyama, H. see Ito, H.
Inada, K., Moriyama, T., Fukuda, O., Sanada, K., Edahiro, T., and Chida, K. see Moriyama, T.
Inada, T., Sugiyama, T., Okano, N., and Ishikawa, Y. Pulsed electron-beam annealing of phosphorus-implanted silicon 54
Inagaki, N., Nakahara, M., Sudo, S., Yoshida, K., Shibuya, S., Kokura, K., and Kuroha, T. see Nakahara, M.
Ingebrigtsen, K.A., Engan, H., and Rønnekleiv, A. see Engan, H.
Inggs, M.R., and Williams, N. Thick-film fabrication techniques for millimetre-wave dielectric waveguide integrated circuits 245
Inoue, K., Washio, K., and Kishida, S. see Washio, K.
Inoue, K., Washio, K., and Tanigawa, T. see Washio, K.
Inoue, T., and Ueno, F. New bilinear switched-capacitor immittance convertor circuit 285
Inoue, T., and Ueno, F. New switched-capacitor immittance converter using operational amplifier leapfrog structure 266
Inoue, T., and Ueno, F. Switched-capacitor immittance convertors using a single operational amplifier 770
Inoue, T., Ueno, F., and Fukuda, Y. Brune-section simulation circuits using two operational amplifiers 781
Irven, J., Rosiewicz, A., Gray, M.H., Titchmarsh, J.G., and Black, P.W. see Rosiewicz, A.
Irving, D., Sabine, P.V.H., and Donaghy, F. see Sabine, P.V.H.
Ishi, T., Mitsui, Y., Kobiki, M., Wataze, M., Segawa, K., and Otsubo, M. see Mitsui, Y.
Ishibashi, T., Takada, T., and Makimura, T. see Takada, T.
Ishida, S., Mizutani, T., Kato, N., Osafune, K., and Ohmori, M. see Mizutani, T.
Ishikawa, R., Kaede, K., Nishimoto, H., Minemura, K., and Matsushita, S. Kaleidoscope micro-optic star coupler 248
Ishikawa, Y., Inada, T., Sugiyama, T., and Okano, N. see Inada, T.
Iskander, M.F., Massoudi, H., and Durney, C.H. see Massoudi, H.
Ismail, M.G.B., and Clarke, R.J. New processing technique for digital facsimile transmission 355
Ismail, M.G.B., and Steele, R. Adaptive pel location coding for bilevel facsimile signals 361
Itaya, Y., Arai, S., Asada, M., Suematsu, Y., Tanbun-ek, T., and Kishino, K. see Arai, S.
Ito, H., Gen-ei, K., and Inaba, H. Active Q-switching of lateral field coupling control d.h. laser 846
Ito, H., Ogawa, Y., and Inaba, H. Integrated astable optical multivibrator using Mach-Zehnder interferometric optical switches 593
Ito, H., Yokoyama, H., and Inaba, H. Bandwidth limited picosecond optical pulse generation from actively mode-locked AlGaAs diode laser 620
Ito, Y., Maekawa, T., Yamamoto, T., and Tanikawa, K. C.C.D./C.M.O.S. transversal filter using switched-capacitor technique for signal detection 724
Iwai, T., Yamamoto, Y., Hagiwara, Y., and Fujisawa, K. see Yamamoto, Y.
Iwane, G., Takahashi, S., and Saito, H. see Takahashi, S.
Izutsu, M., Haga, H., and Sueta, T. Semiconductor laser output modulated in GHz frequency region observed by image tube streak camera 531

J

Jack, M.A., Kapur, N., and Mavor, J. see Kapur, N.
Jacobsen, G., and Ramskov Hansen, J.J. Detailed error estimates for first order WKB calculation method 540
Jacques, A., d'Auria, L., Combemale, Y., and Moronvalle, C. see d'Auria, L.
James, G.L., and Thomas, B. MacA. Comparison of G/T between dual-reflector and primary-focus antennas 286
Jamuar, S.S., and Pyara, V.P. see Pyara, V.P.
Janis, B.A., Crowley, J.D., Sowers, J.J., and Fank, F.B. see Crowley, J.D.
Janson, M., and Josefsson, A. Method for reproducible l.p.e. growth of GaInAsP 879
Jarem, J.M., and Sheikh, N.J. Pattern synthesis of cylindrical slot antenna 383
Jayant Baliga, B. Bipolar operation of power junction field effect transistors 300
Jeffery, R.D., and Hullett, J.L. N-point processing of optical fibre backscatter signals 822
Jen, C.K., and Farnell, G.W. see Farnell, G.W.
Jenkins, D., Smith, D.R., Hooper, R.C., Ahmad, K., Mabbitt, A.W., and Nicklin, R. see Smith, D.R.
Jenkins, W.K. Complex residue number arithmetic for high-speed signal processing 660
Jennings, B.R., and Ridler, P.J. Electrofluorescent colloid light switch 833
Jenssen, Ø., Justnes, B.O., and Stueflotten, S. New line code for digital subscriber loop 847
Jervase, J.A., and Ghobrial, S.I. Effect of profile errors with large correlation diameter on axisymmetric antenna cross-polarisation 663
Jeunhomme, L., and Monerie, M. Polarisation-maintaining single-mode fibre cable design 921
Jeunhomme, L., Monerie, M., and Lamouler, P. see Monerie, M.
Johnson, P.T., and Gardner, K. see Gardner, K.
Jones, E.V., and Daws, D.C. see Daws, D.C.
Joo, C-S., Ra, J-W., and Shin, S-Y. Edge diffraction by right-angled dielectric wedge 934
Josefsson, A., and Janson, M. see Janson, M.
Jovanović, V., and Rabrenović, D. see Rabrenović, D.
Judd, G.W., and Chapman, C.W. see Chapman, C.W.
Justnes, B.O., Jenssen, Ø., and Stueflotten, S. see Jenssen, Ø.

K

Kaede, K., Ishikawa, R., Nishimoto, H., Minemura, K., and Matsushita, S. see Ishikawa, R.
Kajiwara, T., Ebato, T., and Kobayashi, S. see Ebato, T.
Kalouptsidis, N., Carayannis, G., and Manolakis, D. see Carayannis, G.
Kaminow, I.P., Nahory, R.E., Pollack, M.A., Stulz, L.W., and DeWinter, J.C. Single-mode c.w. ridge-waveguide laser emitting at 1.55 μm e75
Kanbe, H., Susa, N., Nakagome, H., and Ando, H. InGaAs avalanche photodiode with InP p-n junction 163

Kaneda, T., Osaka, F., Nakazima, K., Sakurai, T., and Susa, N. see Osaka, F.
Kano, H., and Sugiyama, K. 2.0 μm c.w. operation of GaInAsSb/GaSb d.h. lasers at 80 K 146
Kaplan, B.Z. Certain ineffective parametric interactions 26
Kaplan, B.Z. Parametric interactions when resonator reactances are varied in antiphase 343
Kapur, N., and Dutta Roy, S.C. Implementation of prime transform algorithm using c.c.d. programmable transversal filter 809
Kapur, N., Mavor, J., and Jack, M.A. Discrete cosine transform processor using a c.c.d. programmable transversal filter 139
Karnik, E., and Kovnovich, S. see Kovnovich, S.
Kasahara, J., Kato, Y., Dohsen, M., and Watanabe, N. see Kato, Y.
Kashyap, R., and Reeve, M.H. Single-ended fibre strain and length measurement in frequency domain 689
Kasper, E., Freyer, J., and Barth, H. see Freyer, J.
Katayama, Y., Kurokawa, T., and Yoshizawa, T. see Kurokawa, T.
Kato, N., Mizutani, T., Ishida, S., Osafune, K., and Ohmori, M. see Mizutani, T.
Kato, Y., Dohsen, M., Kasahara, J., and Watanabe, N. Planar GaAs normally-off j.f.e.t. for high speed logic circuits 821
Katoh, M., Hamasaki, Y., Gotoh, H., and Takeuchi, S. see Hamasaki, Y.
Katz, J., Bar-Chaim, N., Margalit, S., and Yariv, A. AlGaAs heterostructure injection laser s.c.r. 840
Kawachi, M., Edahiro, T., Sudo, S., and Nagai, H. see Edahiro, T.
Kawachi, M., Hanawa, F., Sudo, S., and Nakahara, M. see Hanawa, F.
Kawachi, M., Okamoto, K., Sasaki, Y., Miya, T., and Edahiro, T. see Okamoto, K.
Kawachi, M., Sudo, S., Edahiro, T., and Chida, K. see Sudo, S.
Kawachi, M., Tomaru, S., and Edahiro, T. see Tomaru, S.
Kawana, A., Miya, T., Imoto, N., and Tsuchiya, H. Pulse broadening in long-span dispersion-free single-mode fibres at 1.5 μm 188
Kawanishi, H., Hafich, M., Lenz, B., and Petersen, P. AlGaAs transverse junction stripe laser with distributed Bragg reflector 738
Kayran, A.H., and King, R. Least-square inverse polynomials and a counterexample for Jury's conjecture (Comment) 795
Keck, D.B., Bhagavatula, V.A., Love, W.F., and Westwig, R.A. see Bhagavatula, V.A.
Kervarrec, Y., Auffret, R., and Pophillat, L. see Auffret, R.
Khan, A.A., and Singh, H. Petri net approach to enumerate all simple paths in a graph 291
Khan, P.J., and Hicks, R.G. see Hicks, R.G.
Khayata, N., Fray, C., and Papiernik, A. see Fray, C.
Kheirallah, H.N., Knight, J.P., Olsen, R.L., McCormick, K.S., and Segal, B. Frequency dependence of effective path length in prediction of rain attenuation statistics 448
Kikuchi, K., and Okoshi, T. see Okoshi, T.
Kikuchi, K., Okoshi, T., and Nakayama, A. see Okoshi, T.
Kim, B., and Dakss, M.L. see Dakss, M.L.
Kim, H.B., Maciejko, R., and Conradi, J. Effect of laser noise on analogue fibre optic systems 919
Kimura, T., and Kobayashi, S. see Kobayashi, S.
Kimura, T., Kobayashi, S., Yamada, J., and Machida, S. see Kobayashi, S.
Kimura, T., Murakami, Y., Yamada, J-I., and Sakai, J-I. see Murakami, Y.
Kimura, T., Saito, S., and Yamamoto, Y. see Saito, S.
Kimura, T., Yamada, J-I., Machida, S., and Mukai, T. see Yamada, J-I.
Kimura, T., Yamada, J-I., Temmyo, J., and Yoshikawa, S. see Yamada, J-I.
King, R., and Kayran, A.H. see Kayran, A.H.
King, R.A., and Pal, S.K. see Pal, S.K.
Kingsley, S.A., and Culshaw, B. see Culshaw, B.
Kino, G.S., Behar, D., Bowers, J.E., and Olaisen, H. see Behar, D.
Kino, G.S., Behar, D., Olaisen, H., Corl, D., and Grant, P.M. see Behar, D.
Kinoshita, Y., Hikita, M., Kojima, H., and Tabuchi, T. see Hikita, M.
Kinoshita, Y., Kojima, H., Hikita, M., and Tabuchi, T. see Kojima, H.
Kirchner, P.D., Stall, R.A., Wood, C.E.C., and Eastman, L.F. see Stall, R.A.
Kirton, J., Alder, C.J., Cattell, A., Dexter, K., and Dixon, M. see Alder, C.J.
Kishida, S., Washio, K., and Inoue, K. see Washio, K.
Kishino, K., Arai, S., Asada, M., Suematsu, Y., Itaya, Y., and Tanbun-ek, T. see Arai, S.
Kishino, K., Utaka, K., Kobayashi, K., and Suematsu, Y. see Utaka, K.
Kita, T., Watanabe, R., Nosu, K., and Harada, T. see Watanabe, R.
Kitchen, J.A., and Cochrane, P. see Cochrane, P.
Kneidinger, M., Lechner, A., and Kuch, R. see Lechner, A.
Knight, J.P., Kheirallah, H.N., Olsen, R.L., McCormick, K.S., and Segal, B. see Kheirallah, H.N.
Knight, P. Reception of phase-locked l.f. and m.f. transmissions by receivers having ferrite-rod antennas 40
Knob, A. Novel strays-insensitive switched-capacitor integrator realising the bilinear Z-transform 173
Knob, A., and Gobet, Cl.-A. see Gobet, Cl.-A.
Ko, W.L., and Mittra, R. see Mittra, R.
Kobayashi, K., Utaka, K., Kishino, K., and Suematsu, Y. see Utaka, K.
Kobayashi, S., and Kimura, T. Coherence of injection phase-locked AlGaAs semiconductor laser 668
Kobayashi, S., and Kimura, T. Gain and saturation power of resonant AlGaAs laser amplifier 230
Kobayashi, S., Yamada, J., Machida, S., and Kimura, T. Single-mode operation of 500 Mbit/s modulated AlGaAs semiconductor laser by injection locking 746
Kobayashi, S., Ebato, T., and Kajiwara, T. see Ebato, T.
Kobayashi, Y., Minowa, J., Nakagawa, K., Okuno, K., and Morimoto, M. see Minowa, J.
Kobiki, M., Mitsui, Y., Wataze, M., Segawa, K., Otsubo, M., and Ishi, T. see Mitsui, Y.
Kodama, T. Sampling theorem application to s.a.w. diffraction simulation 460
Kogo, H., Hashimoto, K-Y., Yoshida, M., and Yamaguchi, M. see Hashimoto, K-Y.
Kohn, E., Colquhoun, A., and Rabe, W.J. see Colquhoun, A.
Kojima, H., Kinoshita, Y., Hikita, M., and Tabuchi, T. Velocity, electromechanical coupling factor and acoustic loss of surface shear waves propagating along x-axis on rotated Y-cut plates of $LiNbO_3$ 445
Kojima, H., Hikita, M., Kinoshita, Y., and Tabuchi, T. see Hikita, M.
Kojima, N., Fuchigami, T., Ohmura, M., Tomita, N., and Yamamoto, H. see Fuchigami, T.
Kokura, K., Nakahara, M., Sudo, S., Inagaki, N., Yoshida, K., Shibuya, S., and Kuroha, T. see Nakahara, M.
Kollerstrom, J., and Tozer, T.C. see Tozer, T.C.
Konczykowska, A., and Bon, M. Topological analysis of switched-capacitor networks 89
Kondo, S., and Maitree, K. see Maitree, K.
Kostić, I.M. Error rates of phase-modulated signals in multilink system with interference 599 e718
Kosuge, M., Okoshi, T., and Nishimura, M. see Okoshi, T.
Kotelyansky, I.M., Gulyaev, Yu. V., Medved, A.V., and Mishkinis, R.A. see Gulyaev, Yu. V.
Kotler, G., Bergh, R.A., and Shaw, H.J. see Bergh, R.A.
Kovnovich, S., and Karnik, E. Generation and detection of short-duration unipolar stress pulses using poled PVF_2 films 776
Kowatsche, M., and Lafferl, J. Generation of nanosecond high-voltage pulses with high repetition rate 196
Kozub, V.I., Dobrovolsky, A.A., Lemanov, V.V., Sherman, A.B., and Gal'Perin, Yu.M. see Dobrovolsky, A.A.
Krowne, C.M. E-plane coupling between two rectangular microstrip antennas 635
Krowne, C.M., and Sindoris, A.R. H-plane coupling between rectangular microstrip antennas 211
Krummenacher, F., and Zufferey, J. -L. High-gain c.m.o.s. cascode operational amplifier 232
Kubota, M., Oohara, T., Furuya, K., and Suematsu, Y. Electro-optical polarisation control on single-mode optical fibres 573
Kuch, R., Lechner, A., and Kneidinger, M. see Lechner, A.
Kulakov, M.A., and Morozov, A.I. see Morozov, A.I.
Kumar, A., Pal, B.P., and Ghatak, A.K. see Pal, B.P.
Kumar, N., Chakraborti, N.B., and Mukherjee, A.K. Transform-domain spectrum extrapolator for efficient picture transmission 198
Kummer, R.B., Miller, C.M., Mettler, S.C., and Ridgway, D.N. see Miller, C.M.
Kuroha, T., Nakahara, M., Sudo, S., Inagaki, N., Yoshida, K., Shibuya, S., and Kokura, K. see Nakahara, M.
Kurokawa, T., Yoshizawa, T., and Katayama, Y. Precisely moulded plastic splices for optical fibres 911
Kurshan, R.P., and Odlyzko, A.M. Recursive filters with uniform power distribution 672
Kuschmider, A., Amann, M.-C., and Boeck, J. see Amann, M.-C.
Kushibiki, J., Sannomiya, T., and Chubachi, N. Performance of sputtered SiO_2 film as acoustic antireflection coating at sapphire/water inerface 737
Kwok, P.C.K., and Brandon, P.S. Maximisation of signal/noise ratio in array with broadened zero 60

L

L'Haridon, H., Favennec, P.N., Henry, L., Gauneau, M., and Pelous, G. see Favennec, P.N.
Lacroix, G., Marchegay, Ph., and Al Hossri, N. Prediction of flip-flop behaviour in metastable state 725
Lafferl, J., and Kowatsche, M. see Kowatsche, M.
Lagasse, P.E., and van der Donk, J. see van der Donk, J.
Lam, Y.W., Green, M.A., and Davies, L.W. Surface passivation of inversion layer m.i.s. solar cells 707
Lamouler, P., Monerie, M., and Jeunhomme, L. see Monerie, M.
Lanteri, J.P., Pedron, T.P., Garrigues, M., and Urgell, J.J. see Pedron, T.P.
Larivain, J.P., Hirtz, J.P., Duchemin, J.P., Pearsall, T.P., and Bonnet, M. see Hirtz, J.P.
Lau, J., and Sewell, J.I. Inclusion of amplifier finite gain and bandwidth in analysis of switched-capacitor filters 462

Lauritzen, S., Eriksrud, M., and Ryen, N. see Eriksrud, M.
Laviron, M., Delagebeaudeuf, D., Delescluse, P., Etienne, P., Chaplart, J., and Linh, N.T. see Delagebeaudeuf, D.
Law, H.D., Chin, R., and Milano, R.A. see Chin, R.
Laxpati, S.R. Synthesis of planar arrays based on convolution technique 918
Lazarus, M.J., Pantoja, F.R., Somekh, M., Novak, S., and Margison, S. New direction-of-motion Doppler detector 953
Lazarus, M.J., Somekh, M.G., Richmond, W., and Moroz, J. see Somekh, M.G.
Lazay, P.D., Melliar-Smith, C.M., Pasteur, G.A., Chandross, E.A., and Wood, D.L. see Melliar-Smith, C.M.
Lazić, D.E. Class of block codes for the Gaussian channel 185
Le Guen, D., and Favre, F. see Favre, F.
Lechner, A., Kneidinger, M., and Kuch, R. Planar n-GaAs/N-GaAlAs microwave diodes 1
Lecours, M., Cung, T.T., and Huynh, H.T. see Cung, T.T.
Lee, C.P., Tandon, J.L., and Stocker, P.J. Alloying behaviour of Au-Ge/Pt ohmic contacts to GaAs by pulsed electron beam and furnace heating 849
Lee, K.F., Bernard, J., Frey, J., and Gibbons, J.F. see Bernard, J.
Lee, M.S. Improved circuit elements for switched-capacitor ladder filters 131
Lee, Man Shek Parasitics-insensitive switched-capacitor ladder filters 472
Lee, T.P., Burrus, C.A., and Cho, A.Y. Low threshold current transverse junction lasers on semi-insulating substrates by m.b.e. 510
Lee, T.P., Burrus, C.A., and Dentai, A.G. Dual wavelength surface emitting InGaAsP l.e.d.s. 845
Lee, T.P., Burrus, C.A., Dentai, A.G., and Ogawa, K. Samll area InGaAs/InP p-i-n photodiodes: fabrication, characteristics and performance of devices in 274Mb/s and 45 Mb/s lightwave receivers at 1.31 μm wavelength 155
Lefevre, H.C. Single-mode fibre fractional wave devices and polarisation controllers 778
Legier, J.F., Gelin, Ph., and Toutain, S. see Gelin, Ph.
Leheny, R.F., Nahory, R.E., Pollack, M.A., Ballman, A.A., Beebe, E.D., DeWinter, J.C., and Martin, R.J. Integrated $In_{0.53}Ga_{0.47}As$ p-i-n f.e.t. photoreceiver 353
Lemanov, V.V., Dobrovolsky, A.A., Sherman, A.B., Gal'Perin, Yu.M., and Kozub, V.I. see Dobrovolsky, A.A.
Lemanov, V.V., Sherman, A.B., and Dobrovolsky, A.A. see Sherman, A.B.
Leminger, O.G., and Grau, G.K. Near-field intensity and modal power distribution in multimode graded-index fibres 678
Lenz, B., Kawanishi, H., Hafich, M., and Petersen, P. see Kawanishi, H.
Leuenberger, R. Various approximating functions for cascade or ladder simulating RC active networks 309
Levialdi, S., Arcelli, C., and Cordella, L.P. see Arcelli, C.
Leviatan, Y., and Cory, H. see Cory, H.
Levinshtein, M.E., and Simin, G.S. Simple method to determine the main Gunn domain parameters 191
Lewis, J.E., and Rengarajan, S.R. see Rengarajan, S.R.
Lewis, M.F., Darby, B.J., Gunton, D.J., and Newton, C.O. see Darby, B.J.
Li, M.K. Cascade synthesis of switched-capacitor networks employing voltage inverter switches 370
Li, M.K. Pseudopower in switched-capacitor filters 813
Li, M.K. Switched-capacitor realisation of C- and D-sections 603
Liberatore, A., and Manetti, S. see Manetti, S.
Liertz, H. Fusion splicing machine for optical fibres 426
Ligtenberg, H.C.G., and Snijder, J. Measurement arrangement for direct capacitance/surface-potential recording on m.o.s. capacitor e45
Lin, C., Liu, P.L., Damen, T.C., Eilenberger, D.J., and Hartman, R.L. Simple picosecond pulse generation scheme for injection lasers 600
Lin, J.C. Frequency/depth-penetration considerations in hyperthermia by magnetically induced currents (Comment) 790
Lind, L.F., and De Albuquerque, A.A. Data-transmission filters for duobinary systems 228
Lind, L.F., and Mohammed, S.A. Arbitrary phase polynomials 78
Lindström, C., and Tihanyi, P. Kink-free narrow-stripe proton-isolated GaAlAs/GaAs injection lasers 121
Lindström, C., and Tihanyi, P. Temperature stable heat sink metallisation for improved bonding of c.w. stripe lasers 811
Lindström, C., Tihanyi, P., Andersson, T., and Torphammar, P. High bit rate modulation of narrow-stripe proton-implanted GaAs/GaAlAs injection lasers 575
Linh, N.T., Armand, M., and Chevrier, J. see Armand, M.
Linh, N.T., Delagebeaudeuf, D., Delescluse, P., Etienne, P., Laviron, M., and Chaplart, J. see Delagebeaudeuf, D.
Liu, P.L., Lin, C., Damen, T.C., Eilenberger, D.J., and Hartman, R.L. see Lin, C.
Liu, Y.Z., Anderson, R.J., Deyhimy, I., and Tomasetta, L.R. Proton-bombardment isolated GaAlAs/GaAs charge-coupled devices 327
Liu, Y.Z., and Ng, W. see Ng, W.
Livingstone, A.W., and Mellor, P.J.T. see Mellor, P.J.T.
Lloris, A., Prieto, A., and Velasco, J. C.M.O.S. circuit for implementation of unary operators in ternary logic 161
Lo, P., Haddon, J., Moulsley, T.J., and Vilar, E. see Haddon, J.
Logan, R.A., Capasso, F., Foy, P.W., Sumski, S., and Manchon, D.D. see Capasso, F.
Logan, R.A., Capasso, F., Hutchinson, A., and Manchon, D.D. see Capasso, F.
Lohstroh, J. Calculation method to obtain worst-case static noise margins of logic circuits 273
Look, C.M., Noad, J.P., and Springthorpe, A.J. see Noad, J.P.
Love, W.F., Bhagavatula, V.A., Keck, D.B., and Westwig, R.A. see Bhagavatula, V.A.
Luca, M., Silard, A., and Bodea, M. see Silard, A.
Ludowise, M.J., Cooper, C.B., Aebi, V., and Moon, R.L. see Cooper, C.B.
Ludowise, M.J., Cooper, C.B., and Saxena, R.R. see Cooper, C.B.
Luque, A., Eguren, J., and Del Alamo, J. see Eguren, J.
Luthy, W., Badertscher, G., and Salathe, R.P. see Badertscher, G.
Luukkala, M., and Askerov, S.G. Detection of plastic deformation in metals with photoacoustic microscope 84
Luvison, A. Interpolatory quadrature rules and error rate of digital communication systems 16

M

Mabbitt, A.W., Smith, D.R., Hooper, R.C., Ahmad, K., Jenkins, D., and Nicklin, R. see Smith, D.R.
McCormick, K.S., Kheirallah, H.N., Knight, J.P., Olsen, R.L., and Segal, B. see Kheirallah, H.N.
Macfadyen, D.N., Stanley, C.R., and Wilkinson, C.D.W. Waisted-rib optical waveguides in GaAs 440
Machida, S., Kobayashi, S., Yamada, J., and Kimura, T. see Kobayashi, S.
Machida, S., Yamada, J-I., Mukai, T., and Kimura, T. see Yamada, J-I.
Maciejko, R., Kim, H.B., and Conradi, J. see Kim, H.B.
Macksey, H.M., Tserng, H.Q., and Nelson, S.R. see Tserng, H.Q.
McLevige, W.V., Yuan, H.T., and Doerbeck, F.H. see Yuan, H.T.
McMahon, R.A., Ahmed, H., Dobson, R.M., and Speight, J.D. Characterisation of multiple-scan electron beam annealing method 295
Maekawa, T., Ito, Y., Yamamoto, T., and Tanikawa, K. see Ito, Y.
Maher, E.F., Bickley, W.P., and Eddolls, D.V. see Bickley, W.P.
Mahlein, H.F., Michel, H., Rauscher, W., Reichelt, A., and Winzer, G. Interference filter all-fibre directional coupler for w.d.m. 584
Maitree, K., and Kondo, S. Computation of multiweight 933
Majer, J. Graphical method for conduction loss calculation of TEM transmission lines 638
Makarious, A.H., and Farrell, P.G. Novel p.s.k. tanlock loop 957
Maki, K., Asatani, K., Sato, K., and Miki, T. see Asatani, K.
Makimura, T., Takada, T., and Ishibashi, T. see Takada, T.
Malhi, S.D.S., and Salama, C.A.T. Cutoff frequency of a graded channel f.e.t. 261
Malik, R.J., Aucoin, T.R., Ross, R.L., Board, K., Wood, C.E.C., and Eastman, L.F. Planar-doped barriers in GaAs by molecular beam epitaxy 836
Malyon, D.J., Smith, D.W., and Berry, R.W. Wavelength sensed mode control of semiconductor lasers 744
Manchon, D.D., Capasso, F., Logan, R.A., Foy, P.W., and Sumski, S. see Capasso, F.
Manchon, D.D., Capasso, F., Logan, R.A., and Hutchinson, A. see Capasso, F.
Manetti, S., and Liberatore, A. Switched-capacitor lowpass filter without active components 883
Manolakis, D., Carayannis, G., and Kalouptsidis, N. see Carayannis, G.
Mansour, M., and Badreddin, E. see Badreddin, E.
Mantakas, C., Dagakis, K., and Papadopoulos, G. see Dagakis, K.
Maravall, D. New reinforcement algorithm in learning automata 623
Marchegay, Ph., Lacroix, G., and Al Hossri, N. see Lacroix, G.
Margalit, S., Katz, J., Bar-Chaim, N., and Yariv, A. see Katz, J.
Margison, S., Lazarus, M.J., Pantoja, F.R., Somekh, M., and Novak, S. see Lazarus, M.J.
Marie, K.H.S., Anderson, A.P., and Bennett, J.C. Microwave images with reduced background effects from digitally processed in-line holograms 493
Marino-Acebal, J.B., Nadeu-Camprubi, C., and Masgrau-Gomez, E. Design of band-stop filters by reactance transformation 105
Marlow, B.K., and Batchelor, B.G. Detecting instability in concavity trees 138
Marlow, B.K., and Batchelor, B.G. Improving the speed of convex hull calculations 319
Martin, G.M., Berth, M., and Venger, C. Role of substrate in electrical properties of GaAs implanted layers 278
Martin, K., and Sedra, A.S. Easing prefiltering requirements of s.c. filters 613
Martin, K., and Sedra, S. Transfer function deviations due to resistor-s.c. equivalence assumption in switched-capacitor simulations of LC ladders 387
Martin, R.J., Leheny, R.F., Nahory, R.E., Pollack, M.A., Ballman, A.A., Beebe, E.D., and DeWinter, J.C. see Leheny, R.F.
Martinelli, R.U., Rosen, A., and Caulton, M. see Rosen, A.
Martinez, J., Calleja, E., and Piqueras, J. Current/voltage characteristics of degenerated molybdenum and platinum Schottky diodes 183
Maseng, T., and Bakken, P.M. see Bakken, P.M.
Masgrau-Gomez, E., Marino-Acebal, J.B., and Nadeu-Camprubi, C. see Marino-Acebal, J.B.

Mason, D.C., and Balston, D.M. Relationship between system delay and transmission rate in time-encoded speech 128
Massot, J.N., Meunier, J.P., and Pigeon, J. see Meunier, J.P.
Massoudi, H., Durney, C.H., and Iskander, M.F. Long-wavelength analysis of near-field irradiation of prolate spheroidal models of man and animals 99
Mathews, N.A., and Riris, A. Performance degradation of two-link binary c.p.s.k. system incorporating direct phase regenerator 650
Matricciani, E. Earth-space rain-cell modelling through SIRIO propagation data 81
Matsuda, O., Mori, Y., Morizane, K., and Watanabe, N. see Mori, Y.
Matsumoto, T. Polarisation-independent optical circulator coupled with multimode fibres 8
Matsumura, M., and Wakimoto, T. see Wakimoto, T.
Matsushita, S., Ishikawa, R., Kaede, K., Nishimoto, H., and Minemura, K. see Ishikawa, R.
Mattiocco, F., Dieulesaint, E., and Royer, D. PVF_2 transducers for Rayleigh waves 250
Mavor, J., Kapur, N., and Jack, M.A. see Kapur, N.
Medved, A.V., Gulyaev, Yu. V., Kotelyansky, I.M., and Mishkinis, R.A. see Gulyaev, Yu. V.
Meiksin, Z.H., and Humbel, W.D. Thick-film strain gauges and pressure transducers 242
Melliar-Smith, C.M., Lazay, P.D., Pasteur, G.A., Chandross, E.A., and Wood, D.L. Index matching fluids for long wavelength (1.2-1.6 μm) fibre-optic applications 403
Mellor, P.J.T., and Livingstone, A.W. Capacitor-coupled logic using GaAs depletion-mode f.e.t.s. 749
Menaglia, U., Costa, B., Sordo, B., Piccari, L., and Grasso, G. see Costa, B.
Merritt, J.D., Teng, T.C., Velez, J., Peng, J., and Palkuti, L. see Teng, T.C.
Mettler, S.C., Miller, C.M., Kummer, R.B., and Ridgway, D.N. see Miller, C.M.
Meunier, J.P., Pigeon, J., and Massot, J.N. Perturbation theory for the evaluation of the normalised cutoff frequencies in radially inhomogeneous fibres 27
Michel, H., Mahlein, H.F., Rauscher, W., Reichelt, A., and Winzer, G. see Mahlein, H.F.
Middelkoop, R., Herben, M.H.A.J., and Gielkens, F.J.J. see Herben, M.H.A.J.
Miki, T., Asatani, K., Sato, K., and Maki, K. see Asatani, K.
Mikoshiba, N., and Sasaki, H. see Sasaki, H.
Milano, R.A., Chin, R., and Law, H.D. see Chin, R.
Miles, R.O., Dandridge, A., and Giallorenzi, T.G. see Dandridge, A.
Millar, C.A., and Payne, D.B. see Payne, D.B.
Miller, B.I., and Iga, K. see Iga, K.
Miller, C.M., Kummer, R.B., Mettler, S.C., and Ridgway, D.N. Single-mode optical fibre switch 783
Miller, R.L., Truong, T.K., and Reed, I.S. Fast algorithm for encoding the (255,223) Reed-Solomon code over $GF(2^8)$ 222
Millott, L.J., and Smith, B.M. Mean square error of s.s.b.a.m. class 4 partial response data signals due to slope, sag and ripple group delay components 492
Milovanović, B.D. Numerical analysis of radial thin-wire antenna in presence of conducting sphere 611
Milutinović, V.M. Comparison of three suboptimum detection procedures 681
Milutinović, V.M. Suboptimum detection procedure based on the weighting of partial decisions 237
Minemura, K., Ishikawa, R., Kaede, K., Nishimoto, H., and Matsushita, S. see Ishikawa, R.
Minowa, J., Fujii, Y., Nagata, Y., Aoyama, T., and Doi, K. Nonblocking 8 x 8 optical matrix switch for fibre-optic communication 422
Minowa, J., Nakagawa, K., Okuno, K., Kobayashi, Y., and Morimoto, M. 800 MHz s.a.w. timing filter for optical fibre transmission system 35
Mishkinis, R.A., Gulyaev, Yu. V., Kotelyansky, I.M., and Medved, A.V. see Gulyaev, Yu. V.
Mital, D.P., and Ektare, A.B. see Ektare, A.B.
Mitchell, R.F., Murray, R.J., and Schofield, J. see Murray, R.J.
Mitsui, Y., Kobiki, M., Wataze, M., Segawa, K., Otsubo, M., and Ishi, T. 10 GHz/10 W internally matched flip-chip GaAs power f.e.t.s. 205
Mittra, R., and Ko, W.L. New technique for efficient pattern computation of aperture and reflector antennas 549
Miya, T., Kawana, A., Imoto, N., and Tsuchiya, H. see Kawana, A.
Miya, T., Okamoto, K., Sasaki, Y., Kawachi, M., and Edahiro, T. see Okamoto, K.
Mizutani, T., Kato, N., Ishida, S., Osafune, K., and Ohmori, M. GaAs gigabit logic circuits using normally-off m.e.s.f.e.t.s. 315
Mohammed, S.A., and Lind, L.F. see Lind, L.F.
Mojzes, I., Sebestyen, T., and Szigethy, D. see Sebestyen, T.
Monerie, M., Lamouler, P., and Jeunhomme, L. Polarisation mode dispersion measurements in long single mode fibres 907
Monerie, M., and Jeunhomme, L. see Jeunhomme, L.
Monsion, M., and Commanges, D. Filtre recursif nonlineaire 125 e240
Moon, R.L., Cooper, C.B., Ludowise, M.J., and Aebi, V. see Cooper, C.B.
Mori, Y., Matsuda, O., Morizane, K., and Watanabe, N. V-dh laser: a laser with a V-shaped active region grown by metalorganic c.v.d. 785
Mori, Y., and Watanabe, N. C.W. operation of $Al_xGa_{1-x}As/Al_yGa_{1-y}As$ lasers grown by metalorganic c.v.d. in wavelength range 760 - 780 nm 284
Morimoto, M., Minowa, J., Nakagawa, K., Okuno, K., and Kobayashi, Y. see Minowa, J.
Moriyama, T., Fukuda, O., Sanada, K., Inada, K., Edahiro, T., and Chida, K. Ultimately low OH content v.a.d. optical fibres 698
Morizane, K., Mori, Y., Matsuda, O., and Watanabe, N. see Mori, Y.
Morkoc, H., Witkowski, L.C., Drummond, T.J., Stanchak, C.M., Cho, A.Y., and Streetman, B.G. Growth conditions to achieve mobility enhancement in $Al_xGa_{1-x}As$-GaAs heterojunctions by m.b.e. 753
Moronvalle, C., d'Auria, L., Combemale, Y., and Jacques, A. see d'Auria, L.
Moroz, J., Somekh, M.G., Richmond, W., and Lazarus, M.J. see Somekh, M.G.
Morozov, A.I., and Kulakov, M.A. Single lens transmission scanning acoustic microscope 596
Morrison, R.J., Tangonan, G.L., Persechini, D.I., and Wysocki, J.A. see Tangonan, G.L.
Moschytz, G.S., Von Grünigen, D.C., and Brugger, U.W. see Von Grünigen, D.C.
Mossaheb, S. Stability of certain time-varying nonlinear systems 190
Moulsley, T.J., Haddon, J., Lo, P., and Vilar, E. see Haddon, J.
Mudaly, S.S. Improved microprocessor-controlled pedestrian data-acquisition system 3
Mukai, T., Yamada, J-I., Machida, S., and Kimura, T. see Yamada, J-I.
Mukherjee, A.K., Kumar, N., and Chakraborti, N.B. see Kumar, N.
Müller, G., and Temes, G.C. Simple method for analysis of a class of switched-capacitor filters 852
Munoz Rodriguez, D., and Cattermole, K.W. Intersymbol interference in misequalised coaxial systems 891
Murakami, Y., Yamada, J-I., Sakai, J-I., and Kimura, T. Microlens tipped on a single-mode fibre end for InGaAsP laser coupling improvement 321
Murata, H., and Nagasawa, S. see Nagasawa, S.
Murata, H., and Satake, T. see Satake, T.
Murotani, T., Oomura, E., Higuchi, H., Namizaki, H., and Susaki, W. InGaAsP/InP buried crescent laser emitting at 1.3 μm with very low threshold current 566
Murray, R.J., Mitchell, R.F., and Schofield, J. Harmonic suppression in surface-acoustic-wave devices using jogged multistrip couplers 356

N

Nadeu-Camprubi, C., Marino-Acebal, J.B., and Masgrau-Gomez, E. see Marino-Acebal, J.B.
Nagai, H., Edahiro, T., Kawachi, M., and Sudo, S. see Edahiro, T.
Nagaki, Y., Okada, K., Hashimoto, K., and Shibata, T. see Okada, K.
Nagasawa, S., and Murata, H. Multi-glass-rod optical-fibre splicers made by drawing technique 136
Nagata, Y., Minowa, J., Fujii, Y., Aoyama, T., and Doi, K. see Minowa, J.
Nagel, S.R., and Saifi, M.A. Effect of deposition rate on spectral loss of GeO_2-P_2O_5-SiO_2 graded index fibres 469
Nahory, R.E., Kaminow, I.P., Pollack, M.A., Stulz, L.W., and DeWinter, J.C. see Kaminow, I.P.
Nahory, R.E., Leheny, R.F., Pollack, M.A., Ballman, A.A., Beebe, E.D., DeWinter, J.C., and Martin, R.J. see Leheny, R.F.
Nakagawa, K., Takeshima, M., and Ebisawa, F. Hydraulic pressure buckling in plastic coated optical fibre 838
Nakagawa, K., Minowa, J., Okuno, K., Kobayashi, Y., and Morimoto, M. see Minowa, J.
Nakagome, H., Kanbe, H., Susa, N., and Ando, H. see Kanbe, H.
Nakahara, M., Chida, K., Hanawa, F., Sudo, S., and Horiguchi, M. Fabrication of low-loss and wide-bandwidth v.a.d. optical fibres at 1.3 μm wavelength 102
Nakahara, M., Sudo, S., Inagaki, N., Yoshida, K., Shibuya, S., Kokura, K., and Kuroha, T. Ultra wide bandwidth v.a.d. fibre 391 e644
Nakahara, M., Hanawa, F., Sudo, S., and Kawachi, M. see Hanawa, F.
Nakahara, M., Suda, H., and Chida, K. see Suda, H.
Nakahara, M., Sudo, S., Okazaki, H., and Horiguchi, M. see Sudo, S.
Nakano, H., and Yamauchi, J. Radiation characteristics of helix antenna with parasitic elements 687
Nakayama, A., Okoshi, T., and Kikuchi, K. see Okoshi, T.
Nakazima, K., Osaka, F., Kaneda, T., Sakurai, T., and Susa, N. see Osaka, F.
Namizaki, H., Murotani, T., Oomura, E., Higuchi, H., and Susaki, W. see Murotani, T.
Nanda, N.K., and Bennetts, R.G. Reconvergence phenomenon in synchronous sequential circuits 303
Nandi, R. Lossless inductor simulation: novel configurations using d.v.c.c.s. 666
Nandi, R. Novel insensitive lossless inductor simulation through inverse function generation 481
Nandi, R., and Saha, A.R. see Saha, A.R.
Narraway, J.J., and So, K. -M. Single-row routeing and planarity 219
Nassau, K. Material dispersion zero in infra-red waveguides 924
Nedungadi, A. High current class AB convertor technique 418

Neidert, R.E. Dielectric constant of semi-insulating gallium arsenide 244
Neill, T.R., and Bull, C.J. High voltage electron lithography 621
Nelson, R.J., Dutta, N.K., and Barnes, P.A. see Dutta, N.K.
Nelson, S.R., Tserng, H.Q., and Macksey, H.M. see Tserng, H.Q.
Nelson, T.U. Propagation of m.f. signals along mine tunnel containing an axial wire and water trough 834
Neri, R. Moment-method solution of directed dipole antennas 453
Newton, C.O., Darby, B.J., Gunton, D.J., and Lewis, M.F. see Darby, B.J.
Ng, W., and Liu, Y.Z. Effect of p-doping on carrier lifetime and threshold current density of 1.3 μm GaInAsP/InP lasers by liquid-phase epitaxy 693
Nicholson, G., Gibbs, A.J., and Potter, P.G. see Gibbs, A.J.
Nicholson, H., and Fernando, K.V.M. see Fernando, K.V.M.
Nicklin, R., Smith, D.R., Hooper, R.C., Ahmad, K., Jenkins, D., and Mabbitt, A.W. see Smith, D.R.
Nightingale, C., and Spriggs, H. see Spriggs, H.
Nikias, C.L. Error-free coefficient realisation of recursive part via input-partitioned filter structure 236
Nishimoto, H., Ishikawa, R., Kaede, K., Minemura, K., and Matsushita, S. see Ishikawa, R.
Nishimura, M., Okoshi, T., and Kosuge, M. see Okoshi, T.
Niwa, N., Hotate, K., Yoshida, Y., and Higashiguchi, M. see Hotate, K.
Noad, J.P., Look, C.M., and Springthorpe, A.J. Channelled substrate lasers prepared by combination of organometallic pyrolysis and liquid-phase epitaxy 685
Noras, J.M. Conrad's rule for phase-modulation spectra 5
Norton, R.E., Rawson, E.G., and Goodman, J.W. see Rawson, E.G.
Nossek, J.A. Improved circuit for switched-capacitor simulation of an inductor 141
Nosu, K., and Watanabe, R. Slab waveguide star coupler for multimode optical fibre 608
Nosu, K., Watanabe, R., and Fujii, Y. see Watanabe, R.
Nosu, K., Watanabe, R., Harada, T., and Kita, T. see Watanabe, R.
Nouri, M., and Braine, M.R. Uplink adaptive depolarisation cancellation in a ground-to-satellite link 68
Novak, S., Lazarus, M.J., Pantoja, F.R., Somekh, M., and Margison, S. see Lazarus, M.J.

O

O'Mahony, M.J. Duobinary transmission with p-i-n f.e.t. optical receivers 752
Odlyzko, A.M., and Kurshan, R.P. see Kurshan, R.P.
Ogawa, K., Gloge, D., and Cohen, L.G. see Gloge, D.
Ogawa, K., Lee, T.P., Burrus, C.A., and Dentai, A.G. see Lee, T.P.
Ogawa, Y., Ito, H., and Inaba, H. see Ito, H.
Ogrodzki, J.T. Modified nodal approach to network sensitivity calculation for one-dimensional orthogonal search technique 641
Ogura, Y., and Hirose, Y. see Hirose, Y.
Ohmori, M., Mizutani, T., Kato, N., Ishida, S., and Osafune, K. see Mizutani, T.
Ohmura, M., Fuchigami, T., Kojima, N., Tomita, N., and Yamamoto, H. see Fuchigami, T.
Okada, K., Hashimoto, K., Shibata, T., and Nagaki, Y. Optical cable fault location using correlation technique 629
Okada, K., Sano, K., and Hashimoto, K. see Sano, K.
Okamoto, K., Sasaki, Y., Miya, T., Kawachi, M., and Edahiro, T. Polarisation characteristics in long length v.a.d. single-mode fibres 768
Okamoto, K., Sasaki, Y., Miya, T., Kawachi, M., and Edahiro, T. Polarisation characteristics in long length v.a.d. single-mode fibres (Comment) 954
Okano, N., Inada, T., Sugiyama, T., and Ishikawa, Y. see Inada, T.
Okazaki, H., Sudo, S., Nakahara, M., and Horiguchi, M. see Sudo, S.
Okoshi, T., and Kikuchi, K. Frequency stabilisation of semiconductor lasers for heterodyne-type optical communication systems 179
Okoshi, T., Kikuchi, K., and Nakayama, A. Novel method for high resolution measurement of laser output spectrum 630
Okoshi, T., Nishimura, M., and Kosuge, M. Nondestructive measurement of axially nonsymmetric refractive-index distribution of optical fibre preforms 722
Okoshi, T., and Oyamada, K. Single-polarisation single-mode optical fibre with refractive-index pits on both sides of core 712
Okuno, K., Minowa, J., Nakagawa, K., Kobayashi, Y., and Morimoto, M. see Minowa, J.
Olaisen, H., Behar, D., Kino, G.S., and Bowers, J.E. see Behar, D.
Olaisen, H., Behar, D., Kino, G.S., Corl, D., and Grant, P.M. see Behar, D.
Olcaytug, F., Riedling, K., and Fallmann, W. C/V measurements on m.i.s. structures on n-InSb formed by room temperature reactive deposition of Si_3N_4 677
Olesen, H. Dependence of modal noise on source coherence and fibre length 217
Olsen, G.H., Zamerowski, T.J., and Digiuseppe, N.J. 1.5-1.7 μm v.p.e. InGaAsP/InP c.w. lasers 516
Olsen, R.L., Antar, Y.M.M., Hendry, A., Schlesak, J.J., and Bérubé, R.C. see Antar, Y.M.M.
Olsen, R.L., Kheirallah, H.N., Knight, J.P., McCormick, K.S., and Segal, B. see Kheirallah, H.N.
Omori, H., and Otani, K. see Otani, K.
Oohara, T., Kubota, M., Furuya, K., and Suematsu, Y. see Kubota, M.
Oomura, E., Murotani, T., Higuchi, H., Namizaki, H., and Susaki, W. see Murotani, T.
Osafune, K., Mizutani, T., Kato, N., Ishida, S., and Ohmori, M. see Mizutani, T.
Osaka, F., Nakazima, K., Kaneda, T., Sakurai, T., and Susa, N. InP/InGaAsP avalanche photodiodes with new guard ring structure 716
Osowski, S. Frequency-multiple generation technique using Chebyshev polynomials 91
Otani, K., and Omori, H. Distribution of burst error lengths in Rayleigh fading radio channels 889
Otsubo, M., Mitsui, Y., Kobiki, M., Wataze, M., Segawa, K., and Ishi, T. see Mitsui, Y.
Owens, J.M., Sethares, J.C., and Smith, C.V. see Sethares, J.C.
Oyamada, K., and Okoshi, T. see Okoshi, T.

P

Pal, B.P., Kumar, A., and Ghatak, A.K. Effect of axial refractive-index dip on zero total dispersion wavelength in single-mode fibres 505
Pal, K. Novel f.d.n.c. simulation using current conveyors 639
Pal, S.K., and King, R.A. Image enhancement using fuzzy set 376
Palkuti, L., Teng, T.C., Merritt, J.D., Velez, J., and Peng, J. see Teng, T.C.
Pantoja, F.R., Lazarus, M.J., Somekh, M., Novak, S., and Margison, S. see Lazarus, M.J.
Papadopoulos, G., Dagakis, K., and Mantakas, C. see Dagakis, K.
Papiernik, A., Fray, C., and Khayata, N. see Fray, C.
Papuchon, M., Puech, C., and Schnapper, A. 4-bits digitally driven integrated amplitude modulator for data processing 142
Parini, C.G., and Clarricoats, P.J.B. Reflector antenna profile measurement using ultrasound 544
Parker, E.A., and Cahill, R. see Cahill, R.
Parks, G.B., and Soderstrand, M.A. Elliptic filter design using arithmetic-geometric mean 568
Parodi, M., Bianco, B., Corana, A., Gogioso, L., and Ridella, S. see Bianco, B.
Parsons, J.D., Ibrahim, M.F., and Samuel, R.J. Median signal strength prediction for mobile radio propagation in London 172
Pask, C., and Sammut, R.A. Experimental characterisation of graded-index single-mode fibres 310
Pask, C., and Barrell, K.F. see Barrell, K.F.
Pasteur, G.A., Melliar-Smith, C.M., Lazay, P.D., Chandross, E.A., and Wood, D.L. see Melliar-Smith, C.M.
Pauw, C.K. Application of decision feedback equaliser in an environment with narrow-band interfering signals 787
Pavlović, V.D., and Stojanović, V.S. see Stojanović, V.S.
Payne, D.B., and Millar, C.A. Triple-ball connector using fibre-bead location 11
Payne, D.N., Conduit, A.J., and Hartog, A.H. see Conduit, A.J.
Payne, D.N., Sasaki, I., and Adams, M.J. see Sasaki, I.
Pearsall, T., Hirtz, J.P., Duchemin, J.P., Hirtz, P., de Cremoux, B., and Bonnet, M. see Hirtz, J.P.
Pearsall, T.P. Band-to-band tunnelling current in $Ga_{0.47}$ $In_{0.53}$ As p-n junctions 771
Pearsall, T.P., Hirtz, J.P., Larivaia, J.P., Duchemin, J.P., and Bonnet, M. see Hirtz, J.P.
Pearton, S.J., Tavendale, A.J., and Williams, A.A. Deep trapping centres in n-GaAs surface barrier diodes for nuclear radiation detection 483
Pedron, T.P., Lanteri, J.P., Garrigues, M., and Urgell, J.J. Controlling deep transient depletion of an m.o.s. capacitor 367
Peek, J.A.F. Role of water in gradual degradation of (Al, Ga)As d.h. lasers 441
Pelous, G., Favennec, P.N., Henry, L., Gauneau, M., and L'Haridon, H. see Favennec, P.N.
Peng, J., Teng, T.C., Merritt, J.D., Velez, J., and Palkuti, L. see Teng, T.C.
Peri, D., and Chu, P.L. Index profile determination in transition region of optical fibre preform 916
Peri, D., and Chu, P.L. see Chu, P.L.
Persechini, D.I., Tangonan, G.L., Morrison, R.J., and Wysocki, J.A. see Tangonan, G.L.
Petersen, P., Kawanishi, H., Hafich, M., and Lenz, B. see Kawanishi, H.
Petrović, G. Power spectrum of scrambled signal 147 e240
Petrović, G. Power spectrum of the balanced digital signal generated by Markov source e240
Petrović, G., and Drajić, D. see Drajić, D.
Petrović, P.M. Spectral shaping of digitised speech for mobile radio applications 363
Petrović, R. Multilayer multimode optical fibre 562
Petts, C.R., and Wickramasinghe, H.K. Acoustic microscopy in gases 9
Petty, M.C., Dharmadasa, I.M., and Roberts, G.G. see Dharmadasa, I.M.
Piasecki, J. Subpicosecond measurement of response of optical fibres 498
Piasecki, J., and Barthelemy, A. Novel method for transmitting images through monomode fibres 420
Piazzolla, S., Daino, B., and De Marchis, G. see Daino, B.
Pic, E., and Saguet, P. see Saguet, P.
Piccari, L., Costa, B., Sordo, B., Menaglia, U., and Grasso, G. see Costa, B.

Pickup, C.P. New a.d. convertor with special application to medium precision platinum resistance thermometry 578
Picton, P.D. Clock-steering synthesis using spectral techniques 409
Pigeon, J., Meunier, J.P., and Massot, J.N. see Meunier, J.P.
Pilkuhn, M.H., Renz, H., Weidlein, J., and Benz, K.W. see Renz, H.
Piqueras, J., Martinez, J., and Calleja, E. see Martinez, J.
Pitt, C.W., and Singh, S.P. Neutralised ion beam milling: anomalous sputter yield behaviour 721
Pitt, C.W., Stride, A.A., and Trigle, R.I. Low temperature diffusion process for fabricating optical waveguides in glass 701
Planat, M., Theobald, G., Gagnepain, J.J., and Siffert, P. Intermodulation in X-cut lithium tantalate resonators 174
Plumb, R.G., and Curtis, J.P. Channelled substrate narrow stripe GaAs/(GaAl)As lasers with quarter-wavelength facet coatings 706
Podcameni, A., and Coimbra, M.L. Slotline-microstrip transition on iso/anisotropic substrate: a more accurate design 780
Pollack, M.A., Kaminow, I.P., Nahory, R.E., Stulz, L.W., and DeWinter, J.C. see Kaminow, I.P.
Pollack, M.A., Leheny, R.F., Nahory, R.E., Ballman, A.A., Beebe, E.D., DeWinter, J.C., and Martin, R.J. see Leheny, R.F.
Ponse, F., Beneking, H., and Filensky, W. see Beneking, H.
Ponse, F., Filensky, W., and Beneking, H. see Filensky, W.
Poor, H.V. Minimum-distortion functional for one-dimensional quantisation 23
Pophillat, L., Auffret, R., and Kervarrec, Y. see Auffret, R.
Popović, R.S., and Stojadinović, N.D. see Stojadinović, N.D.
Porter, B. Necessary conditions for absolute stability of nonlinear multivariable regulators 392
Porter, B. Necessary conditions for absolute stability of nonlinear regulators 181
Porter, B. Transmission zeros of linear multivariable systems with parasitics 679
Potter, J.M. Recursive code generation based on m-sequence 858
Potter, P.G., Gibbs, A.J., and Nicholson, G. see Gibbs, A.J.
Prabhu, K.M.M., and Renganathan, H. Optimised data windows 38
Prasad, V.C., and Gaur, P.B.L. Sufficient conditions for global homeomorphism of piecewise linear functions 335
Preis, D., and Bunks, C. Chebyshev time-domain deconvolution for transversal filter equalisers 899
Premoli, A., and Biey, M. see Biey, M.
Prieto, A., Lloris, A., and Velasco, J. see Lloris, A.
Puangpool, M., Thajchayapong, P., and Banjongjit, S. see Thajchayapong, P.
Puc, A.B., and Yip, G.L. Pulse broadening compensation in fibre-optical links 162
Puech, C., Papuchon, M., and Schnapper, A. see Papuchon, M.
Pues, H.F., and van de Capelle, A.R. Approximate formulas for frequency dependence of microstrip parameters 870
Pursley, M.B., and Garber, F.D. see Garber, F.D.
Pyara, V.P., and Jamuar, S.S. Single element controlled oscillator without external capacitors 607

R

Ra, J-W., Joo, C-S., and Shin, S-Y. see Joo, C-S.
Rabe, W.J., Colquhoun, A., and Kohn, E. see Colquhoun, A.
Rabrenović, D., and Jovanović, V. All-pole filter with predistorted attenuation characteristic 950
Radice, C., Cho, A.Y., Casey, Jun, H.C., and Foy, P.W. see Cho, A.Y.
Ragaie, H.F. Electrical conduction in metal/implanted SiO_2/Si structures 565
Rakouth, H., Ash, E.A., and Dieulesant, E. see Ash, E.A.
Ramnarayan, A.S. Practical realisation of mod p, p prime multiplier 466
Ramskov Hansen, J.J., Adams, M.J., Ankiewicz, A., and Sladen, F.M.E. Near-field correction factors for elliptical fibres 580
Ramskov Hansen, J.J., Ankiewicz, A., and Adams, M.J. Attenuation of leaky modes in graded noncircular multimode fibres 94
Ramskov Hansen, J.J., and Jacobsen, G. see Jacobsen, G.
Rao, M.K.N., Haslett, J.W., and Bruton, L.T. see Haslett, J.W.
Rauscher, C. Broadband varactor-tuned GaAs f.e.t. oscillator 534
Rauscher, W., Mahlein, H.F., Michel, H., Reichelt, A., and Winzer, G. see Mahlein, H.F.
Rawson, E.G., Norton, R.E., and Goodman, J.W. Temporal frequency dependence of modal noise in fibres 301
Reddy, V.U. Estimation of a sinusoid in uncorrelated noise using adaptive line enhancer 473
Redwood, M., and Foster, S.J. see Foster, S.J.
Reed, I.S., Miller, R.L., and Truong, T.K. see Miller, R.L.
Rees, G.J., and Socha, J.B. see Socha, J.B.
Reeve, M.H., and Kashyap, R. see Kashyap, R.
Reichelt, A., Mahlein, H.F., Michel, H., Rauscher, W., and Winzer, G. see Mahlein, H.F.
Reilly, J., Haykin, S., and Taylor, D. see Haykin, S.
Rejman, M.A.Z., Smith, D.R., Chatterjee, A.K., Wake, D., and White, B.R. see Smith, D.R.
Renganathan, H., and Prabhu, K.M.M. see Prabhu, K.M.M.
Rengarajan, S.R., and Lewis, J.E. First higher-mode cutoff in two-layer elliptical fibre waveguides 263
Renz, H., Weidlein, J., Benz, K.W., and Pilkuhn, M.H. InP epitaxy with a new metalorganic compound 228
Richmond, W., Somekh, M.G., Moroz, J., and Lazarus, M.J. see Somekh, M.G.
Ridella, S., Bianco, B., Corana, A., Gogioso, L., and Parodi, M. see Bianco, B.
Ridgway, D.N., Miller, C.M., Kummer, R.B., and Mettler, S.C. see Miller, C.M.
Ridler, P.J., and Jennings, B.R. see Jennings, B.R.
Riedling, K., Olcaytug, F., and Fallmann, W. see Olcaytug, F.
Riris, A., and Mathews, N.A. see Mathews, N.A.
Roberts, G.G., Dharmadasa, I.M., and Petty, M.C. see Dharmadasa, I.M.
Robson, P.N., Westbrook, L.D., and Fiddyment, P.J. see Westbrook, L.D.
Rocchi, M., Cathelin, M., Durand, G., and Gavant, M. see Cathelin, M.
Rodriguez-Vazquez, A., and Huertas, J.L. Novel active-compensated weighted summer 394
Rogers, A.J. Polarisation optical time domain reflectometry 489
Romestan, J., Bonnafe, J., Castagne, M., De Murcia, M., and Fillard, J.P. see Bonnafe, J.
Rønnekleiv, A., Engan, H., and Ingebrigtsen, K.A. see Engan, H.
Rosen, A., Martinelli, R.U., and Caulton, M. Temperature dependence of storage time in silicon p^+-n-n^+ switching diodes and reduction of harmonic distortion 66
Rosencwaig, A. Depth profiling of integrated circuits with thermal wave electron microscopy 928
Rosiewicz, A., Gray, M.H., Irven, J., Titchmarsh, J.G., and Black, P.W. Effects of radiation on doped silica core optical fibres 866
Ross, R.L., Malik, R.J., Aucoin, T.R., Board, K., Wood, C.E.C., and Eastman, L.F. see Malik, R.J.
Rossel, P., Sautereau, J.F., Graffeuil, J., and Tantrarongroj, K. see Sautereau, J.F.
Roth, W., Beneking, H., Grote, N., and Svilans, M.N. see Beneking, H.
Roulston, D.J. Very low noise photodetector system using p-i-n diode and baseband parametric upconvertor 595
Roulston, D.J., and Depey, M. Emitter-collector breakdown voltage versus gain for various n-p-n collector doping levels 803
Rousseau-Leberre, M., and Arnaud, J. see Arnaud, J.
Royer, D., Mattiocco, F., and Dieulesaint, E. see Mattiocco, F.
Runovc, F. Effectiveness of charged vacancies in diffusion of implanted boron in silicon 49
Rush, J., Ainslie, B.J., Day, C.R., and Beales, K.J. see Ainslie, B.J.
Ryen, N., Eriksrud, M., and Lauritzen, S. see Eriksrud, M.

S

Sabine, P.V.H., Donaghy, F., and Irving, D. Fibre refractive-index profiling by modified near-field scanning 882
Sachse, K., and Citerne, J. Frequency-dependent solution of suspended microstrip line with tuning septums 264
Saguet, P., and Pic, E. An improvement for the t.l.m. method 247
Saha, A.R., and Nandi, R. Novel active R supercapacitor simulation: applications in low sensitivity multifunction network realisation 570
Saifi, M.A., and Nagel, S.R. see Nagel, S.R.
Saijonmaa, J., Sharma, A.B., and Halme, S.J. Optimal excitation of multimode graded-index fibres in d.m.d. and d.m.a. measurements 690
Saijonmaa, J., Sharma, A.B., and Halme, S.J. see Sharma, A.B.
Saillard, J., and Chassay, G. see Chassay, G.
Saito, H., Takahashi, S., and Iwane, G. see Takahashi, S.
Saito, S., Yamamoto, Y., and Kimura, T. Optical heterodyne detection of directly frequency modulated semiconductor laser signals 826
Sakai, J-I., Murakami, Y., Yamada, J-I., and Kimura, T. see Murakami, Y.
Sakakibara, Y., Furuya, K., Utaka, K., and Suematsu, Y. Single-mode oscillation under high-speed direct modulation in GaInAsP/InP integrated twin-guide lasers with distributed Bragg reflectors 456
Sakurai, T., Osaka, F., Nakazima, K., Kaneda, T., and Susa, N. see Osaka, F.
Salama, C.A.T., and Malhi, S.D.S. see Malhi, S.D.S.
Salathe, R.P., Badertscher, G., and Luthy, W. see Badertscher, G.
Sammut, R.A. Birefringence in graded-index monomode fibres with elliptical cross-section 156
Sammut, R.A. Birefringence in slightly elliptical optical fibres 728
Sammut, R.A., and Snyder, A.W. Graded monomode fibres and planar waveguides 32
Sammut, R.A., and Pask, C. see Pask, C.
Samuel, R.J., Parsons, J.D., and Ibrahim, M.F. see Parsons, J.D.
Sanada, K., Moriyama, T., Fukuda, O., Inada, K., Edahiro, T., and Chida, K. see Moriyama, T.
Sanders, I.R., Shah, N.J., Ahmed, H., and Singleton, J.F. see Shah, N.J.
Sannomiya, T., Kushibiki, J., and Chubachi, N. see Kushibiki, J.
Sano, K., Okada, K., and Hashimoto, K. Simple optical wavelength meter in 700-1200 nm wavelength region 912
Sarhadi, M., and Aitchison, C.S. Sub-Nyquist sampling process in presence of noisy sampling signal 350

Saruwatari, M., and Sugie, T. Efficient laser-diode-single-mode-fibre coupling using two confocal lenses 955
Sasaki, H., and Mikoshiba, N. Tunable magnetostatic surface wave demultiplexing filter/switch 700
Sasaki, I., Payne, D.N., and Adams, M.J. Measurement of refractive-index profiles in optical-fibre preforms by spatial-filtering technique 219
Sasaki, Y., Okamoto, K., Miya T., Kawachi, M., and Edahiro, T. see Okamoto, K.
Saseendran Pillai, P.R., and Sridhar, C.S. Tuning of transducer elements in transducer array 606
Satake, T., and Murata, H. Moulded multifibre connectors using rectangular multirod arrangement 281
Sato, K., and Asatani, K. Superimposed pulse modulation for fibre optic analogue video transmission using semiconductor laser diodes 538
Sato, K., Asatani, K., Maki, K., and Miki, T. see Asatani, K.
Sauter, E.G., and Grau, G.K. Excitation of steady-state power distribution in parabolic-index fibres at Gaussian TEM_{00}-beam 748
Sautereau, J.F., Graffeuil, J., Tantrarongroj, K., and Rossel, P. High efficiency GaAs Schottky-barrier gate f.e.t. oscillator 490
Saxena, R.R., Cooper, C.B., and Ludowise, M.J. see Cooper, C.B.
Scanlan, J.O., and Young, G.P. see Young, G.P.
Scavennec, A., and Ankri, D. see Ankri, D.
Schizas, C., and Evans, F.J. Rank-invariant transformations and controllability of large-scale systems 19
Schleher, D.C. Numerical evaluation of logarithmic receiver thresholds 875
Schlesak, J.J., Antar, Y.M.M., Hendry, A., Olsen, R.L., and Bérubé, R.C. see Antar, Y.M.M.
Schlosser, W.O., Wemple, S.H., and Steinberger, M.L. see Wemple, S.H.
Schnapper, A., Papuchon, M., and Puech, C. see Papuchon, M.
Schofield, J., Murray, R.J., and Mitchell, R.F. see Murray, R.J.
Scovell, P.D., and Young, J.M. Low temperature thermal annealing of arsenic implanted silicon 614
Sealy, B.J., Badawi, M.H., and Clegg, J.B. see Badawi, M.H.
Sealy, B.J., and Emerson, N.G. see Emerson, N.G.
Sebestyen, T., Mojzes, I., and Szigethy, D. Use of Ga in metal-GaAs contacts to eliminate large As loss peaks 504
Sedra, A.S., and Martin, K. see Martin, K.
Sedra, S., and Martin, K. see Martin, K.
Seebald, E., and Doring, K. -H. see Doring, K. -H.
Seevinck, E. Deriving stability criteria for nonlinear circuits with application to worst-case noise margin of I^2L 867
Segal, B., Kheirallah, H.N., Knight, J.P., Olsen, R.L., and McCormick, K.S. see Kheirallah, H.N.
Segawa, K., Mitsui, Y., Kobiki, M., Wataze, M., Otsubo, M., and Ishi, T. see Mitsui, Y.
Seikai, S., Yamanishi, T., Yoshimura, K., Suzuki, S., and Uchida, N. see Yamanishi, T.
Sen, T.K., Sridhar, N., and Srivastava, G.P. see Sridhar, N.
Senani, R. Floating ideal inductor with one d.v.c.c.s. (Comment) 117
Senani, R. New tunable synthetic floating inductors 382
Senani, R. Novel active RC realisations of tunable floating inductors 154
Senani, R. Novel circuit implementation of current conveyors using an o.a. and an o.t.a. 2
Senani, R. Novel sinusoidal oscillator employing grounded capacitors 62
Senani, R. Novel sinusoidal oscillator employing grounded capacitors (Comment) 863
Serizawa, H., Tanaka, T., and Tsujimoto, Y. see Tanaka, T.
Sethares, J.C., Owens, J.M., and Smith, C.V. M.S.W. nondispersive, electronically tunable time delay elements 825
Sewell, J.I., and Lau, J. see Lau, J.
Shah, N.J., Ahmed, H., Sanders, I.R., and Singleton, J.F. Activation of low dose silicon implants in GaAs by multiply scanned electron beams 433
Sharma, A.B., Saijonmaa, J., and Halme, S.J. Comparison of pulse responses of step-index fibres 557
Sharma, A.B., Saijonmaa, J., and Halme, S.J. see Saijonmaa, J.
Sharma, Y.K. Space charge limited current in an insulator at high fields 896
Shaw, H.J., Bergh. R.A., and Kotler, G. see Bergh, R.A.
Sheikh, N.J., and Jarem, J.M. see Jarem, J.M.
Sherlock, J.F. Delining thermal imager pictures 774
Sherman, A.B., Dobrovolsky, A.A., and Lemanov, V.V. Nonlinear acoustoelectroluminescence 37
Sherman, A.B., Dobrovolsky, A.A., Lemanov, V.V., Gal'Perin, Yu.M., and Kozub, V.I. see Dobrovolsky, A.A.
Shibata, T., Okada, K., Hashimoto, K., and Nagaki, Y. see Okada, K.
Shibuya, S., Nakahara, M., Sudo, S., Inagaki, N., Yoshida, K., Kokura, K., and Kuroha, T. see Nakahara, M.
Shichijo, H., Hess, K., and Stillman, G.E. Orientation dependence of ballistic electron transport and impact ionisation 208
Shin, S-Y., Joo, C-S., and Ra, J-W. see Joo, C-S.
Shirae, K., and Dalpadado, R.N.G. see Dalpadado, R.N.G.
Shooter, L.T., and Ettinger, G.M. see Ettinger, G.M.
Shur, M.S., and Eastman, L.F. GaAs n^+-p^-n^+ ballistic structure 522
Shur, M.S., Eastman, L.F., Stall, R., Woodard, D., Dandekar, N., Wood, C.E.C., and Board, K. see Eastman, L.F.
Sierra, M. Miniature microstrip bandpass filter with large stopbands 340
Siffert, P., Planat, M., Theobald, G., and Gagnepain, J.J. see Planat, M.
Sigel, G.H. Jr., Dandridge, A., Tveten, A.B., West, E.J., and Giallorenzi, T.G. see Dandridge, A.
Silard, A., Bodea, M., and Luca, M. Predicting the surge capability of power thyristors 325
Simin, G.S., and Levinshtein, M.E. see Levinshtein, M.E.
Simpson, R.S., and Cruz, J. see Cruz, J.
Sinclair, D.A., and Ash, E.A. Bond integrity evaluation using transmission scanning acoustic microscopy 880
Sinclair, D.A., and Smith, I.R. Dark field acoustic microscopy 627
Sinclair, D.A., Dürr, W., and Ash, E.A. see Dürr, W.
Sindoris, A.R., and Krowne, C.M. see Krowne, C.M.
Singh, H., and Tjhung, T.T. Error-rate measurements for s.f.s.k. with band limitation 64
Singh, H., and Khan, A.A. see Khan, A.A.
Singh, H.R., and Ahmed, K.U. see Ahmed, K.U.
Singh, S.P., and Pitt, C.W. see Pitt, C.W.
Singh, V. Novel active RC realisations of tunable floating inductors (Comment) 758
Singh, V. Novel sinusoidal oscillator employing grounded capacitors (Comment) 757
Singh, V. Stable reduced order Padé approximants using stability equation method (Comment) 820
Singh, V.K. Novel insensitive lossless inductor simulation through inverse function generation (Comment) 901
Singleton, J.F., Shah, N.J., Ahmed, H., and Sanders, I.R. see Shah, N.J.
Sinha, N.K. Reduction of multivariable systems 788
Sinha, S.N., and Agarawal, R.P. Reactance-loaded short-backfire arrays: new results 764
Sinha, S.N., and Agrawal, R.P. Reactance-controlled short-backfire array 253
Skorik, V.A., and Fursin, G.I. Semidistributed neuristor using plasma-coupled modulating transistors 676
Sladen, F.M.E., Ramskov Hansen, J.J., Adams, M.J., and Ankiewicz, A. see Ramskov Hansen, J.J.
Smith, A.M. Faraday effect in single-mode optical fibre using an injection laser light source 206
Smith, A.M. Single-mode fibre pressure sensitivity 773
Smith, B.M., and Millott, L.J. see Millott, L.J.
Smith, C.V., Sethares, J.C., and Owens, J.M. see Sethares, J.C.
Smith, D.C., and Tebbenham, R.L. Transient thermal analysis of integral-heatsink GaAs pulsed Gunn device 334
Smith, D.R., Chatterjee, A.K., Rejman, M.A.Z., Wake, D., and White, B.R. p-i-n f.e.t. hybrid optical receiver for 1.1-1.6 μm optical communication systems 750
Smith, D.R., Hooper, R.C., Ahmad, K., Jenkins, D., Mabbitt, A.W., and Nicklin, R. p-i-n/f.e.t. hybrid optical receiver for longer-wavelength optical communication systems 69
Smith, D.W., Malyon, D.J., and Berry, R.W. see Malyon, D.J.
Smith, I.R., and Sinclair, D.A. see Sinclair, D.A.
Snijder, J., and Ligtenberg, H.C.G. see Ligtenberg, H.C.G.
Snyder, A.W., and Sammut, R.A. see Sammut, R.A.
So, K. -M., and Narraway, J.J. see Narraway, J.J.
Sobaih, A., El-Konyaly, E.H., and El-Dokany, I. see El-Konyaly, E.H.
Sobhy, M.I., and Bedair, S.S. see Bedair, S.S.
Sobieski, P., and Delogne, P. Adaptive crosstalk cancellation for crosspolarised digital transmissions 385
Socha, J.B., and Rees, G.J. Ballistic electron transport in a nonparabolic band 872
Soderstrand, M.A., and Parks, G.B. see Parks, G.B.
Soliman, A.M. Novel phase lead inverting integrator and its application in two-integrator loop filters 475
Soliman, A.M. Novel two-o.a. three-resistor variable phase inverting amplifier 294
Soliman, A.M. Phase correction in two-integrator loop filters using new variable-phase inverting amplifier 186
Somekh, M., Lazarus, M.J., Pantoja, F.R., Novak, S., and Margison, S. see Lazarus, M.J.
Somekh, M.G., Richmond, W., Moroz, J., and Lazarus, M.J. Development of pulsed self-oscillating mixer 597
Sopilnik, A.V., and van Peppen, J.C.L. Representation of imperfect dielectric materials by an equivalent circuit 368
Sordo, B., Costa, B., Menaglia, U., Piccari, L., and Grasso, G. see Costa, B.
Sowers, J.J., Crowley, J.D., Janis, B.A., and Fank, F.B. see Crowley, J.D.
Spassov, L., Grantcharov, K., Borissov, M., Detchev, D., and Yossifov, E. see Grantcharov, K.
Speight, J.D., McMahon, R.A., Ahmed, H., and Dobson, R.M. see McMahon, R.A.
Spence, R., and Ilumoka, A. see Ilumoka, A.
Spriggs, H., and Nightingale, C. Method of designing filters with shaped passband response 267
Springthorpe, A.J., Noad, J.P., and Look, C.M. see Noad, J.P.
Sridhar, C.S., and Saseendran Pillai, P.R. see Saseendran Pillai, P.R.
Sridhar, N., Sen, T.K., and Srivastava, G.P. Determination of modal amplitudes by resolution of radiation patterns 12
Srinivasan, V., Wong, C.P., and Wang, M.L. Single-step continuous-tone computer-generated holograms 213
Srivastava, G.P., Sridhar, N., and Sen, T.K. see Sridhar, N.

Srivastava, N.C., and Bajpai, S.N. see Bajpai, S.N.
Stall, R., Eastman, L.F., Woodard, D., Dandekar, N., Wood, C.E.C., Shur, M.S., and Board, K. see Eastman, L.F.
Stall, R.A., Wood, C.E.C., Kirchner, P.D., and Eastman, L.F. Growth-parameter dependence of deep levels in molecular-beam-epitaxial GaAs 171
Stamenković, B.B. Synthesis of active RC multiport voltage transfer functions with reduced number of operational amplifiers (Comment) 333
Stanchak, C.M., Morkoc, H., Witkowski, L.C., Drummond, T.J., Cho, A.Y., and Streetman, B.G. see Morkoc, H.
Stanley, C.R., Macfadyen, D.N., and Wilkinson, C.D.W. see Macfadyen, D.N.
Steele, R., and Ismail, M.G.B. see Ismail, M.G.B.
Stefanović, M.Č. C.P.S.K. receiver performances in presence of carrier-frequency offset 182
Stein, R.A., Bartley, N.R., and Bruton, L.T. Continuously variable digital filters based on linear interpolation of coefficients 670
Steinberger, M.L., Wemple, S.H., and Schlosser, W.O. see Wemple, S.H.
Stephens, K.G., Szajnowski, W.J., and Hodgart, M.S. see Szajnowski, W.J.
Stevens, F.A., Westcott, B.S., and Brickell, F. see Westcott, B.S.
Stewart, W.J. Simplified parameter-based analysis of single-mode optical guides 380
Stillman, G.E., Chin, R., Holonyak, N. Jun., Tang, J.Y., and Hess, K. see Chin, R.
Stillman, G.E., Shichijo, H., and Hess, K. see Shichijo, H.
Stocker, P.J., Lee, C.P., and Tandon, J.L. see Lee, C.P.
Stockton, J.R. Proposed quarter squares double dual-slope digital wattmeter 819
Stoica, P. Comparison of two iterative estimation procedures 754
Stoisiek, M., Wolf, D., and Werner, W. Bipolar transistors with low 1/f noise 372
Stojadinović, N.D., and Popović, R.S. Elimination of emitter edge dislocations in silicon planar n-p-n transistors 842
Stojanović, V.S., and Pavlović, V.D. Transitional multiple-pole transfer functions for active-filter design 21
Stoltz, B., and Yevick, D. see Yevick, D.
Stoyanov, O. Resistor rotators of bridged- and double-T type 642
Strashilov, V.L., Hinkov, V.P., and Bransalov, K.P. Trapped-energy flexural mode filter 729
Streetman, B.G., Morkoc, H., Witkowski, L.C., Drummond, T.J., Stanchak, C.M., and Cho, A.Y. see Morkoc, H.
Stride, A.A., Pitt, C.W., and Trigle, R.I. see Pitt, C.W.
Stubkjaer, K., Suematsu, Y., Asada, M., Arai, S., and Adams, A.R. Measurement of refractive-index variation with free carrier density and temperature for 1.6 μm GaInAsP/InP lasers 895
Stuchly, M.A., Bahl, I.J., and Stuchly, S.S. see Bahl, I.J.
Stuchly, S.S., Bahl, I.J., and Stuchly, M.A. see Bahl, I.J.
Stueflotten, S., Jenssen, Ø., and Justnes, B.O. see Jenssen, Ø.
Stulz, L.W., Kaminow, I.P., Nahory, R.E., Pollack, M.A., and DeWinter, J.C. see Kaminow, I.P.
Suda, H., Chida, K., and Nakahara, M. Transmission loss in low grade $SiCl_4$ v.a.d. fibres 802
Sudo, S., Kawachi, M., Edahiro, T., and Chida, K. 21.2 km graded-index v.a.d. fibre with low loss and wide bandwidth 152
Sudo, S., Okazaki, H., Nakahara, M., and Horiguchi, M. Transmission properties of 30.4 km v.a.d. fibre 280
Sudo, S., Edahiro, T., Kawachi, M., and Nagai, H. see Edahiro, T.
Sudo, S., Hanawa, F., Kawachi, M., and Nakahara, M. see Hanawa, F.
Sudo, S., Nakahara, M., Chida, K., Hanawa, F., and Horiguchi, M. see Nakahara, M.
Sudo, S., Nakahara, M., Inagaki, N., Yoshida, K., Shibuya, S., Kokura, K., and Kuroha, T. see Nakahara, M.
Suematsu, Y., Arai, S., Asada, M., Itaya, Y., Tanbun-ek, T., and Kishino, K. see Arai, S.
Suematsu, Y., Kubota, M., Oohara, T., and Furuya, K. see Kubota, M.
Suematsu, Y., Sakakibara, Y., Furuya, K., and Utaka, K. see Sakakibara, Y.
Suematsu, Y., Stubkjaer, K., Asada, M., Arai, S., and Adams, A.R. see Stubkjaer, K.
Suematsu, Y., Utaka, K., Kobayashi, K., and Kishino, K. see Utaka, K.
Sueta, T., Izutsu, M., and Haga, H. see Izutsu, M.
Sugie, T., and Saruwatari, M. see Saruwatari, M.
Sugiyama, K., and Kano, H. see Kano, H.
Sugiyama, T., Inada, T., Okano, N., and Ishikawa, Y. see Inada, T.
Sumski, S., Capasso, F., Logan, R.A., Foy, P.W., and Manchon, D.D. see Capasso, F.
Sundara Murthy, K.M., and Cattermole, K.W. Evaluation of error probability for partial response systems 886
Susa, N., Kanbe, H., Nakagome, H., and Ando, H. see Kanbe, H.
Susa, N., Osaka, F., Nakazima, K., Kaneda, T., and Sakurai, T. see Osaka, F.
Susaki, W., Murotani, T., Oomura, E., Higuchi, H., and Namizaki, H. see Murotani, T.
Suzuki, S., Yamanishi, T., Yoshimura, K., Seikai, S., and Uchida, N. see Yamanishi, T.
Svilans, M.N., Beneking, H., Grote, N., and Roth, W. see Beneking, H.
Szajnowski, W.J., Hodgart, M.S., and Stephens, K.G. Ion beam co-ordinate monitor 674
Szepanski, W. Δ-entropy and rate distortion bounds for generalised Gaussian information sources and their applications to image signals 109
Szigethy, D., Sebestyen, T., and Mojzes, I. see Sebestyen, T.

T

Tabuchi, T., Hikita, M., Kinoshita, Y., and Kojima, H. see Hikita, M.
Tabuchi, T., Kojima, H., Kinoshita, Y., and Hikita, M. see Kojima, H.
Takada, T., Makimura, T., and Ishibashi, T. Unbiased InP detectors in the submillimetre wave region 765
Takahashi, S., Saito, H., and Iwane, G. Channelled substrate buried heterostructure InGaAsP/InP laser emitting at 1.55 μm 922
Takeshima, M., Nakagawa, K., and Ebisawa, F. see Nakagawa, K.
Takeuchi, S., Hamasaki, Y., Gotoh, H., and Katoh, M. see Hamasaki, Y.
Tanaka, T., Serizawa, H., and Tsujimoto, Y. Simple structure high isolation multi/demultiplexer 869
Tanbun-ek, T., Arai, S., Asada, M., Suematsu, Y., Itaya, Y., and Kishino, K. see Arai, S.
Tandon, J.L., Lee, C.P., and Stocker, P.J. see Lee, C.P.
Tang, J.Y., Chin, R., Holonyak, N. Jun., Stillman, G.E., and Hess, K. see Chin, R.
Tangonan, G.L., Persechini, D.I., Morrison, R.J., and Wysocki, J.A. Current sensing with metal-coated multimode optical fibres 958
Tanigawa, T., Washio, K., and Inoue, K. see Washio, K.
Tanikawa, K., Ito, Y., Maekawa, T., and Yamamoto, T. see Ito, Y.
Tanski, W.J. S.A.W. device reflectors weighted by combination of withdrawn and segmented lines 793
Tantrarongroj, K., Sautereau, J.F., Graffeuil, J., and Rossel, P. see Sautereau, J.F.
Tatham, H.L., Adams, A.R., Hayes, J.R., El-Sabbahy, A.N., and Greene, P.D. see Adams, A.R.
Tattersall, G., Ambikairajah, E., and Carey, M.J. see Ambikairajah, E.
Tavendale, A.J., Pearton, S.J., and Williams, A.A. see Pearton, S.J.
Taylor, D., Haykin, S., and Reilly, J. see Haykin, S.
Tebbenham, R.L., and Smith, D.C. see Smith, D.C.
Tegude, F.J., and Heime, K. Photo-f.e.t. method: high-resolution deep-level measurement technique using a m.e.s.f.e.t. structure 22
Tell, R., and Eng, S.T. 8 Gbit/s optical transmission with t.j.s. GaAlAs laser and p-i-n detection 497
Temes, G.C., and Ghanderi, M.B. Bilinear switched-capacitor ladder filter with reduced number of amplifiers 412
Temes, G.C., and Müller, G. see Müller, G.
Temkin, H., and Chin, A.K. Near-infra-red absorption using InGaAsP sources 437
Temmyo, J., Yamada, J-I., Yoshikawa, S., and Kimura, T. see Yamada, J-I.
Teng, T.C., Merritt, J.D., Velez, J., Peng, J., and Palkuti, L. Short-channel polysilicon-gate m.o.s.f.e.t.s fabricated by c.w. argon laser annealing of arsenic-implanted source and drain 477
Teo, T.M., and Harris, D.J. see Harris, D.J.
Thajchayapong, P., Puangpool, M., and Banjongjit, S. Maximally flat f.i.r. filter with prescribed cutoff frequency 514
Theobald, G., Planat, M., Gagnepain, J.J., and Siffert, P. see Planat, M.
Thomas, B. MacA., and James, G.L. see James, G.L.
Thompson, G.H.B., and Henshall, G.D. Nonradiative carrier loss and temperature sensitivity of threshold in 1.27 μm (GaIn)(AsP)/InP d.h. lasers 42
Thorvaldesen, T. Spiral antenna with integrated detector 484
Tihanyi, P., and Lindström, C. see Lindström, C.
Tihanyi, P., Lindström, C., Andersson, T., and Torphammar, P. see Lindström, C.
Titchmarsh, J.G., Rosiewicz, A., Gray, M.H., Irven, J., and Black, P.W. see Rosiewicz, A.
Tjhung, T.T., and Singh, H. see Singh, H.
Tomaru, S., Kawachi, M., and Edahiro, T. Fabrication of single-mode fibres by v.a.d. 511
Tomasetta, L.R., Liu, Y.Z., Anderson, R.J., and Deyhimy, I. see Liu, Y.Z.
Tomita, N., Fuchigami, T., Kojima, N., Ohmura, M., and Yamamoto, H. see Fuchigami, T.
Tong, K.Y. Single-fault location in a linear analogue system with variable sensitivity matrix 221
Torphammar, P., and Eng, S.T. Picosecond pulse generation in semiconductor lasers using resonance oscillation 587
Torphammar, P., Lindström, C., Tihanyi, P., and Andersson, T. see Lindström, C.
Toussaint, G.T. Algorithms for computing relative neighbourhood graph (Comment) 860
Toutain, S., Gelin, Ph., and Legier, J.F. see Gelin, Ph.
Tozer, T.C., and Kollerstrom, J. Penalties of hard decision in signal detection 199
Trigle, R.I., Pitt, C.W., and Stride, A.A. see Pitt, C.W.
Truong, T.K., Miller, R.L., and Reed, I.S. see Miller, R.L.
Tsang, W.T. Symmetric separate confinement heterostructure lasers with low threshold and narrow beam divergence by M.B.E. 939
Tserng, H.Q., Macksey, H.M., and Nelson, S.R. 2W, 8-12 GHz GaAs f.e.t. amplifier 680

Tsironis, C., and Harrop, P. Dual gate GaAs m.e.s.f.e.t. phase shifter with gain at 12 GHz 553
Tsividis, Y.P. Method for signal processing with transfer function coefficients dependent only on timing 796
Tsuchiya, H., Kawana, A., Miya, T., and Imoto, N. see Kawana, A.
Tsuchiya, H., and Yamamoto, Y. see Yamamoto, Y.
Tsujimoto, Y., Tanaka, T., and Serizawa, H. see Tanaka, T.
Tuladhar, K.K. High frequency stability of near-perfect active phase compensated integrators 888
Tuladhar, K.K. Tunable active-phase-compensated universal biquadratic filter 44
Turner, L.F., Frangoulis, E., and Alcaim, A. Further results on relationship between system delay and transmission rate in time encoded speech-type systems 947
Tveten, A.B., Dandridge, A., Davis, C.M., and Giallorenzi, T.G. Fibre optic accelerometer 854
Tveten, A.B., Dandridge, A., Sigel, G.H. Jr., West, E.J., and Giallorenzi, T.G. see Dandridge, A.

U

Uchida, N., Yamanishi, T., Yoshimura, K., Suzuki, S., and Seikai, S. see Yamanishi, T.
Ueno, F., and Inoue, T. see Inoue, T.
Ueno, F., Inoue, T., and Fukuda, Y. see Inoue, T.
Uki, S., and Urabe, S. see Urabe, S.
Urabe, S., and Uki, S. Voltage controlled monolithic s.a.w. phase shifter using m.z.o.s. structure 777
Urgell, J.J., Pedron, T.P., Lanteri, J.P., and Garrigues, M. see Pedron, T.P.
Urquhart, R.B. Algorithms for computation of relative neighbourhood graph 556
Utaka, K., Kobayashi, K., Kishino, K., and Suematsu, Y. 1.5-1.6 μm GaInAsP/InP integrated twin-guide lasers with first-order distributed Bragg reflectors 455
Utaka, K., Sakakibara, Y., Furuya, K., and Suematsu, Y. see Sakakibara, Y.

V

Vakil, S.M., and Davies, D.E.N. see Davies, D.E.N.
van de Capelle, A.R., and Pues, H.F. see Pues, H.F.
van der Donk, J., and Lagasse, P.E. Analysis of geodesic lenses by beam propagation method 292
Van Ommeren, M.J.S., Herben, M.H.A.J., and Arnbak, J. Improved orbit utilisation by interferometric sidelobe suppression 937
van Peppen, J.C.L., and Sopilnik, A.V. see Sopilnik, A.V.
Velasco, J., Lloris, A., and Prieto, A. see Lloris, A.
Velez, J., Teng, T.C., Merritt, J.D., Peng, J., and Palkuti, L. see Teng, T.C.
Venger, C., Martin, G.M., and Berth, M. see Martin, G.M.
Vidallon, C.M. Improved minimax algorithm for circuit optimisation 436
Vilar, E., Haddon, J., Lo, P., and Moulsley, T.J. see Haddon, J.
Viswanathan, T.L., and Viswanathan, T.R. see Viswanathan, T.R.
Viswanathan, T.R., and Viswanathan, T.L. Increasing the clock frequency of switched-capacitor filters 316
Viswanathan, T.R., Faruque, S.M., and Vlach, J. see Faruque, S.M.
Vlach, J., Faruque, S.M., and Viswanathan, T.R. see Faruque, S.M.
Von Grünigen, D.C., Brugger, U.W., and Moschytz, G.S. Novel stray-insensitive switched-capacitor integrator 395
von Gruningen, D.C., Brugger, U.W., and Hosticka, B.J. Bottom-plate stray-insensitive bilinear switched-capacitor integrators 25
Vowinkel, B. Cryogenic 2-4 GHz f.e.t. amplifier 730

W

Wait, J.R. Propagation in rectangular tunnel with imperfectly conducting walls 521
Wake, D., Smith, D.R., Chatterjee, A.K., Rejman, M.A.Z., and White, B.R. see Smith, D.R.
Wakimoto, T., and Matsumura, M. New n-channel m.o.s.f.e.t.s. 402
Walf, G., Baack, C., Elze, G., and Enning, B. see Baack, C.
Wang, M.L., Srinivasan, V., and Wong, C.P. see Srinivasan, V.
Wang, M.-T., Young, J.H., and Brezovich, I.A. see Young, J.H.
Washio, K., Inoue, K., and Kishida, S. Efficient large-frequency-shifted three-wave mixing in low dispersion wavelength region in single-mode optical fibre 658
Washio, K., Inoue, K., and Tanigawa, T. Efficient generation of near-i.r. stimulated light scattering in optical fibres pumped in low-dispersion region at 1.3 μm 331
Watanabe, N., Kato, Y., Dohsen, M., and Kasahara, J. see Kato, Y.
Watanabe, N., and Mori, Y. see Mori, Y.
Watanabe, N., Mori, Y., Matsuda, O., and Morizane, K. see Mori, Y.
Watanabe, R., and Asatani, K. 1 x 2 optical switch using new type of pentagonal prism 257
Watanabe, R., Nosu, K., and Fujii, Y. Optical grating multiplexer in the 1.1-1.5 μm wavelength region 108
Watanabe, R., Nosu, K., Harada, T., and Kita, T. Optical demultiplexer using concave grating in 0.7-0.9 μm wavelength region 106
Watanabe, R., and Nosu, K. see Nosu, K.
Wataze, M., Mitsui, Y., Kobiki, M., Segawa, K., Otsubo, M., and Ishi, T. see Mitsui, Y.
Wehrhahn, E. Evaluation of transfer functions of ideal s.c. networks in z-domain using standard linear symbolic or semi-symbolic network analysis programs 801
Weidel, E., and Guttmann, J. Asymmetric T-couplers for fibre optic data buses 673
Weidlein, J., Renz, H., Benz, K.W., and Pilkuhn, M.H. see Renz, H.
Weierholt, A. Modal dispersion of optical fibres with a composite (alpha)-profile graded-index core e75
Wemple, S.H., Steinberger, M.L., and Schlosser, W.O. Relationship between power added efficiency and gate-drain avalanche in GaAs m.e.s.f.e.t.s. 459
Werner, W., Stoisiek, M., and Wolf, D. see Stoisiek, M.
Wessels, B.W., and Besomi, P. see Besomi, P.
West, E.J., Dandridge, A., Tveten, A.B., Sigel, G.H. Jr., and Giallorenzi, T.G. see Dandridge, A.
Westbrook, L.D., Fiddyment, P.J., and Robson, P.N. Photoelastic channel optical waveguides in epitaxial GaAs layers 169
Westcott, B.S., Stevens, F.A., and Brickell, F. Exact synthesis of offset dual reflectors 168
Westwig, R.A., Bhagavatula, V.A., Love, W.F., and Keck, D.B. see Bhagavatula, V.A.
Whale, G. Construction of optimal low-rate convolutional codes 767
White, B.R., Smith, D.R., Chatterjee, A.K., Rejman, M.A.Z., and Wake, D. see Smith, D.R.
White, T.A., and Allnatt, J.W. Double-stimulus quality rating method for television digital codecs 714
Wickramasinghe, H.K., and Petts, C.R. see Petts, C.R.
Wilden, H. Crow's-nest antenna 256
Wilkinson, C.D.W., Macfadyen, D.N., and Stanley, C.R. see Macfadyen, D.N.
Williams, A.A., Pearton, S.J., and Tavendale, A.J. see Pearton, S.J.
Williams, G.M., and Gertner, E.R. n-channel m.i.s.f.e.t.s. in epitaxial HgCdTe/CdTe 839
Williams, N., and Inggs, M.R. see Inggs, M.R.
Winzer, G., Mahlein, H.F., Michel, H., Rauscher, W., and Reichelt, A. see Mahlein, H.F.
Witkowski, L.C., Morkoc, H., Drummond, T.J., Stanchak, C.M., Cho, A.Y., and Streetman, B.G. see Morkoc, H.
Witten, I.H., and Ha, Y.K. see Ha, Y.K.
Wolf, D., Stoisiek, M., and Werner, W. see Stoisiek, M.
Wolfenson, M., and Da Rocha, V.C. Jun. Soft-decision decoding with unknown source distribution 949
Wong, C.P., Srinivasan, V., and Wang, M.L. see Srinivasan, V.
Wood, C.E.C., Eastman, L.F., Stall, R., Woodard, D., Dandekar, N., Shur, M.S., and Board, K. see Eastman, L.F.
Wood, C.E.C., Malik, R.J., Aucoin, T.R., Ross, R.L., Board, K., and Eastman, L.F. see Malik, R.J.
Wood, C.E.C., Stall, R.A., Kirchner, P.D., and Eastman, L.F. see Stall, R.A.
Wood, D.L., Melliar-Smith, C.M., Lazay, P.D., Pasteur, G.A., and Chandross, E.A. see Melliar-Smith, C.M.
Woodard, D., Eastman, L.F., Stall, R., Dandekar, N., Wood, C.E.C., Shur, M.S., and Board, K. see Eastman, L.F.
Woodcock, J.M., and Harris, J.J. see Harris, J.J.
Wysocki, J.A., Tangonan, G.L., Persechini, D.I., and Morrison, R.J. see Tangonan, G.L.

Y

Yamada, J., Kobayashi, S., Machida, S., and Kimura, T. see Kobayashi, S.
Yamada, J-I., Machida, S., Mukai, T., and Kimura, T. 800 Mbit/s optical transmission experiments with dispersion-free fibres at 1.5 μm 115
Yamada, J-I., Temmyo, J., Yoshikawa, S., and Kimura, T. 1.6 Gbit/s optical receiver at 1.3 μm with saw timing retrieval circuit 57
Yamada, J-I., Murakami, Y., Sakai, J-I., and Kimura, T. see Murakami, Y.
Yamada, K., and Daikoku, K. Error performance of frequency-hopped d.p.s.k. system 305
Yamaguchi, M., Hashimoto, K-Y., Yoshida, M., and Kogo, H. see Hashimoto, K-Y.
Yamamoto, H., Fuchigami, T., Kojima, N., Ohmura, M., and Tomita, N. see Fuchigami, T.
Yamamoto, T., Ito, Y., Maekawa, T., and Tanikawa, K. see Ito, Y.
Yamamoto, Y., Hagiwara, Y., Iwai, T., and Fujisawa, K. Parallel-wire meander line deflection circuit for electron beams 654 e863
Yamamoto, Y., and Tsuchiya, H. Optical receiver sensitivity improvement by a semiconductor laser preamplifier 233
Yamamoto, Y., Saito, S., and Kimura, T. see Saito, S.
Yamanishi, T., Yoshimura, K., Suzuki, S., Seikai, S., and Uchida, N. Modified silicone as new type of primary coat for optical fibre 100
Yamauchi, J., and Nakano, H. see Nakano, H.
Yariv, A., Katz, J., Bar-Chaim, N., and Margalit, S. see Katz, J.
Yevick, D., and Stoltz, B. Near-field distributions in selectively excited elliptical optical fibres 210
Yi, M-G. Physical dependence of output conductance of voltage driven b.j.t.s 861
Yip, G.L., and Puc, A.B. see Puc, A.B.
Yokoyama, H., Ito, H., and Inaba, H. see Ito, H.
Yoneda, S., Emura, M., and Fukui, Y. see Emura, M.

Yoshida, K., Nakahara, M., Sudo, S., Inagaki, N., Shibuya, S., Kokura, K., and Kuroha, T. see Nakahara, M.
Yoshida, M., Hashimoto, K-Y., Yamaguchi, M., and Kogo, H. see Hashimoto, K-Y.
Yoshida, Y., Hotate, K., Higashiguchi, M., and Niwa, N. see Hotate, K.
Yoshikawa, S., Yamada, J-I., Temmyo, J., and Kimura, T. see Yamada, J-I.
Yoshimura, K., Yamanishi, T., Suzuki, S., Seikai, S., and Uchida, N. see Yamanishi, T.
Yoshizawa, T., Kurokawa, T., and Katayama, Y. see Kurokawa, T.
Yossifov, E., Grantcharov, K., Borissov, M., Detchev, D., and Spassov, L. see Grantcharov, K.
Young, G.P., and Scanlan, J.O. Treatment of noise-figure calculations in microwave transistor amplifiers 17
Young, J.H., Wang, M.-T., and Brezovich, I.A. Frequency/depth-penetration considerations in hyperthermia by magnetically induced currents 358
Young, J.M., and Scovell, P.D. see Scovell, P.D.
Yuan, H.T., Doerbeck, F.H., and McLevige, W.V. Ion implanted GaAs bipolar transistors 637

Z

Zakarevicius, R.A. Determining transfer functions, especially at high frequencies 508
Zamerowski, T.J., Olsen, G.H., and Digiuseppe, N.J. see Olsen, G.H.
Ziegler, H., and Bromba, M.U.A. see Bromba, M.U.A.
Zimmermann, J., Fauquembergue, R., Charef, M., and Constant, E. Electron dynamics in P-Si m.o.s.f.e.t. inversion channels 664
Znamirowski, Z., and Czarczynski, W. High radiation effects in X-ray lithography 178
Zufferey, J. -L., and Krummenacher, F. see Krummenacher, F.
Zurada, J., and Goodman, K. Equivalent circuit of multiplying d.a.c. using R-2R ladder network 925

Subject index

ACOUSTIC DEVICES

Diode laser sensor. A.Dandridge, R.O.Miles and T.G.Giallorenzi 948

ACOUSTIC MICROSCOPY

Acoustic microscopy in gases. C.R.Petts and H.K.Wickramasinghe 9

Bond integrity evaluation using transmission scanning acoustic microscopy. D.A.Sinclair and E.A.Ash 880

ACOUSTICS

Combined triple-transit and bulk-wave suppression in s.a.w. delay line. D.J.Gunton 149 e240

Detection of plastic deformation in metals with photoacoustic microscope. M.Luukkala and S.G.Askerov 84

Effective data collection aperture in long-wavelength imaging systems. J.C.Bennett and S.Abdul-Jauwad 696

High resolution acoustic probe. W.Dürr, D.A.Sinclair and E.A.Ash 805

Performance of sputtered SiO_2 film as acoustic antireflection coating at sapphire/water inerface. J.Kushibiki, T.Sannomiya and N.Chubachi 737

Photoacoustic effect in laser annealing. K.Hoh 931

S.A.W. monolithic acoustoelectronic oscillator. Yu.V.Gulyaev, I.M.Kotelyansky, A.V.Medved and R.A.Mishkinis 114

ACTIVE FILTERS

Bottom-plate stray-insensitive bilinear switched-capacitor integrators. D.C.von Gruningen, U.W.Brugger and B.J.Hosticka 25

High frequency stability of near-perfect active phase compensated integrators. K.K.Tuladhar 888

Monolithic v.c.c.s. for high-frequency RC active filters. J.W.Haslett, M.K.N.Rao and L.T.Bruton 175 e444

New tunable synthetic floating inductors. R.Senani 382

Novel active filters using amplifier pole. P.V.Ananda Mohan 378 e483

Transitional multiple-pole transfer functions for active-filter design. V.S.Stojanović and V.D.Pavlović 21

Tunable active-phase-compensated universal biquadratic filter. K.K.Tuladhar 44

ACTIVE NETWORKS

Novel active-compensated weighted summer. A.Rodriguez-Vazquez and J.L.Huertas 394

Novel active RC realisations of tunable floating inductors. R.Senani 154

Novel active RC realisations of tunable floating inductors (Comment). V.Singh 758

Novel circuit implementation of current conveyors using an o.a. and an o.t.a.. R.Senani 2

Novel insensitive lossless inductor simulation through inverse function generation. R.Nandi 481

Novel phase lead inverting integrator and its application in two-integrator loop filters. A.M.Soliman 475

Novel sinusoidal oscillator employing grounded capacitors. R.Senani 62

Novel sinusoidal oscillator employing grounded capacitors (Comment). R.Senani 863

Novel sinusoidal oscillator employing grounded capacitors (Comment). V.Singh 757

Novel two-o.a. three-resistor variable phase inverting amplifier. A.M.Soliman 294

Single element controlled oscillator without external capacitors. V.P.Pyara and S.S.Jamuar 607

Various approximating functions for cascade or ladder simulating RC active networks. R.Leuenberger 309

ADAPTIVE SYSTEMS AND CONTROL

Adaptive Kalman filter equaliser. E.Dalle Mese and G.Corsini 547

Estimation of a sinusoid in uncorrelated noise using adaptive line enhancer. V.U.Reddy 473

L.M.S. algorithm for sequentially adapting all-zero digital filters in modified cascade form. P.C.Ching and C.C.Goodyear 270

ALGORITHMS

Algorithms for computing relative neighbourhood graph (Comment). G.T.Toussaint 860

Construction of optimal low-rate convolutional codes. G.Whale 767

Delining thermal imager pictures. J.F.Sherlock 774

Efficient algorithm for determination of a.r. part of a.r.m.a. model. G.Carayannis, N.Kalouptsidis and D.Manolakis 656

Evaluation of error probability for partial response systems. K.M.Sundara Murthy and K.W.Cattermole 886

Fast algorithm for encoding the (255,223) Reed-Solomon code over $GF(2^8)$. R.L.Miller, T.K.Truong and I.S.Reed 222

Improved minimax algorithm for circuit optimisation. C.M.Vidallon 436

More about a thinning algorithm. C.Arcelli, L.P.Cordella and S.Levialdi 51 e240

Multiplexer logic circuit design using cubical complexes. A.B.Ektare and D.P.Mital 495 e718

Reduction of multivariable systems. N.K.Sinha 788

Statistical approach to reduction of circuit performance variability. A.Ilumoka and R.Spence 761

AMPLIFIERS

Cryogenic 2-4 GHz f.e.t. amplifier. B.Vowinkel 730

Deduction of amplifier phase transfer characteristic from measured a.m./p.m. conversion-coefficient characteristic. M.T.Abuelma'atti and J.G.Gardiner 298

Error rates of phase-modulated signals in multilink system with interference. I.M.Kostić 599 e718

Floating ideal inductor with one d.v.c.c.s. (Comment). R.Senani 117

High-gain c.m.o.s. cascode operational amplifier. F.Krummenacher and J.-L.Zufferey 232

Inclusion of amplifier finite gain and bandwidth in analysis of switched-capacitor filters. J.Lau and J.I.Sewell 462

New switched-capacitor immittance converter using operational amplifier leapfrog structure. T.Inoue and F.Ueno 266

Novel active-compensated weighted summer. A.Rodriguez-Vazquez and J.L.Huertas 394

Novel two-o.a. three-resistor variable phase inverting amplifier. A.M.Soliman 294

Synthesis of active RC multiport voltage transfer functions with reduced number of operational amplifiers (Comment). B.B.Stamenković 333

Tunable active-phase-compensated universal biquadratic filter. K.K.Tuladhar 44

ANALOGUE-DIGITAL CONVERSION

Automatic aperture performance measurement for high speed analogue-digital convertors. K.Gardner and P.T.Johnson 741

Equivalent circuit of multiplying d.a.c. using R-2R ladder network. J.Zurada and K.Goodman 925

Integrated optic a.d. convertor based on bulk acousto-optic interaction. M.Gottlieb and G.B.Brandt 359

New a.d. convertor with special application to medium precision platinum resistance thermometry. C.P.Pickup 578

Proposed quarter squares double dual-slope digital wattmeter. J.R.Stockton 819

ANNEALING

Alloying behaviour of Au-Ge/Pt ohmic contacts to GaAs by pulsed electron beam and furnace heating. C.P.Lee, J.L.Tandon and P.J.Stocker 849

Low temperature thermal annealing of arsenic implanted silicon. P.D.Scovell and J.M.Young 614

Pulsed electron-beam annealing of phosphorus-implanted silicon. T.Inada, T.Sugiyama, N.Okano and Y.Ishikawa 54

Redistribution of chromium in semi-insulating GaAs: Cr during laser annealing. M.H.Badawi, B.J.Sealy and J.B.Clegg 554

ANTENNA ARRAYS

Synthesis of planar arrays based on convolution technique. S.R.Laxpati 918

ANTENNAS

Circularly polarised radiation from narrow wall slots in rectangular waveguide. D.R.Hill 559

Compact directional V.H.F. antennas. H.M.Buettner 938

Comparison of G/T between dual-reflector and primary-focus antennas. G.L.James and B.MacA.Thomas 286

Crosspolarisation characteristics of linear comb-line microstrip antennas. A.K.Brown 743

Crow's-nest antenna. H.Wilden 256

Determination of modal amplitudes by resolution of radiation patterns. N.Sridhar, T.K.Sen and G.P.Srivastava 12

E-plane coupling between two rectangular microstrip antennas. C.M.Krowne 635

Effect of profile errors with large correlation diameter on axisymmetric antenna crosspolarisation. J.A.Jervase and S.I.Ghobrial 663
Exact synthesis of offset dual reflectors. B.S.Westcott, F.A.Stevens and F.Brickell 168
Field probe for measuring both amplitude and phase of antenna radiation patterns. D.E.N.Davies and S.M.Vakil 873
H-plane coupling between rectangular microstrip antennas. C.M.Krowne and A.R.Sindoris 211
High-gain flat-plate phase-monopulse antenna. R.J.Dewey 30
Maximisation of signal/noise ratio in array with broadened zero. P.C.K.Kwok and P.S.Brandon 60
Moment-method solution of directed dipole antennas. R.Neri 453
New commutated Doppler microwave landing system. F.R.Connor 365
New microstrip slot radiator for medical applications. I.J.Bahl, S.S.Stuchly and M.A.Stuchly 731
New realisation of maximum likelihood receiver for low-angle tracking radar. S.Haykin, J.Reilly and D.Taylor 288
New technique for efficient pattern computation of aperture and reflector antennas. R.Mittra and W.L.Ko 549
New wideband microstrip antenna using log-periodic technique. P.S.Hall 127
Numerical analysis of radial thin-wire antenna in presence of conducting sphere. B.D.Milovanović 611
Optimum antenna separation for space diversity in l.o.s. radio links over flat ground. J.A.Garcia-Lopez and V.Casares-Giner 717
Pattern synthesis of cylindrical slot antenna. J.M.Jarem and N.J.Sheikh 383
Radiation characteristics of helix antenna with parasitic elements. H.Nakano and J.Yamauchi 687
Reactance-controlled short-backfire array. S.N.Sinha and R.P.Agrawal 253
Reactance-loaded short-backfire arrays: new results. S.N.Sinha and R.P.Agarawal 764
Reception of phase-locked l.f. and m.f. transmissions by receivers having ferrite-rod antennas. P.Knight 40
Reduction of sidelobes in uniformly excited arrays with element pattern control. D.R.Hill 134
Reflector antenna profile measurement using ultrasound. C.G.Parini and P.J.B.Clarricoats 544
Spiral antenna with integrated detector. T.Thorvaldesen 484
Stationary phase method for far-field computation of defocused reflector antennas. M.H.A.J.Herben, R.Middelkoop and F.J.J.Gielkens 519
Validity of the quasi-tem approximation for the modes supported by a horizontal wire above ground. M.P.Carpentier and A.F.Dos Santos 85

AUTOMATIC TESTING

Single-fault location in a linear analogue system with variable sensitivity matrix. K.Y.Tong 221

BANDPASS FILTERS

Trapped-energy flexural mode filter. V.L.Strashilov, V.P.Hinkov and K.P.Bransalov 729

BINARY SEQUENCES

Properties of a simple noise-sequence generator. W.Freeman and S.M.Hebden 55
Recursive code generation based on m-sequence. J.M.Potter 858
Soft-decision decoding with unknown source distribution. M.Wolfenson and V.C.Jun.Da Rocha 949

BIPOLAR DEVICES

Bipolar operation of power junction field effect transistors. B.Jayant Baliga 300
Bipolar transistors with low 1/f noise. M.Stoisiek, D.Wolf and W.Werner 372
Current mirror saturation sensing technique. B.L.Hart 927
Design and evaluation of a planar GaAlAs-GaAs bipolar transistor. D.Ankri and A.Scavennec 41
Early voltage uniqueness test for bipolar junction transistors. B.L.Hart 703
Elimination of emitter edge dislocations in silicon planar n-p-n transistors. N.D.Stojadinović and R.S.Popović 842
Ion implanted GaAs bipolar transistors. H.T.Yuan, F.H.Doerbeck and W.V.McLevige 637
Modulating transistor: a new class of semiconductor device. G.I.Fursin 662
Physical dependence of output conductance of voltage driven b.j.t.s. M-G.Yi 861

BIREFRINGENCE

Birefringence in slightly elliptical optical fibres. R.A.Sammut 728
Single-mode fibre fractional wave devices and polarisation controllers. H.C.Lefevre 778
Single-mode fibre pressure sensitivity. A.M.Smith 773
Single-polarisation single-mode optical fibre with refractive-index pits on both sides of core. T.Okoshi and K.Oyamada 712

BROADCASTING

Reception of phase-locked l.f. and m.f. transmissions by receivers having ferrite-rod antennas. P.Knight 40

CABLES

New star quad symmetrical cable. T.Fuchigami, N.Kojima, M.Ohmura, N.Tomita and H.Yamamoto 204
Polarisation-maintaining single-mode fibre cable design. L.Jeunhomme and M.Monerie 921

CAPACITORS AND CAPACITANCE

Effects of capacitance at crossover wirings in power GaAs m.e.s.f.e.t.s.. Y.Aono, A.Higashisaka and F.Hasegawa 417
Estimation of fringing capacitance of electrodes on s.i. GaAs substrate. A.Higashisaka and F.Hasegawa 411
Measurement arrangement for direct capacitance/surface-potential recording on m.o.s. capacitor. H.C.G.Ligtenberg and J.Snijder e45
Novel strays-insensitive switched-capacitor integrator realising the bilinear Z-transform. A.Knob 173

CHARGE-COUPLED DEVICES

C.C.D./C.M.O.S. transversal filter using switched-capacitor technique for signal detection. Y.Ito, T.Maekawa, T.Yamamoto and K.Tanikawa 724
Discrete cosine transform processor using a c.c.d. programmable transversal filter. N.Kapur, J.Mavor and M.A.Jack 139
Error-rate measurements for s.f.s.k. with band limitation. H.Singh and T.T.Tjhung 64
Implementation of prime transform algorithm using c.c.d. programmable transversal filter. N.Kapur and S.C.Dutta Roy 809
New frequency division circuit using b.b.d.. M.Emura, Y.Fukui and S.Yoneda 530
Proton-bombardment isolated GaAlAs/GaAs charge-coupled devices. Y.Z.Liu, R.J.Anderson, I.Deyhimy and L.R.Tomasetta 327

CIRCUIT THEORY AND DESIGN

Applications of scattering matrix for development of microwave mixers. W.Hauth 501
Arbitrary phase polynomials. L.F.Lind and S.A.Mohammed 78
Cascade synthesis of switched-capacitor networks employing voltage inverter switches. M.K.Li 370
Circuit implementation of current conveyor. J.L.Huertas 225
Current mirror saturation sensing technique. B.L.Hart 927
Data-transmission filters for duobinary systems. L.F.Lind and A.A.De Albuquerque 228
Deriving stability criteria for nonlinear circuits with application to worst-case noise margin of I^2L. E.Seevinck 867
Design of bandstop filters by reactance transformation. J.B.Marino-Acebal, C.Nadeu-Camprubi and E.Masgrau-Gomez 105
Easing prefiltering requirements of s.c. filters. K.Martin and A.S.Seara 613
Floating ideal inductor with one d.v.c.c.s. (Comment). R.Senani 117
Frequency-multiple generation technique using Chebyshev polynomials. S.Osowski 91
Generation of nanosecond high-voltage pulses with high repetition rate. M.Kowatsche and J.Lafferl 196
High current class AB convertor technique. A.Nedungadi 418
Improved circuit elements for switched-capacitor ladder filters. M.S.Lee 131
Improved circuit for switched-capacitor simulation of an inductor. J.A.Nossek 141
Improved minimax algorithm for circuit optimisation. C.M.Vidallon 436
Lossless inductor simulation: novel configurations using d.v.c.c.s.. R.Nandi 666
Method for signal processing with transfer function coefficients dependent only on timing. Y.P.Tsividis 796
Modified nodal approach to network sensitivity calculation for one-dimensional orthogonal search technique. J.T.Ogrodzki 641
Monolithic v.c.c.s. for high-frequency RC active filters. J.W.Haslett, M.K.N.Rao and L.T.Bruton 175 e444
Negative failsafe sequential circuits. N.Gaitanis and C.Halatsis 615
New bilinear switched-capacitor immittance convertor circuit. T.Inoue and F.Ueno 285

Novel active R supercapacitor simulation: applications in low sensitivity multifunction network realisation. A.R.Saha and R.Nandi 570
Novel f.d.n.c. simulation using current conveyors. K.Pal 639
Novel insensitive lossless inductor simulation through inverse function generation. R.Nandi 481
Novel insensitive lossless inductor simulation through inverse function generation (Comment). V.K.Singh 901
Novel strays-insensitive switched-capacitor integrator realising the bilinear Z-transform. A.Knob 173
Novel submicroamper current-source design technique for monolithic circuits. R.W.J.Barker and B.L.Hart 609
Parametric interactions when resonator reactances are varied in antiphase. B.Z.Kaplan 343
Phase correction in two-integrator loop filters using new variable-phase inverting amplifier. A.M.Soliman 186
Pole sensitivity of all-pole lowpass LC ladder networks. J.K.Fidler 856
Pseudopower in switched-capacitor filters. M.K.Li 813
Resistor rotators of bridged- and double-T type. O.Stoyanov 642
Sampled-data recursive integrator for ultra-low-frequency wideband phase shifter. M.Emura, Y.Fukui and S.Yoneda 330
Simple method for analysis of a class of switched-capacitor filters. G.Müller and G.C.Temes 852
Switched-capacitor lowpass filter without active components. S.Manetti and A.Liberatore 883
Synthesis of nonlinear functions using continued fraction expansion. A.Cichocki 431
Transient response of sample-and-hold circuits. B.Guryanov 123

COAXIAL CABLES

Intersymbol interference in misequalised coaxial systems. D.Munoz Rodriguez and K.W.Cattermole 891

CODES AND CODING

7B8B balanced code with simple error detecting capability. R.Brooks 458
Adaptive pel location coding for bilevel facsimile signals. M.G.B.Ismail and R.Steele 361
Block adaptive prediction of colour television signals. H.Gharavi 226
Class of block codes for the Gaussian channel. D.E.Lazić 185
Connection between primitive generators of $GF(2^n)$. B.Arazi 223
Construction of optimal low-rate convolutional codes. G.Whale 767
Fast algorithm for encoding the (255,223) Reed-Solomon code over $GF(2^8)$. R.L.Miller, T.K.Truong and I.S.Reed 222
Implementation of mitre public key cryptographic system. J.E.Hershey 930
Line coding and burst transmission in the local network. H.B.Groen 165
New line code for digital subscriber loop. Ø.Jenssen, B.O.Justnes and S.Stueflotten 847
New processing technique for digital facsimile transmission. M.G.B.Ismail and R.J.Clarke 355
Power spectra of HDBn signals. D.Drajić and G.Petrović 289
Recursive code generation based on m-sequence. J.M.Potter 858
Soft-decision decoding with unknown source distribution. M.Wolfenson and V.C.Jun.Da Rocha 949

COMMUNICATION NETWORKS

Optical demultiplexer using concave grating in 0.7-0.9 μm wavelength region. R.Watanabe, K.Nosu, T.Harada and T.Kita 106
Optical grating multiplexer in the 1.1-1.5 μm wavelength region. R.Watanabe, K.Nosu and Y.Fujii 108
Optimal phases of maximal length sequences for asynchronous spread-spectrum multiplexing. F.D.Garber and M.B.Pursley 756

COMPUTER-AIDED DESIGN

Improved minimax algorithm for circuit optimisation. C.M.Vidallon 436

COMPUTER APPLICATIONS

Practical realisation of mod p, p prime multiplier. A.S.Ramnarayan 466
Single-step continuous-tone computer-generated holograms. V.Srinivasan, C.P.Wong and M.L.Wang 213

COMPUTERS

Technique for performing multiplication on a 16-bit microprocessor using an extension of Booth's algorithm. E.Ambikairajah and M.J.Carey 53

CONTROL THEORY

Disturbance rejection and multivariable self-tuning controllers. T.Hesketh 404
Double-sided least-squares problem with diagonal constraints. K.V.M.Fernando and H.Nicholson 82
Rank-invariant transformations and controllability of large-scale systems. C.Schizas and F.J.Evans 19
Stability of certain time-varying nonlinear systems. S.Mossaheb 190
System identification: approach to a coherent picture through template functions. P.Eykhoff 502

CONVERTORS

High current class AB convertor technique. A.Nedungadi 418

CONVOLUTION

Efficient miniature s.a.w. convolver. B.J.Darby, D.J.Gunton, M.F.Lewis and C.O.Newton 726

CORRELATION AND CORRELATORS

Nonlinear acoustoelectroluminescence. A.B.Sherman, A.A.Dobrovolsky and V.V.Lemanov 37

CROSSTALK

Barrage technique for measurement of p.c.m. regenerator section loss limits. A.J.Gibbs, G.Nicholson and P.G.Potter 814

CRYSTAL RESONATORS

Investigations on a new force-frequency measuring gauge. K.Grantcharov, M.Borissov, D.Detchev, L.Spassov and E.Yossifov 71
Narrow-band frequency discriminator using two monolithic crystal filters. S.J.Foster and M.Redwood 104

CRYSTALS

Elimination of emitter edge dislocations in silicon planar n-p-n transistors. N.D.Stojadinović and R.S.Popović 842
Intermodulation in X-cut lithium tantalate resonators. M.Planat, G.Theobald, J.J.Gagnepain and P.Siffert 174

CURRENT CONVEYORS

Novel circuit implementation of current conveyors using an o.a. and an o.t.a.. R.Senani 2

CYBERNETICS

Computation of multiweight. K.Maitree and S.Kondo 933
New reinforcement algorithm in learning automata. D.Maravall 623

DATA TRANSMISSION

Barrage technique for measurement of p.c.m. regenerator section loss limits. A.J.Gibbs, G.Nicholson and P.G.Potter 814
Comparison of three suboptimum detection procedures. V.M.Milutinović 681
Further results on relationship between system delay and transmission rate in time encoded speech-type systems. L.F.Turner, E.Frangoulis and A.Alcaim 947
New technique for channel synchronisation in time division multiplexing. K.Dagakis, C.Mantakas and G.Papadopoulos 944
Recursive code generation based on m-sequence. J.M.Potter 858
Single-ended fibre strain and length measurement in frequency domain. R.Kashyap and M.H.Reeve 689
Suboptimum detection procedure based on the weighting of partial decisions. V.M.Milutinović 237

DELAY LINES

Tunable magnetostatic surface wave demultiplexing filter/switch. H.Sasaki and N.Mikoshiba 700

DETECTOR CIRCUITS

Unbiased InP detectors in the submillimetre wave region. T.Takada, T.Makimura and T.Ishibashi 765

DIELECTRICS AND DIELECTRIC DEVICES

Dielectric constant of semi-insulating gallium arsenide. R.E.Neidert 244
Dielectric resonator dual modes filter. P.Guillon, Y.Garault and J.Farence 646
Effect of hydroscopic water on dielectric constant of dust at X-band. S.I.Ghobrial 393
Magnetostatic bulk wave propagation in a multilayered structure. S.N.Bajpai and N.C.Srivastava 269
Representation of imperfect dielectric materials by an equivalent circuit. A.V.Sopilnik and J.C.L.van Peppen 368

DIFFRACTION

Edge diffraction by right-angled dielectric wedge. C-S.Joo, J-W.Ra and S-Y.Shin 934
Measurement of s.a.w. device stripe/period ratio using optical diffraction. C.W.Chapman and G.W.Judd 952

DIFFUSION

Effectiveness of charged vacancies in diffusion of implanted boron in silicon. F.Runovc 49
I.C.-compatible completely planar GaAs m.e.s.f.e.t.s. by selective diffusion. N.Arnold, H.Daembkes and K.Heime 923
Low temperature diffusion process for fabricating optical waveguides in glass. C.W.Pitt, A.A.Stride and R.I.Trigle 701
Open ampoule diffusion in InP. P.N.Favennec, L.Henry, M.Gauneau, H.L'Haridon and G.Pelous 832

DIGITAL CIRCUITS

Bit synchronisation in Gbit/s range using dual gate GaAs m.e.s.f.e.t.s.. H.Beneking, W.Filensky and F.Ponse 543
Improved framing circuit and its performance evaluation. W.Chengyi 144
Multi/demultiplexing in Gbit/s range using dual gate GaAs m.e.s.f.e.t.s.. H.Beneking, W.Filensky and F.Ponse 551
New frequency division circuit using b.b.d.. M.Emura, Y.Fukui and S.Yoneda 530
Reconvergence phenomenon in synchronous sequential circuits. N.K.Nanda and R.G.Bennetts 303

DIGITAL COMMUNICATION SYSTEMS

Adaptive Kalman filter equaliser. E.Dalle Mese and G.Corsini 547
Implementation of mitre public key cryptographic system. J.E.Hershey 930
Improved framing circuit and its performance evaluation. W.Chengyi 144
Interpolatory quadrature rules and error rate of digital communication systems. A.Luvison 16
New charge transfer recursive filter. M.Feldmann and J.Henaff 585
Proposed quarter squares double dual-slope digital wattmeter. J.R.Stockton 819
S.A.W. implementation of whitening filters for satellite digital communications. J.Henaff and M.Feldmann 124

DIGITAL COMPUTERS

Fast binary logarith, computing circuit for binary numbers less than one. G.Frangakis 574
Improvements to binary floating-point digital differential analysers. G.Hannington 337
Technique for performing multiplication on a 16-bit microprocessor using an extension of Booth's algorithm. E.Ambikairajah and M.J.Carey 53

DIGITAL CONTROL

Filters using digital techniques to improve operation of a fast digital phasemeter. M.Durvaux 447
L.M.S. algorithm for sequentially adapting all-zero digital filters in modified cascade form. P.C.Ching and C.C.Goodyear 270
Maximally flat f.i.r. filter with prescribed cutoff frequency. P.Thajchayapong, M.Puangpool and S.Banjongjit 514

DIGITAL FILTERS

Complex residue number arithmetic for high-speed signal processing. W.K.Jenkins 660
Continuously variable digital filters based on linear interpolation of coefficients. R.A.Stein, N.R.Bartley and L.T.Bruton 670
Error-free coefficient realisation of recursive part via input-partitioned filter structure. C.L.Nikias 236
Explicit formula for filter function of maximally flat nonrecursive digital filters. M.U.A.Bromba and H.Ziegler 905
I.I.R. digital filter design using constrained optimisation techniques. T.S.Durrani and R.Chapman 843
Spectral shaping of digitised speech for mobile radio applications. P.M.Petrović 363
Technique for performing multiplication on a 16-bit microprocessor using an extension of Booth's algorithm. E.Ambikairajah and M.J.Carey 53

DIGITAL SIGNALLING

Efficient algorithm for determination of a.r. part of a.r.m.a. model. G.Carayannis, N.Kalouptsidis and D.Manolakis 656
Minimum-distortion functional for one-dimensional quantisation. H.V.Poor 23
Power spectrum of the balanced digital signal generated by Markov source. G.Petrović e240

DIGITAL TRANSMISSION

Alternative burst transmission technique for digital telephone reticulation. R.A.Court 583
Distribution of burst error lengths in Rayleigh fading radio channels. K.Otani and H.Omori 889
Evaluation of error probability for partial response systems. K.M.Sundara Murthy and K.W.Cattermole 886
Improved digital automatic gain control for p.c.m. signals. J.E.Flood and J.M.Fonseca 589
Intersymbol interference in misequalised coaxial systems. D.Munoz Rodriguez and K.W.Cattermole 891
New line code for digital subscriber loop. Ø.Jenssen, B.O.Justnes and S.Stueflotten 847

DIODES

Current/voltage characteristics of degenerated molybdenum and platinum Schottky diodes. J.Martinez, E.Calleja and J.Piqueras 183
Deep trapping centres in n-GaAs surface barrier diodes for nuclear radiation detection. S.J.Pearton, A.J.Tavendale and A.A.Williams 483
Duobinary transmission with p-i-n f.e.t. optical receivers. M.J.O'Mahony 752
High performance millimetre Ge-GaAs mixer diode for low l.o. power applications. A.Christou, W.T.Jr.Anderson, J.E.Davey, M.L.Bark and Y.Anand 254
Ideality and noise figure characteristics of r.f. sputtered millimetre GaAs diodes. Y.Anand, A.Christou and H.Day 581
Ka-band self-oscillating mixers with Schottky Baritt diodes. P.N.Förg and J.Freyer 827
Low leakage current and saturated reverse characteristic in broad-area InGaAsP diodes. F.Capasso, R.A.Logan, P.W.Foy, S.Sumski and D.D.Manchon 241
Low noise GaAs varactor and mixer diodes prepared by molecular beam epitaxy. J.J.Harris and J.M.Woodcock 317
Near-infra-red absorption using InGaAsP sources. H.Temkin and A.K.Chin 437
p-i-n f.e.t. hybrid optical receiver for 1.1-1.6 μm optical communication systems. D.R.Smith, A.K.Chatterjee, M.A.Z.Rejman, D.Wake and B.R.White 750
Planar n-GaAs/N-GaAlAs microwave diodes. A.Lechner, M.Kneidinger and R.Kuch 1
Temperature dependence of storage time in silicon p^+-n-n^+ switching diodes and reduction of harmonic distortion. A.Rosen, R.U.Martinelli and M.Caulton 66
Unbiased InP detectors in the submillimetre wave region. T.Takada, T.Makimura and T.Ishibashi 765

DIRECTIONAL COUPLERS

Interdigitated coplanar directional couplers. E.M.Bastida and N.Fanelli 645

DISCRETE SYSTEMS

Model reduction of discrete-time systems using the Schwarz canonical form. E.Badreddin and M.Mansour 782

DISPERSION (WAVE)

Effect of chromatic dispersion on pulses of arbitrary coherence. D.Gloge e240

DOPING

Activation of low dose silicon implants in GaAs by multiply scanned electron beams. N.J.Shah, H.Ahmed, I.R.Sanders and J.F.Singleton 433

Cutoff frequency of a graded channel f.e.t.. S.D.S.Malhi and C.A.T.Salama 261

Effect of p-doping on carrier lifetime and threshold current density of 1.3 μm GaInAsP/InP lasers by liquid-phase epitaxy. W.Ng and Y.Z.Liu 693

Extrinsic photoconductivity in platinum-doped silicon. W.P.Bickley, D.V.Eddolls and E.F.Maher 898

I.C.-compatible completely planar GaAs m.e.s.f.e.t.s. by selective diffusion. N.Arnold, H.Daembkes and K.Heime 923

Laser annealing of low dose Se-implanted GaAs studied by d.l.t.s.. N.G.Emerson and B.J.Sealy 512

Optimisation of p^+ doping level of n^+ -p-p^+ bifacial b.s.f. solar cells by ion implantation. J.Eguren, J.Del Alamo and A.Luque 633

Role of substrate in electrical properties of GaAs implanted layers. G.M.Martin, M.Berth and C.Venger 278

Short-channel polysilicon-gate m.o.s.f.e.t.s fabricated by c.w. argon laser annealing of arsenic-implanted source and drain. T.C.Teng, J.D.Merritt, J.Velez, J.Peng and L.Palkuti 477

ELECTROLUMINESCENCF

Bulk and junction effects in d.c. electroluminescent ZnS: Cu, Mn powder panels. C.J.Alder, A.Cattell, K.Dexter, M.Dixon and J.Kirton 571

ELECTROMAGNETIC FIELD THEORY

Edge diffraction by right-angled dielectric wedge. C-S.Joo, J-W.Ra and S-Y.Shin 934

ELECTROMAGNETIC WAVES

Approximate solution for propagation modes on lossy multiconductor transmission lines in inhomogeneous media. S.S.Bedair and M.I.Sobhy 914

Effect of edge region on crosspolar performance of dichroic plate. R.Cahill and E.A.Parker 710

Pattern synthesis of cylindrical slot antenna. J.M.Jarem and N.J.Sheikh 383

Reflection and radiation of flanged circular dielectric rod. C.Fray, N.Khayata and A.Papiernik 740

ELECTROMAGNETISM

Long-wavelength analysis of near-field irradiation of prolate spheroidal models of man and animals. H.Massoudi, C.H.Durney and M.F.Iskander 99

Microwave detection of third-order nonlinearities in fatigue cracks. A.J.Bahr 150

Parallel-wire meander line deflection circuit for electron beams. Y.Yamamoto, Y.Hagiwara, T.Iwai and K.Fujisawa 654 e863

ELECTRON MICROSCOPY

Depth profiling of integrated circuits with thermal wave electron microscopy. A.Rosencwaig 928

ELECTRON TUBES

Nonlinear interaction of s.a.w.s. in piezoelectric crystals with secondary electrons. A.A.Dobrovolsky, V.V.Lemanov, A.B.Sherman, Yu.M.Gal'Perin and V.I.Kozub 243

Parallel-wire meander line deflection circuit for electron beams. Y.Yamamoto, Y.Hagiwara, T.Iwai and K.Fujisawa 654 e863

EPITAXY AND EPITAXIAL GROWTH

1.5-1.7 μm v.p.e. InGaAsP/InP c.w. lasers. G.H.Olsen, T.J.Zamerowski and N.J.Digiuseppe 516

C.W. operation of $Al_xGa_{1-x}As/Al_yGa_{1-y}As$ lasers grown by metalorganic c.v.d. in wavelength range 760 - 780 nm. Y.Mori and N.Watanabe 284

Channelles substrate lasers prepared by combination of organometallic pyrolysis and liquid-phase epitaxy. J.P.Noad, C.M.Look and A.J.Springthorpe 685

$Ga_xIn_{1-x}As_yP_{1-y}/InP$ d.h. laser emitting at 1.15 μm grown by low-pressure metalorganic c.v.d.. J.P.Hirtz, J.P.Duchemin, P.Hirtz, B.de Cremoux, T.Pearsall and M.Bonnet 275

Growth conditions to achieve mobility enhancement in $Al_xGa_{1-x}As$-GaAs heterojunctions by m.b.e.. H.Morkoc, L.C.Witkowski, T.J.Drummond, C.M.Stanchak, A.Y.Cho and B.G.Streetman 753

Growth of $Ga_{0.47}In_{0.53}As$ on InP by low-pressure m.o. c.v.d.. J.P.Hirtz, J.P.Larivain, J.P.Duchemin, T.P.Pearsall and M.Bonnet 415

Influence of growth conditions on the threshold current density of double-heterostructure lasers prepared by molecular-beam epitaxy. A.Y.Cho, Jun Casey,H.C., C.Radice and P.W.Foy 72

InP epitaxy with a new metalorganic compound. H.Renz, J.Weidlein, K.W.Benz and M.H.Pilkuhn 228

Low noise GaAs varactor and mixer diodes prepared by molecular beam epitaxy. J.J.Harris and J.M.Woodcock 317

Low threshold current transverse junction lasers on semi-insulating substrates by m.b.e.. T.P.Lee, C.A.Burrus and A.Y.Cho 510

Method for reproducible l.p.e. growth of GaInAsP. M.Janson and A.Josefsson 879

New 1.6 μm wavelength GaInAsP/InP buried heterostructure lasers. S.Arai, M.Asada, Y.Suematsu, Y.Itaya, T.Tanbun-ek and K.Kishino 349

O.M. V.P.E. growth of AlGaSb and AlGaAsSb. C.B.Cooper, R.R.Saxena and M.J.Ludowise 892

Pulsed V-band m.b.e. Si Impatt diodes. J.Freyer, E.Kasper and H.Barth 865

Symmetric separate confinement heterostructure lasers with low threshold and narrow beam divergence by M.B.E.. W.T.Tsang 939

Use of trimethylantimony and trimethylarsenic for organometallic v.p.e. growth of $GaAs_{1-x}Sb_x$ and $Ga_{1-x}In_xAs$. C.B.Cooper, M.J.Ludowise, V.Aebi and R.L.Moon 20

EQUALISERS

Chebyshev time-domain deconvolution for transversal filter equalisers. D.Preis and C.Bunks 899

EQUIVALENT CIRCUITS

Equivalent circuit of multiplying d.a.c. using R-2R ladder network. J.Zurada and K.Goodman 925

ERRORS

7B8B balanced code with simple error detecting capability. R.Brooks 458

Class of block codes for the Gaussian channel. D.E.Lazić 185

Distribution of burst error lengths in Rayleigh fading radio channels. K.Otani and H.Omori 889

Error performance of frequency-hopped d.p.s.k. system. K.Yamada and K.Daikoku 305

Error rates of phase-modulated signals in multilink system with interference. I.M.Kostić 599 e718

Interpolatory quadrature rules and error rate of digital communication systems. A.Luvison 16

Penalties of hard decision in signal detection. T.C.Tozer and J.Kollerstrom 199

FAST FOURIER TRANSFORMS

,Numerical evaluation of logarithmic receiver thresholds. D.C.Schleher 875

FEEDBACK

Application of decision feedback equaliser in an environment with narrowband interfering signals. C.K.Pauw 787

Effect of dead time on closed-loop regulation. C.C.Hang 133

Modal noise and optical feedback in high-speed optical systems at 0.85 μm. C.Baack, G.Elze, B.Enning and G.Walf 592

Simultaneous feedback control of bias and modulation currents for injection lasers. F.S.Chen 7

Wavelength sensed mode control of semiconductor lasers. D.J.Malyon, D.W.Smith and R.W.Berry 744

FERRITE DEVICES

Reception of phase-locked l.f. and m.f. transmissions by receivers having ferrite-rod antennas. P.Knight 40

FERRITES

Compact directional V.H.F. antennas. H.M.Buettner 938

M.S.W. nondispersive, electronically tunable time delay elements. J.C.Sethares, J.M.Owens and C.V.Smith 825

Microstrip rectangular resonators on ferrimagnetic substrates. N.Das and S.K.Chowdhury 817

FIBRE OPTICS

In-line fibre-optic polariser. W.Eickhoff 762

FIELD-EFFECT DEVICES

Cutoff frequency of a graded channel f.e.t.. S.D.S.Malhi and C.A.T.Salama 261
High efficiency GaAs Schottky-barrier gate f.e.t. oscillator. J.F.Sautereau, J.Graffeuil, K.Tantrarongroj and P.Rossel 490
Relationship between power added efficiency and gate-drain avalanche in GaAs m.e.s.f.e.t.s.. S.H.Wemple, M.L.Steinberger and W.O.Schlosser 459

FIELD-EFFECT TRANSISTORS

2W, 8-12 GHz GaAs f.e.t. amplifier. H.Q.Tserng, H.M.Macksey and S.R.Nelson 680
Bipolar operation of power junction field effect transistors. B.Jayant Baliga 300
Capacitor-coupled logic using GaAs depletion-mode f.e.t.s.. P.J.T.Mellor and A.W.Livingstone 749
Effects of capacitance at crossover wirings in power GaAs m.e.s.f.e.t.s.. Y.Aono, A.Higashisaka and F.Hasegawa 417
I.C.-compatible completely planar GaAs m.e.s.f.e.t.s. by selective diffusion. N.Arnold, H.Daembkes and K.Heime 923
Integrated $In_{0.53}Ga_{0.47}As$ p-i-n f.e.t. photoreceiver. R.F.Leheny, R.E.Nahory, M.A.Pollack, A.A.Ballman, E.D.Beebe, J.C.DeWinter and R.J.Martin 353
Micrometre-gate m.e.s.f.e.t.s. on laser-annealed polysilicon. J.Bernard, J.Frey, K.F.Lee and J.F.Gibbons 297
Microwave power amplification with InP f.e.t.s.. M.Armand, J.Chevrier and N.T.Linh 906
Photo-f.e.t. method: high-resolution deep-level measurement technique using a m.e.s.f.e.t. structure. F.J.Tegude and K.Heime 22
Planar GaAs normally-off j.f.e.t. for high speed logic circuits. Y.Kato, M.Dohsen, J.Kasahara and N.Watanabe 821

FILTERING AND PREDICTION THEORY

Optimised data windows. K.M.M.Prabhu and H.Renganathan 38
Stability of linear predictive descriptions of curves used in handwriting. Y.K.Ha and I.H.Witten 909

FILTERS

A source of thermocouple error in radiofrequency electric fields. D.P.Chakraborty and I.A.Brezovich 853
All-pole filter with predistorted attenuation characteristic. D.Rabrenović and V.Jovanović 950
Arbitrary phase polynomials. L.F.Lind and S.A.Mohammed 78
C.C.D./C.M.O.S. transversal filter using switched-capacitor technique for signal detection. Y.Ito, T.Maekawa, T.Yamamoto and K.Tanikawa 724
Chebyshev time-domain deconvolution for transversal filter equalisers. D.Preis and C.Bunks 899
Data-transmission filters for duobinary systems. L.F.Lind and A.A.De Albuquerque 228
Design of bandstop filters by reactance transformation. J.B.Marino-Acebal, C.Nadeu-Camprubi and E.Masgrau-Gomez 105
Discrete cosine transform processor using a c.c.d. programmable transversal filter. N.Kapur, J.Mavor and M.A.Jack 139
Elliptic filter design using arithmetic-geometric mean. G.B.Parks and M.A.Soderstrand 568
Error-rate measurements for s.f.s.k. with band limitation. H.Singh and T.T.Tjhung 64
Estimation of a sinusoid in uncorrelated noise using adaptive line enhancer. V.U.Reddy 473
Filters using digital techniques to improve operation of a fast digital phasemeter. M.Durvaux 447
Filtre recursif nonlineaire. M.Monsion and D.Commanges 125 e240
Implementation of prime transform algorithm using c.c.d. programmable transversal filter. N.Kapur and S.C.Dutta Roy 809
Improved circuit elements for switched-capacitor ladder filters. M.S.Lee 131
Integrated bandpass filters. K.U.Ahmed 424 e525
Integrated nonuniform thin-film bandpass filter. K.U.Ahmed and H.R.Singh 277
L.M.S. algorithm for sequentially adapting all-zero digital filters in modified cascade form. P.C.Ching and C.C.Goodyear 270
Least-square inverse polynomials and a counterexample for Jury's conjecture (Comment). A.H.Kayran and R.King 795
Maximally flat f.i.r. filter with prescribed cutoff frequency. P.Thajchayapong, M.Puangpool and S.Banjongjit 514
Method for signal processing with transfer function coefficients dependent only on timing. Y.P.Tsividis 796
Method of designing filters with shaped passband response. H.Spriggs and C.Nightingale 267
Miniature microstrip bandpass filter with large stopbands. M.Sierra 340
New charge transfer recursive filter. M.Feldmann and J.Henaff 585
Novel phase lead inverting integrator and its application in two-integrator loop filters. A.M.Soliman 475
Novel stray-insensitive switched-capacitor integrator. D.C.Von Grünigen, U.W.Brugger and G.S.Moschytz 395
Phase correction in two-integrator loop filters using new variable-phase inverting amplifier. A.M.Soliman 186
Pole sensitivity of all-pole lowpass LC ladder networks. J.K.Fidler 856
Resonant s.a.w. filter using surface shear wave mode on $LiTaO_3$ substrate. M.Hikita, Y.Kinoshita, H.Kojima and T.Tabuchi 446
Topological analysis of switched-capacitor networks. A.Konczykowska and M.Bon 89
Transfer functions with equiripple passband and very low Q-factor for economical active filters (Comment). M.Biey and A.Premoli 74
Trapped-energy flexural mode filter. V.L.Strashilov, V.P.Hinkov and K.P.Bransalov 729
Tunable active-phase-compensated universal biquadratic filter. K.K.Tuladhar 44
Use of a programmable filter for inverse filtering. D.Behar, H.Olaisen, G.S.Kino, D.Corl and P.M.Grant 88

FLIP-FLOPS

Prediction of flip-flop behaviour in metastable state. G.Lacroix, Ph.Marchegay and N.Al Hossri 725

FOURIER TRANSFORMS

Implementation of prime transform algorithm using c.c.d. programmable transversal filter. N.Kapur and S.C.Dutta Roy 809
Optimised data windows. K.M.M.Prabhu and H.Renganathan 38

FREQUENCY CONVERTORS

Efficient large-frequency-shifted three-wave mixing in low dispersion wavelength region in single-mode optical fibre. K.Washio, K.Inoue and S.Kishida 658

FREQUENCY-DOMAIN ANALYSIS

Mixed time/frequency domain approach to model reduction (Comment). Y.Bistritz 189

FREQUENCY SHIFT KEYING

Error-rate measurements for s.f.s.k. with band limitation. H.Singh and T.T.Tjhung 64

GALLIUM ARSENIDE

Alloying behaviour of Au-Ge/Pt ohmic contacts to GaAs by pulsed electron beam and furnace heating. C.P.Lee, J.L.Tandon and P.J.Stocker 849
Capacitor-coupled logic using GaAs depletion-mode f.e.t.s.. P.J.T.Mellor and A.W.Livingstone 749
Design and evaluation of a planar GaAlAs-GaAs bipolar transistor. D.Ankri and A.Scavennec 41
Planar-doped barriers in GaAs by molecular beam epitaxy. R.J.Malik, T.R.Aucoin, R.L.Ross, K.Board, C.E.C.Wood and L.F.Eastman 836
Planar GaAs normally-off j.f.e.t. for high speed logic circuits. Y.Kato, M.Dohsen, J.Kasahara and N.Watanabe 821
R.F. sputtered Au-Mo contacts to n-GaAs. W.J.Devlin 92

GALLIUM COMPOUNDS

Nonradiative carrier loss and temperature sensitivity of threshold in 1.27 μm (GaIn) (AsP)/InP d.h. lasers. G.H.B.Thompson and G.D.Henshall 42
Use of trimethylantimony and trimethylarsenic for organometallic v.p.e. growth of $GaAs_{1-y}Sb_y$ and $Ga_{1-x}In_xAs$. C.B.Cooper, M.J.Ludowise, V.Aebi and R.L.Moon 20

GRAPHS AND GRAPH THEORY

Algorithms for computation of relative neighbourhood graph. R.B.Urquhart 556
Algorithms for computing relative neighbourhood graph (Comment). G.T.Toussaint 860
Imaginary Smith chart for evanescent-mode structures. D.E.De Jersey 93
Petri net approach to enumerate all simple paths in a graph. A.A.Khan and H.Singh 291
Single-row routeing and planarity. J.J.Narraway and K.-M.So 219
Topological analysis of switched-capacitor networks. A.Konczykowska and M.Bon 89

GUNN DEVICES

Development of pulsed self-oscillating mixer. M.G.Somekh, W.Richmond, J.Moroz and M.J.Lazarus 597
High efficiency 90 GHz InP Gunn oscillators. J.D.Crowley, J.J.Sowers, B.A.Janis and F.B.Fank 705
Simple method to determine the main Gunn domain parameters. M.E.Levinshtein and G.S.Simin 191
Transient thermal analysis of integral-heat-sink GaAs pulsed Gunn device. D.C.Smith and R.L.Tebbenham 334

IMAGE INTENSIFIERS

Delining thermal imager pictures. J.F.Sherlock 774

IMAGE PROCESSING

Adaptive pel location coding for bilevel facsimile signals. M.G.B.Ismail and R.Steele 361
Delining thermal imager pictures. J.F.Sherlock 774
Δ-entropy and rate distortion bounds for generalised Gaussian information sources and their applications to image signals. W.Szepanski 109
Double-stimulas quality rating method for television digital codecs. T.A.White and J.W.Allnatt 714
Effective data collection aperture in long-wavelength imaging systems. J.C.Bennett and S.Abdul-Jauwad 696
Hierarchical and parallel processing structure of two-dimensional systems. K.V.M.Fernando and H.Nicholson 274
Image enhancement using fuzzy set. S.K.Pal and R.A.King 376
Improving the speed of convex hull calculations. B.K.Marlow and B.G.Batchelor 319
Microwave images with reduced background effects from digitally processed in-line holograms. K.H.S.Marie, A.P.Anderson and J.C.Bennett 493
New processing technique for digital facsimile transmission. M.G.B.Ismail and R.J.Clarke 355
Subjective assessment method for television digital codecs. J.W.Allnatt 450
Transform-domain spectrum extrapolator for efficient picture transmission. N.Kumar, N.B.Chakraborti and A.K.Mukherjee 198

IMPATTS

Free space video detection of harmonic content of 100 GHz impatt oscillator. J.R.Birch 799
Pulsed V-band m.b.e. Si Impatt diodes. J.Freyer, E.Kasper and H.Barth 865

INDIUM COMPOUNDS

Nonradiative carrier loss and temperature sensitivity of threshold in 1.27 μm (GaIn) (AsP)/InP d.h. lasers. G.H.B.Thompson and G.D.Henshall 42
Use of trimethylantimony and trimethylarsenic for organometallic v.p.e. growth of $GaAs_{1-y}Sb_y$ and $Ga_{1-x}In_xAs$. C.B.Cooper, M.J.Ludowise, V.Aebi and R.L.Moon 20

INDUCTANCE SIMULATION

Lossless inductor simulation: novel configurations using d.v.c.c.s.. R.Nandi 666
Novel insensitive lossless inductor simulation through inverse function generation (Comment). V.K.Singh 901

INFORMATION THEORY

Soft-decision decoding with unknown source distribution. M.Wolfenson and V.C.Jun.Da Rocha 949

INSTRUMENTATION

Improved microprocessor-controlled pedestrian data-acquisition system. S.S.Mudaly 3

INSULATING MATERIALS AND INSULATORS

Electrical conduction in metal/implanted SiO_2/Si structures. H.F.Ragaie 565
Space charge limited current in an insulator at high fields. Y.K.Sharma 896

INTEGRATED CIRCUITS

Circuit implementation of current conveyor. J.L.Huertas 225
Current mirror saturation sensing technique. B.L.Hart 927
Depth profiling of integrated circuits with thermal wave electron microscopy. A.Rosencwaig 928
Integrated bandpass filters. K.U.Ahmed 424 e525
Integrated nonuniform thin-film bandpass filter. K.U.Ahmed and H.R.Singh 277
Novel submicroamper current-source design technique for monolithic circuits. R.W.J.Barker and B.L.Hart 609
Physical dependence of output conductance of voltage driven b.j.t.s. M-G.Yi 861
Thick-film fabrication techniques for millimetre-wave dielectric waveguide integrated circuits. M.R.Inggs and N.Williams 245
Topological analysis of switched-capacitor networks. A.Konczykowska and M.Bon 89

INTEGRATED OPTICS

4-bits digitally driven integrated amplitude modulator for data processing. M.Papuchon, C.Puech and A.Schnapper 142
AlGaAs heterostructure injection laser s.c.r.. J.Katz, N.Bar-Chaim, S.Margalit and A.Yariv 840
AlGaAs transverse junction stripe laser with distributed Bragg reflector. H.Kawanishi, M.Hafich, B.Lenz and P.Petersen 738
GaAs-GaAlAs phototransistor/laser light amplifier. H.Beneking, N.Grote, W.Roth and M.N.Svilans 602
Gain and saturation power of resonant AlGaAs laser amplifier. S.Kobayashi and T.Kimura 230
High sensitivity InP/InGaAs heterojunction phototransistor. J.C.Campbell, A.G.Dentai, C.A.Burrus and J.F.Ferguson 713
Integrated optic a.d. convertor based on bulk acousto-optic interaction. M.Gottlieb and G.B.Brandt 359
Optical demultiplexer using concave grating in 0.7-0.9 μm wavelength region. R.Watanabe, K.Nosu, T.Harada and T.Kita 106
Optical grating multiplexer in the 1.1-1.5 μm wavelength region. R.Watanabe, K.Nosu and Y.Fujii 108
Optical memory readout by superluminescent diode with integrated photodetector. M.-C.Amann, A.Kuschmider and J.Boeck 58
p-i-n f.e.t. hybrid optical receiver for 1.1-1.6 μm optical communication systems. D.R.Smith, A.K.Chatterjee, M.A.Z.Rejman, D.Wake and B.R.White 750
Very low noise photodetector system using p-i-n diode and baseband parametric upconvertor. D.J.Roulston 595

INTERFERENCE

Evaluation of error probability for partial response systems. K.M.Sundara Murthy and K.W.Cattermole 886
Intersymbol interference in misequalised coaxial systems. D.Munoz Rodriguez and K.W.Cattermole 891

INTERFEROMETERS

Holographic measurement of refractive-index profile of optical fibre preform. P.L.Chu and D.Peri 876

ION IMPLANTATION

Effectiveness of charged vacancies in diffusion of implanted boron in silicon. F.Runovc 49
Ion implanted GaAs bipolar transistors. H.T.Yuan, F.H.Doerbeck and W.V.McLevige 637
Optimisation of p^+ doping level of n^+ -p-p^+ bifacial b.s.f. solar cells by ion implantation. J.Eguren, J.Del Alamo and A.Luque 633

IONISATION

Impact ionisation in multilayered heterojunction structures. R.Chin, N.Jun.Holonyak, G.E.Stillman, J.Y.Tang and K.Hess 467
Low temperature diffusion process for fabricating optical waveguides in glass. C.W.Pitt, A.A.Stride and R.I.Trigle 701

JOSEPHSON JUNCTIONS

Ion beam oxidation of Nb-based Josephson junctions. R.Herwig 850

LASER ANNEALING

Photoacoustic effect in laser annealing. K.Hoh 931

LASERS AND LASER APPLICATIONS

1.5-1.6 μm GaInAsP/InP integrated twin-guide lasers with first-order distributed Bragg reflectors. K.Utaka, K.Kobayashi, K.Kishino and Y.Suematsu 455

1.5-1.7 μm v.p.e. InGaAsP/InP c.w. lasers. G.H.Olsen, T.J.Zamerowski and N.J.Digiuseppe 516
2.0 μm c.w. operation of GaInAsSb/GaSb d.h. lasers at 80 K. H.Kano and K.Sugiyama 146
800 MHz s.a.w. timing filter for optical fibre transmission system. J.Minowa, K.Nakagawa, K.Okuno, Y.Kobayashi and M.Morimoto 35
8 Gbit/s optical transmission with t.j.s. GaAlAs laser and p-i-n detection. R.Tell and S.T.Eng 497
Active Q-switching of lateral field coupling control d.h. laser. H.Ito, K.Gen-ei and H.Inaba 846
AlGaAs heterostructure injection laser s.c.r.. J.Katz, N.Bar-Chaim, S.Margalit and A.Yariv 840
AlGaAs transverse junction stripe laser with distributed Bragg reflector. H.Kawanishi, M.Hafich, B.Lenz and P.Petersen 738
Bandwidth limited picosecond optical pulse generation from actively mode-locked AlGaAs diode laser. H.Ito, H.Yokoyama and H.Inaba 620
Bandwidth of distorted multimode waveguides excited by laser sources. J.Arnaud and M.Rousseau-Leberre 34
C.W. operation of $Al_xGa_{1-x}As/Al_yGa_{1-y}As$ lasers grown by metalorganic c.v.d. in wavelength range 760 - 780 nm. Y.Mori and N.Watanabe 284
C.W. operation of GaInAsP/InP laser with chemically etched mirror. K.Iga and B.I.Miller 830
Channelled substrate buried heterostructure InGaAsP/InP laser emitting at 1.55 μm. S.Takahashi, H.Saito and G.Iwane 922
Channelled substrate narrow stripe GaAs/(GaAl)As lasers with quarter-wavelength facet coatings. R.G.Plumb and J.P.Curtis 706
Channelled substrate lasers prepared by combination of organometallic pyrolysis and liquid-phase epitaxy. J.P.Noad, C.M.Look and A.J.Springthorpe 685
Coherence of injection phase-locked AlGaAs semiconductor laser. S.Kobayashi and T.Kimura 668
Diode laser sensor. A.Dandridge, R.O.Miles and T.G.Giallorenzi 948
Effect of laser noise on analogue fibre optic systems. H.B.Kim, R.Maciejko and J.Conradi 919
Effect of p-doping on carrier lifetime and threshold current density of 1.3 μm GaInAsP/InP lasers by liquid-phase epitaxy. W.Ng and Y.Z.Liu 693
Effects of fibre propagation loss on diode-laser-fibre coupling. M.L.Dakss and B.Kim 421
Efficient large-frequency-shifted three-wave mixing in low dispersion wavelength region in single-mode optical fibre. K.Washio, K.Inoue and S.Kishida 658
Frequency stabilisation of semiconductor lasers for heterodyne-type optical communication systems. T.Okoshi and K.Kikuchi 179
GaAs-GaAlAs phototransistor/laser light amplifier. H.Beneking, N.Grote, W.Roth and M.N.Svilans 602
Gain and saturation power of resonant AlGaAs laser amplifier. S.Kobayashi and T.Kimura 230
GaInAsP/InP laser with monolithically integrated monitoring detector. K.Iga and B.I.Miller 342
$Ga_xIn_{1-x}As_yP_{1-y}/InP$ d.h. laser emitting at 1.15 μm grown by low-pressure metalorganic c.v.d.. J.P.Hirtz, J.P.Duchemin, P.Hirtz, B.de Cremoux, T.Pearsall and M.Bonnet 275
Generation of surface acoustic waves by means of a c.w. laser. E.A.Ash, E.Dieulesant and H.Rakouth 470
High bit rate modulation of narrow-stripe proton-implanted GaAs/GaAlAs injection lasers. C.Lindström, P.Tihanyi, T.Andersson and P.Torphammar 575
High frequency stability of laser diode for heterodyne communication systems. F.Favre and D.Le Guen 709
High index microlenses for GaAlAs laser-fibre coupling. L.d'Auria, Y.Combemale, C.Moronvalle and A.Jacques 322
Influence of growth conditions on the threshold current density of double-heterostructure lasers prepared by molecular-beam epitaxy. A.Y.Cho, Jun Casey,H.C., C.Radice and P.W.Foy 72
InGaAsP/InP buried crescent laser emitting at 1.3 μm with very low threshold current. T.Murotani, E.Oomura, H.Higuchi, H.Namizaki and W.Susaki 566
Kink-free narrow-stripe proton-isolated GaAlAs/GaAs injection lasers. C.Lindström and P.Tihanyi 121
Low threshold current transverse junction lasers on semi-insulating substrates by m.b.e.. T.P.Lee, C.A.Burrus and A.Y.Cho 510
Low-threshold high-T_0 constricted double heterojunction AlGaAs diode lasers. D.Botez and J.C.Connolly 942
Measurement of refractive-index variation with free carrier density and temperature for 1.6 μm GaInAsP/InP lasers. K.Stubkjaer, Y.Suematsu, M.Asada, S.Arai and A.R.Adams 895
Microlens tipped on a single-mode fibre end for InGaAsP laser coupling improvement. Y.Murakami, J-I.Yamada, J-I.Sakai and T.Kimura 321
Model for return-beam-induced noise generation in GaAlAs semiconductor lasers. Y.Hirose and Y.Ogura 202
New 1.6 μm wavelength GaInAsP/InP buried heterostructure lasers. S.Arai, M.Asada, Y.Suematsu, Y.Itaya, T.Tanbun-ek and K.Kishino 349
Nonradiative carrier loss and temperature sensitivity of threshold in 1.27 μm (GaIn) (AsP)/InP d.h. lasers. G.H.B.Thompson and G.D.Henshall 42
Novel method for high resolution measurement of laser output spectrum. T.Okoshi, K.Kikuchi and A.Nakayama 630
Novel method for transmitting images through monomode fibres. J.Piasecki and A.Barthelemy 420
Ohmic contacts on n-GaAs produced by laser alloying of Ge films. G.Badertscher, R.P.Salathe and W.Luthy 113
Optical heterodyne detection of directly frequency modulated semiconductor laser signals. S.Saito, Y.Yamamoto and T.Kimura 826
Optical memory readout by superluminescent diode with integrated photodetector. M.-C.Amann, A.Kuschmider and J.Boeck 58
Optical receiver sensitivity improvement by a semiconductor laser preamplifier. Y.Yamamoto and H.Tsuchiya 233
Optoelectronic regenerative pulser. T.C.Damen and M.A.Duguay 166
Picosecond pulse generation in semiconductor lasers using resonance oscillation. P.Torphammar and S.T.Eng 587
Role of water in gradual degradation of (Al, Ga)As d.h. lasers. J.A.F.Peck 441
Semiconductor laser output modulated in GHz frequency region observed by image tube streak camera. M.Izutsu, H.Haga and T.Sueta 531
Simple picosecond pulse generation scheme for injection lasers. C.Lin, P.L.Liu, T.C.Damen, D.J.Eilenberger and R.L.Hartman 600
Single-mode c.w. ridge-waveguide laser emitting at 1.55 μm. I.P.Kaminow, R.E.Nahory, M.A.Pollack, L.W.Stulz and J.C.DeWinter e75
Single-mode operation of 500 Mbit/s modulated AlGaAs semiconductor laser by injection locking. S.Kobayashi, J.Yamada, S.Machida and T.Kimura 746
Single-mode oscillation under high-speed direct modulation in GaInAsP/InP integrated twin-guide lasers with distributed Bragg reflectors. Y.Sakakibara, K.Furuya, K.Utaka and Y.Suematsu 456
Symmetric separate confinement heterostructure lasers with low threshold and narrow beam divergence by M.B.E.. W.T.Tsang 939
Temperature dependence of threshold and electrical characteristics of InGaAsP-InP d.h. lasers. N.K.Dutta, R.J.Nelson and P.A.Barnes 653
Temperature stable heat sink metallisation for improved bonding of c.w. stripe lasers. C.Lindström and P.Tihanyi 811
V-dh laser: a laser with a V-shaped active region grown by metalorganic c.v.d.. Y.Mori, O.Matsuda, K.Morizane and N.Watanabe 785
Wavelength sensed mode control of semiconductor lasers. D.J.Malyon, D.W.Smith and R.W.Berry 744

LENSES

Coupling efficiency calculations on an integrated l.e.d./sphere-lens source for optical fibres. R.A.Abram and R.C.Goodfellow 14

LIGHT-EMITTING DIODES

Coupling efficiency calculations on an integrated l.e.d./sphere-lens source for optical fibres. R.A.Abram and R.C.Goodfellow 14
Dual wavelength surface emitting InGaAsP l.e.d.s.. T.P.Lee, C.A.Burrus and A.G.Dentai 845

LINEAR NETWORKS

Novel strays-insensitive switched-capacitor integrator realising the bilinear Z-transform. A.Knob 173

LINEAR SYSTEMS

Comparison of two iterative estimation procedures. P.Stoica 754
Hierarchical and parallel processing structure of two-dimensional systems. K.V.M.Fernando and H.Nicholson 274
Mixed complete Padé model reduction: a useful formulation for closed loop design. Y.Bistritz 563
Reduction of multivariable systems. N.K.Sinha 788
Transmission zeros of linear multivariable systems with parasitics. B.Porter 679

LITHOGRAPHY

High voltage electron lithography. T.R.Neill and C.J.Bull 621

LOGIC AND LOGIC DESIGN

5 GHz binary frequency division on GaAs. M.Cathelin, G.Durand, M.Gavant and M.Rocchi 535
Bit synchronisation in Gbit/s range using dual gate GaAs m.e.s.f.e.t.s.. H.Beneking, W.Filensky and F.Ponse 543
C.M.O.S. circuit for implementation of unary operators in ternary logic. A.Lloris, A.Prieto and J.Velasco 161
Calculation method to obtain worst-case static noise margins of logic circuits. J.Lohstroh 273

Capacitor-coupled logic using GaAs depletion-mode f.e.t.s.. P.J.T.Mellor and A.W.Livingstone 749
Clock-steering synthesis using spectral techniques. P.D.Picton 409
Deriving stability criteria for nonlinear circuits with application to worst-case noise margin of I^2L. E.Seevinck 867
Hardware-efficient bit sequential adders and multipliers using mode-controlled logic. D.C.Daws and E.V.Jones 434
Image enhancement using fuzzy set. S.K.Pal and R.A.King 376
Improved framing circuit and its performance evaluation. W.Chengyi 144
Multiplexer logic circuit design using cubical complexes. A.B.Ektare and D.P.Mital 495 e718
Negative failsafe sequential circuits. N.Gaitanis and C.Halatsis 615
Planar GaAs normally-off j.f.e.t. for high speed logic circuits. Y.Kato, M.Dohsen, J.Kasahara and N.Watanabe 821
Probabilistic approach to multiplexer logic circuit design. A.B.Ektare and D.P.Mital 686
Reconvergence phenomenon in synchronous sequential circuits. N.K.Nanda and R.G.Bennetts 303

LOGIC CIRCUITS

Continuously variable solid state delay circuits. G.M.Ettinger and L.T.Shooter 857
Prediction of flip-flop behaviour in metastable state. G.Lacroix, Ph.Marchegay and N.Al Hossri 725

LOGIC DEVICES

Easily testable sequential machines with extra inputs and extra outputs. S.R.Das, Z.Chen and Y.L.Dai 119

LOSSES

Graphical method for conduction loss calculation of TEM transmission lines. J.Majer 638

MAGNETISM

Frequency/depth-penetration considerations in hyperthermia by magnetically induced currents. J.H.Young, M.-T.Wang and I.A.Brezovich 358
Frequency/depth-penetration considerations in hyperthermia by magnetically induced currents (Comment). J.C.Lin 790
Magnetic noise controlled by electric current through core. R.N.G.Dalpadado and K.Shirae 103
Optical fibre magnetic field sensors. A.Dandridge, A.B.Tveten, G.H.Jr.Sigel, E.J.West and T.G.Giallorenzi 408
Stress dependences of longitudinal wave velocity in magnetostrictive metallic-glass ribbon. K-Y.Hashimoto, M.Yoshida, M.Yamaguchi and H.Kogo 425
Terminations for magnetostatic waves. W.Faber 452

MAGNETOSTATIC WAVES

M.S.W. nondispersive, electronically tunable time delay elements. J.C.Sethares, J.M.Owens and C.V.Smith 825
Propagation of magnetostatic surface waves in multiple magnetic layer structures. L.R.Adkins and H.L.Glass 590
Tunable magnetostatic surface wave demultiplexing filter/switch. H.Sasaki and N.Mikoshiba 700

MATHEMATICAL TECHNIQUES

Connection between primitive generators of $GF(2^n)$. B.Arazi 223
High-gain decentralised control of interconnected dynamical systems. A.Bradshaw 216
Least-square inverse polynomials and a counterexample for Jury's conjecture (Comment). A.H.Kayran and R.King 795
Numerical analysis of radial thin-wire antenna in presence of conducting sphere. B.D.Milovanović 611
Sufficient conditions for global homeomorphism of piecewise linear functions. V.C.Prasad and P.B.L.Gaur 335

MATRIX ALGEBRA

An improvement for the t.l.m. method. P.Saguet and E.Pic 247
Necessary conditions for absolute stability of nonlinear multivariable regulators. B.Porter 392

MEASUREMENT

A source of thermocouple error in radiofrequency electric fields. D.P.Chakraborty and I.A.Brezovich 853
Determination of modal amplitudes by resolution of radiation patterns. N.Sridhar, T.K.Sen and G.P.Srivastava 12
Differential measurement technique for evaluating microstrip line attenuation. L.Accatino and A.Angelucci 427 e791
Faraday effect in single-mode optical fibre using an injection laser light source. A.M.Smith 206
Fibre optic accelerometer. A.B.Tveten, A.Dandridge, C.M.Davis and T.G.Giallorenzi 854
Field probe for measuring both amplitude and phase of antenna radiation patterns. D.E.N.Davies and S.M.Vakil 873
Holographic measurement of refractive-index profile of optical fibre preform. P.L.Chu and D.Peri 876
Investigations on a new force-frequency measuring gauge. K.Grantcharov, M.Borissov, D.Detchev, L.Spassov and E.Yossifov 71
Measurement of extinction cross-section of single particles at 100 GHz. D.J.Harris and T.M.Teo 500
Microwave detection of third-order nonlinearities in fatigue cracks. A.J.Bahr 150
New a.d. convertor with special application to medium precision platinum resistance thermometry. C.P.Pickup 578
Open-circuited coaxial lines as standards for microwave measurements. B.Bianco, A.Corana, L.Gogioso, S.Ridella and M.Parodi 373
OPSEF: An optical sensor for measurement of high electric field intensity. Y.Hamasaki, H.Gotoh, M.Katoh and S.Takeuchi 406
Polarisation optical time domain reflectometry. A.J.Rogers 489
Precision time-domain measurement system. F.Caspers 29
Simple optical wavelength meter in 700-1200 nm wavelength region. K.Sano, K.Okada and K.Hashimoto 912
Single-fault location in a linear analogue system with variable sensitivity matrix. K.Y.Tong 221
Thick-film strain gauges and pressure transducers. Z.H.Meiksin and W.D.Humbel 242

METAL-INSULATOR-SEMICONDUCTOR STRUCTURES AND DEVICES

C/V measurements on m.i.s. structures on n-InSb formed by room temperature reactive deposition of Si_3N_4. F.Olcaytug, K.Riedling and W.Fallmann 677
Measurement arrangement for direct capacitance/surface-potential recording on m.o.s. capacitor. H.C.G.Ligtenberg and J.Snijder e45
n-channel m.i.s.f.e.t.s. in epitaxial HgCdTe/CdTe. G.M.Williams and E.R.Gertner 839
R.F. sputtered Au-Mo contacts to n-GaAs. W.J.Devlin 92
Simple method for evaluating electronic properties at silicon-sapphire interface. P.Gentil 617
Surface passivation of inversion layer m.i.s. solar cells. Y.W.Lam, M.A.Green and L.W.Davies 707
Switching in m.i.s.m. and m.i.s.i.m. structures. M.Darwish and K.Board 577

METAL-OXIDE-SEMICONDUCTOR STRUCTURES AND DEVICES

Continuously variable solid state delay circuits. G.M.Ettinger and L.T.Shooter 857
Controlling deep transient depletion of an m.o.s. capacitor. T.P.Pedron, J.P.Lanteri, M.Garrigues and J.J.Urgell 367
Electrical conduction in metal/implanted SiO_2/Si structures. H.F.Ragaie 565
Electron dynamics in P-Si m.o.s.f.e.t. inversion channels. J.Zimmermann, R.Fauquembergue, M.Charef and E.Constant 664
High-gain c.m.o.s. cascode operational amplifier. F.Krummenacher and J.-L.Zufferey 232
New n-channel m.o.s.f.e.t.s.. T.Wakimoto and M.Matsumura 402
Novel bottom-plate stray-insensitive voltage inverter switch. D.Herbst and B.J.Hosticka 636

MICROPROCESSORS AND MICROPROCESSOR APPLICATIONS

Estimating the pitch period of voiced speech. E.Ambikairajah, M.J.Carey and G.Tattersall 464
Improved microprocessor-controlled pedestrian data-acquisition system. S.S.Mudaly 3
Improvements to binary floating-point digital differential analysers. G.Hannington 337
Improving the speed of convex hull calculations. B.K.Marlow and B.G.Batchelor 319
Technique for performing multiplication on a 16-bit microprocessor using an extension of Booth's algorithm. E.Ambikairajah and M.J.Carey 53

MICROSCOPES AND MICROSCOPY

Dark field acoustic microscopy. D.A.Sinclair and I.R.Smith 627
Detection of plastic deformation in metals with photoacoustic microscope. M.Luukkala and S.G.Askerov 84
Planar acoustic microscope lens using Rayleigh to compressional conversion. G.W.Farnell and C.K.Jen 541
Single lens transmission scanning acoustic microscope. A.I.Morozov and M.A.Kulakov 596

MICROSTRIP

Approximate formulas for frequency dependence of microstrip parameters. H.F.Pues and A.R.van de Capelle 870
Compact microstrip bandpass filter using both λ/2 and λ/4 resonators. M.A.Flemming 915
Crosspolarisation characteristics of linear comb-line microstrip antennas. A.K.Brown 743
E-plane coupling between two rectangular microstrip antennas. C.M.Krowne 635
High-gain flat-plate phase-monopulse antenna. R.J.Dewey 30
Microstrip rectangular resonators on ferrimagnetic substrates. N.Das and S.K.Chowdhury 817
New microstrip slot radiator for medical applications. I.J.Bahl, S.S.Stuchly and M.A.Stuchly 731
New wideband microstrip antenna using log-periodic technique. P.S.Hall 127
Slotline-microstrip transition on iso/anisotropic substrate: a more accurate design. A.Podcameni and M.L.Coimbra 780

MICROWAVE AMPLIFIERS

Treatment of noise-figure calculations in microwave transistor amplifiers. G.P.Young and J.O.Scanlan 17

MICROWAVE ANTENNAS

High-gain flat-plate phase-monopulse antenna. R.J.Dewey 30

MICROWAVE CIRCUITS AND SYSTEMS

2W, 8-12 GHz GaAs f.e.t. amplifier. H.Q.Tserng, H.M.Macksey and S.R.Nelson 680
Adaptive crosstalk cancellation for crosspolarised digital transmissions. P.Sobieski and P.Delogne 385
Applications of scattering matrix for development of microwave mixers. W.Hauth 501
Broadband varactor-tuned GaAs f.e.t. oscillator. C.Rauscher 534
Cryogenic 2-4 GHz f.e.t. amplifier. B.Vowinkel 730
Dual gate GaAs m.e.s.f.e.t. phase shifter with gain at 12 GHz. C.Tsironis and P.Harrop 553
GaAs varactors for linear tuning characteristics. A.Colquhoun, E.Kohn and W.J.Rabe 736
High efficiency GaAs Schottky-barrier gate f.e.t. oscillator. J.F.Sautereau, J.Graffeuil, K.Tantrarongroj and P.Rossel 490
Increasing power input to a single solar power satellite rectenna by using a pair of satellites. R.V.Gelsthorpe and P.Q.Collins 311
Interdigitated coplanar directional couplers. E.M.Bastida and N.Fanelli 645
Microwave images with reduced background effects from digitally processed in-line holograms. K.H.S.Marie, A.P.Anderson and J.C.Bennett 493
Miniature microstrip bandpass filter with large stopbands. M.Sierra 340
New commutated Doppler microwave landing system. F.R.Connor 365
New direction-of-motion Doppler detector. M.J.Lazarus, F.R.Pantoja, M.Somekh, S.Novak and S.Margison 953
Numerical technique for determining pumped nonlinear device waveforms. R.G.Hicks and P.J.Khan 375
Parametric interactions when resonator reactances are varied in antiphase. B.Z.Kaplan 343
Switched-capacitor realisation of C- and D-sections. M.K.Li 603

MICROWAVE DEVICES AND COMPONENTS

10 GHz/10 W internally matched flip-chip GaAs power f.e.t.s.. Y.Mitsui, M.Kobiki, M.Wataze, K.Segawa, M.Otsubo and T.Ishi 205
Applications of dual-gate GaAs m.e.s.f.e.t.s. for fast pulse shape regeneration systems. W.Filensky, F.Ponse and H.Beneking 214
Combined triple-transit and bulk-wave suppression in s.a.w. delay line. D.J.Gunton 149 e240
GaAs gigabit logic circuits using normally-off m.e.s.f.e.t.s.. T.Mizutani, N.Kato, S.Ishida, K.Osafune and M.Ohmori 315
High performance millimetre Ge-GaAs mixer diode for low l.o. power applications. A.Christou, W.T.Jr.Anderson, J.E.Davey, M.L.Bark and Y.Anand 254
High transformation ratio for impedance matching with a radial line. K.-H.Doring and E.Seebald 50
Ka-band self-oscillating mixers with Schottky Baritt diodes. P.N.Förg and J.Freyer 827
Microwave detection of third-order nonlinearities in fatigue cracks. A.J.Bahr 150
Microwave power amplification with InP f.e.t.s.. M.Armand, J.Chevrier and N.T.Linh 906
New analytical model for rectangular image guide. Ph.Gelin, S.Toutain and J.F.Legier 442
Planar n-GaAs/N-GaAlAs microwave diodes. A.Lechner, M.Kneidinger and R.Kuch 1
Pulsed V-band m.b.e. Si Impatt diodes. J.Freyer, E.Kasper and H.Barth 865
Transient thermal analysis of integral-heat-sink GaAs pulsed Gunn device. D.C.Smith and R.L.Tebbenham 334

MICROWAVE FILTERS

Compact microstrip bandpass filter using both λ/2 and λ/4 resonators. M.A.Flemming 915

MICROWAVE LINKS

Earth-space rain-cell modelling through SIRIO propagation data. E.Matricciani 81

MIXERS

Development of pulsed self-oscillating mixer. M.G.Somekh, W.Richmond, J.Moroz and M.J.Lazarus 597
New direction-of-motion Doppler detector. M.J.Lazarus, F.R.Pantoja, M.Somekh, S.Novak and S.Margison 953

MOBILE RADIO SYSTEMS

Distribution of burst error lengths in Rayleigh fading radio channels. K.Otani and H.Omori 889
Median signal strength prediction for mobile radio propagation in London. J.D.Parsons, M.F.Ibrahim and R.J.Samuel 172

MODEL ANALYSIS

Long-wavelength analysis of near-field irradiation of prolate spheroidal models of man and animals. H.Massoudi, C.H.Durney and M.F.Iskander 99

MODELLING

Mixed complete Padé model reduction: a useful formulation for closed loop design. Y.Bistritz 563
Mixed time/frequency domain approach to model reduction (Comment). Y.Bistritz 189
Mixed time/frequency domain approach to model reduction (Comment). J.Hickin 338
Model reduction of discrete-time systems using the Schwarz canonical form. E.Badreddin and M.Mansour 782
Representation of imperfect dielectric materials by an equivalent circuit. A.V.Sopilnik and J.C.L.van Peppen 368
Stable reduced-order Padé approximants using stability-equation method. T.C.Chen, C.Y.Chang and K.W.Han 345
Stable reduced order Padé approximants using stability equation method (Comment). V.Singh 820

MODULATION

8 Gbit/s optical transmission with t.j.s. GaAlAs laser and p-i-n detection. R.Tell and S.T.Eng 497
Block adaptive prediction of colour television signals. H.Gharavi 226
C.P.S.K. receiver performances in presence of carrier-frequency offset. M.Č.Stefanović 182
Conrad's rule for phase-modulation spectra. J.M.Noras 5
Deduction of amplifier phase transfer characteristic from measured a.m./p.m. conversion-coefficient characteristic. M.T.Abuelma'atti and J.G.Gardiner 298
High bit rate modulation of narrow-stripe proton-implanted GaAs/GaAlAs injection lasers. C.Lindström, P.Tihanyi, T.Andersson and P.Torphammar 575
Intermode phase scanning for recovering phase-modulated signals on multimode optical fibres. P.R.Ball and B.Culshaw 259
Mean square error of s.s.b.a.m. class 4 partial response data signals due to slope, sag and ripple group delay components. L.J.Millott and B.M.Smith 492
New digital automatic gain control for p.c.m. signals. J.E.Flood and J.M.Fonseca 96
Novel p.s.k. tanlock loop. A.H.Makarious and P.G.Farrell 957
Novel supervisory channel for fibre optic transmission systems. P.Cochrane and J.A.Kitchen 624
Power spectra of d.p.s.k. signals for data transmission. D.Drajić and G.Petrović 251
Single-mode operation of 500 Mbit/s modulated AlGaAs semiconductor laser by injection locking. S.Kobayashi, J.Yamada, S.Machida and T.Kimura 746
Television demodulator receiving signals by satellite. J.M.Adant and P.Delogne 401

MONTE CARLO METHODS

Statistical approach to reduction of circuit performance variability. A.Ilumoka and R.Spence 761

MULTIPLEXING

E.I.R.P. allocation for a nonlinear satellite channel with multiple transmit beams and carriers. J.Arnbak e75
Interference filter all-fibre directional coupler for w.d.m.. H.F.Mahlein, H.Michel, W.Rauscher, A.Reichelt and G.Winzer 584
Multi/demultiplexing in Gbit/s range using dual gate GaAs m.e.s.f.e.t.s.. H.Beneking, W.Filensky and F.Ponse 551
New technique for channel synchronisation in time division multiplexing. K.Dagakis, C.Mantakas and G.Papadopoulos 944
Optimal phases of maximal length sequences for asynchronous spread-spectrum multiplexing. F.D.Garber and M.B.Pursley 756
Probabilistic approach to multiplexer logic circuit design. A.B.Ektare and D.P.Mital 686
Simple structure high isolation multi/demultiplexer. T.Tanaka, H.Serizawa and Y.Tsujimoto 869

MULTIVARIABLE SYSTEMS

Approximate aggregation for linear multivariable systems. J.Hickin 518
Reduction of multivariable systems. N.K.Sinha 788
Transmission zeros of linear multivariable systems with parasitics. B.Porter 679

NEGATIVE RESISTANCE

Modulating transistor: a new class of semiconductor device. G.I.Fursin 662
Semidistributed neuristor using plasma-coupled modulating transistors. V.A.Skorik and G.I.Fursin 676

NETWORKS

Bilinear switched-capacitor ladder filter with reduced number of amplifiers. G.C.Temes and M.B.Ghanderi 412
Bottom-plate stray-insensitive bilinear switched-capacitor integrators. D.C.von Gruningen, U.W.Brugger and B.J.Hosticka 25
Cascade synthesis of switched-capacitor networks employing voltage inverter switches. M.K.Li 370
Circuit implementation of current conveyor. J.L.Huertas 225
Easing prefiltering requirements of s.c. filters. K.Martin and A.S.Sedra 613
Inclusion of amplifier finite gain and bandwidth in analysis of switched-capacitor filters. J.Lau and J.I.Sewell 462
Increasing the clock frequency of switched-capacitor filters. T.R.Viswanathan and T.L.Viswanathan 316
Modified nodal approach to network sensitivity calculation for one-dimensional orthogonal search technique. J.T.Ogrodzki 641
New bilinear switched-capacitor immittance convertor circuit. T.Inoue and F.Ueno 285
New switched-capacitor immittance converter using operational amplifier leapfrog structure. T.Inoue and F.Ueno 266
Noise generated in switched capacitor networks. Cl.-A.Gobet and A.Knob 734
Novel active R supercapacitor simulation: applications in low sensitivity multifunction network realisation. A.R.Saha and R.Nandi 570
Novel f.d.n.c. simulation using current conveyors. K.Pal 639
Novel stray-insensitive switched-capacitor integrator. D.C.Von Grünigen, U.W.Brugger and G.S.Moschytz 395
Parasitics-insensitive switched-capacitor ladder filters. ManShek Lee 472
Petri net approach to enumerate all simple paths in a graph. A.A.Khan and H.Singh 291
Strays-insensitive active switched-capacitor biquad. E.I.El-Masry 480
Sufficient conditions for global homeomorphism of piecewise linear functions. V.C.Prasad and P.B.L.Gaur 335
Switched-capacitor biquads based on switched-capacitor transconductance. S.M.Faruque, J.Vlach and T.R.Viswanathan 63
Switched-capacitor immittance convertors using a single operational amplifier. T.Inoue and F.Ueno 770
Synthesis of active RC multiport voltage transfer functions with reduced number of operational amplifiers (Comment). B.B.Stamenković 333
Topological analysis of switched-capacitor networks. A.Konczykowska and M.Bon 89
Transfer function deviations due to resistor-s.c. equivalence assumption in switched-capacitor simulations of LC ladders. K.Martin and S.Sedra 387

NOISE

Analysis and measurement of modal noise in an optical fibre. B.Daino, G.De Marchis and S.Piazzolla e75
Bipolar transistors with low 1/f noise. M.Stoisiek, D.Wolf and W.Werner 372
Calculation method to obtain worst-case static noise margins of logic circuits. J.Lohstroh 273
Deriving stability criteria for nonlinear circuits with application to worst-case noise margin of I^2L. E.Seevinck 867
Effect of laser noise on analogue fibre optic systems. H.B.Kim, R.Maciejko and J.Conradi 919
Magnetic noise controlled by electric current through core. R.N.G.Dalpadado and K.Shirae 103
Maximisation of signal/noise ratio in array with broadened zero. P.C.K.Kwok and P.S.Brandon 60
Modal noise and optical feedback in high-speed optical systems at 0.85 μm. C.Baack, G.Elze, B.Enning and G.Walf 592
N-point processing of optical fibre backscatter signals. R.D.Jeffery and J.L.Hullett 822
Noise generated in switched capacitor networks. Cl.-A.Gobet and A.Knob 734
Penalties of hard decision in signal detection. T.C.Tozer and J.Kollerstrom 199
Properties of a simple noise-sequence generator. W.Freeman and S.M.Hebden 55
Sub-Nyquist sampling process in presence of noisy sampling signal. M.Sarhadi and C.S.Aitchison 350
Superimposed pulse modulation for fibre optic analogue video transmission using semiconductor laser diodes. K.Sato and K.Asatani 538
Temporal frequency dependence of modal noise in fibres. E.G.Rawson, R.E.Norton and J.W.Goodman 301
Thermal phase noise in coherent optical-fibre systems. B.Culshaw and S.A.Kingsley 97
Treatment of noise-figure calculations in microwave transistor amplifiers. G.P.Young and J.O.Scanlan 17

NONLINEAR NETWORKS

Deriving stability criteria for nonlinear circuits with application to worst-case noise margin of I^2L. E.Seevinck 867

NONLINEAR SYSTEMS

Necessary conditions for absolute stability of nonlinear regulators. B.Porter 181
Numerical technique for determining pumped nonlinear device waveforms. R.G.Hicks and P.J.Khan 375
Stability of certain time-varying nonlinear systems. S.Mossaheb 190
System identification: approach to a coherent picture through template functions. P.Eykhoff 502

NUMERICAL METHODS AND NUMBER THEORY

Complex residue number arithmetic for high-speed signal processing. W.K.Jenkins 660
Interpolatory quadrature rules and error rate of digital communication systems. A.Luvison 16
Solution of $X=A_1X+XA_2+D$, $X(0)=C$ and receding horizon problem. E.H.El-Konyaly, A.Sobaih and I.El-Dokany 657

OPERATIONAL AMPLIFIERS

Novel circuit implementation of current conveyors using an o.a. and an o.t.a.. R.Senani 2
Novel insensitive lossless inductor simulation through inverse function generation (Comment). V.K.Singh 901
Switched-capacitor immittance convertors using a single operational amplifier. T.Inoue and F.Ueno 770

OPTICAL COMMUNICATION

1.6 Gbit/s optical receiver at 1.3 μm with saw timing retrieval circuit. J-I.Yamada, J.Temmyo, S.Yoshikawa and T.Kimura 57
Mechanical fibre optic switching using p.v.d.f. bimorph. T.Ebato, T.Kajiwara and S.Kobayashi 829
Optical heterodyne detection of directly frequency modulated semiconductor laser signals. S.Saito, Y.Yamamoto and T.Kimura 826
p-i-n f.e.t. hybrid optical receiver for 1.1-1.6 μm optical communication systems. D.R.Smith, A.K.Chatterjee, M.A.Z.Rejman, D.Wake and B.R.White 750
p-i-n/f.e.t. hybrid optical receiver for longer-wavelength optical communication systems. D.R.Smith, R.C.Hooper, K.Ahmad, D.Jenkins, A.W.Mabbitt and R.Nicklin 69
Simple optical wavelength meter in 700-1200 nm wavelength region. K.Sano, K.Okada and K.Hashimoto 912
Single-mode c.w. ridge-waveguide laser emitting at 1.55 μm. I.P.Kaminow, R.E.Nahory, M.A.Pollack, L.W.Stulz and J.C.DeWinter e75
Wavelength sensed mode control of semiconductor lasers. D.J.Malyon, D.W.Smith and R.W.Berry 744

OPTICAL CONNECTORS & COUPLERS

Asymmetric T-couplers for fibre optic data buses. E.Weidel and J.Guttmann 673

Coupling efficiency calculations on an integrated l.e.d./sphere-lens source for optical fibres. R.A.Abram and R.C.Goodfellow 14
Efficient laser-diode-single-mode-fibre coupling using two confocal lenses. M.Saruwatari and T.Sugie 955
Polarisation-independent optical circulator coupled with multimode fibres. T.Matsumoto 8
Precisely moulded plastic splices for optical fibres. T.Kurokawa, T.Yoshizawa and Y.Katayama 911
Triple-ball connector using fibre-bead location. D.B.Payne and C.A.Millar 11

OPTICAL DETECTORS

p-i-n f.e.t. hybrid optical receiver for 1.1-1.6 μm optical communication systems. D.R.Smith, A.K.Chatterjee, M.A.Z.Rejman, D.Wake and B.R.White 750

OPTICAL DISPERSION

Modal dispersion of optical fibres with a composite (alpha)-profile graded-index core. A.Weierholt e75
Polarisation mode dispersion measurements in long single mode fibres. M.Monerie, P.Lamouler and L.Jeunhomme 907

OPTICAL FIBRES

1 x 2 optical switch using new type of pentagonal prism. R.Watanabe and K.Asatani 257
21.2 km graded-index v.a.d. fibre with low loss and wide bandwidth. S.Sudo, M.Kawachi, T.Edahiro and K.Chida 152
800 Mbit/s optical transmission experiments with dispersion-free fibres at 1.5 μm. J-I.Yamada, S.Machida, T.Mukai and T.Kimura 115
800 MHz s.a.w. timing filter for optical fibre transmission system. J.Minowa, K.Nakagawa, K.Okuno, Y.Kobayashi and M.Morimoto 35
Adiabatic method for fibres with nonseparable index profiles. A.Barthelemy and J.Arnaud 193
Analysis and measurement of modal noise in an optical fibre. B.Daino, G.De Marchis and S.Piazzolla e75
Asymmetric T-couplers for fibre optic data buses. E.Weidel and J.Guttmann 673
Attenuation measurements performed by backscattering technique. B.Costa, B.Sordo, U.Menaglia, L.Piccari and G.Grasso 352
Attenuation of leaky modes in graded noncircular multimode fibres. J.J.Ramskov Hansen, A.Ankiewicz and M.J.Adams 94
Backscatter attenuation measurements in graded index fibres. M.Eriksrud, S.Lauritzen and N.Ryen 877
Backscattering in single-mode fibres. E.Brinkmeyer 329
Bandwidth of distorted multimode waveguides excited by laser sources. J.Arnaud and M.Rousseau-Leberre 34
Bandwidth of long monomode fibre links in the presence of weak mode coupling. M.Eve 80
Birefringence in graded-index monomode fibres with elliptical cross-section. R.A.Sammut 156
Birefringence in slightly elliptical optical fibres. R.A.Sammut 728
Bistable optical fibre switch. C.Dähne and A.L.Harmer 647
Calculation of impulse response of multimode optical fibre. P.L.Chu 429
Comparison of pulse responses of step-index fibres. A.B.Sharma, J.Saijonmaa and S.J.Halme 557
Coupling efficiency calculations on an integrated l.e.d./sphere-lens source for optical fibres. R.A.Abram and R.C.Goodfellow 14
Current sensing with metal-coated multimode optical fibres. G.L.Tangonan, D.I.Persechini, R.J.Morrison and J.A.Wysocki 958
Cutoff frequencies of vector wave modes in cladded inhomogeneous optical fibre. M.Hashimoto 806
Dependence of modal noise on source coherence and fibre length. H.Olesen 217
Detailed error estimates for first order WKB calculation method. G.Jacobsen and J.J.Ramskov Hansen 540
Differential propagation delay in optical multifibre cables. E.F.Andersen 389
Effect of axial refractive-index dip on zero total dispersion wavelength in single-mode fibres. B.P.Pal, A.Kumar and A.K.Ghatak 505
Effect of chromatic dispersion on pulses of arbitrary coherence. D.Gloge e240
Effect of deposition rate on spectral loss of GeO_2-P_2O_5-SiO_2 graded index fibres. S.R.Nagel and M.A.Saifi 469
Effect of laser noise on analogue fibre optic systems. H.B.Kim, R.Maciejko and J.Conradi 919
Effects of fibre propagation loss on diode-laser-fibre coupling. M.L.Dakss and B.Kim 421
Effects of radiation on doped silica core optical fibres. A.Rosiewicz, M.H.Gray, J.Irven, J.G.Titchmarsh and P.W.Black 866
Efficient large-frequency-shifted three-wave mixing in low dispersion wavelength region in single-mode optical fibre. K.Washio, K.Inoue and S.Kishida 658
Efficient laser-diode-single-mode-fibre coupling using two confocal lenses. M.Saruwatari and T.Sugie 955
Electro-optical polarisation control on single-mode optical fibres. M.Kubota, T.Oohara, K.Furuya and Y.Suematsu 573
Excitation of steady-state power distribution in parabolic-index fibres at Gaussian TEM_{00}-beam. E.G.Sauter and G.K.Grau 748
Experimental characterisation of graded-index single-mode fibres. C.Pask and R.A.Sammut 310
Fabrication of completely OH-free v.a.d. fibre. F.Hanawa, S.Sudo, M.Kawachi and M.Nakahara 699
Fabrication of low-loss and wide-bandwidth v.a.d. optical fibres at 1.3 μm wavelength. M.Nakahara, K.Chida, F.Hanawa, S.Sudo and M.Horiguchi 102
Fabrication of single-mode fibres by v.a.d.. S.Tomaru, M.Kawachi and T.Edahiro 511
Fibre optic accelerometer. A.B.Tveten, A.Dandridge, C.M.Davis and T.G.Giallorenzi 854
Fibre optic analogue transmission experiment for high-definition television signals using semiconductor laser diodes. K.Asatani, K.Sato, K.Maki and T.Miki 536
Fibre refractive-index profiling by modified near-field scanning. P.V.H.Sabine, F.Donaghy and D.Irving 882
Field measurement set for attenuation and bandwidth of optical links. R.Auffret, L.Pophillat and Y.Kervarrec 798
First higher-mode cutoff in two-layer elliptical fibre waveguides. S.R.Rengarajan and J.E.Lewis 263
Fusion splicing machine for optical fibres. H.Liertz 426
Graded monomode fibres and planar waveguides. R.A.Sammut and A.W.Snyder 32
High index microlenses for GaAlAs laser-fibre coupling. L.d'Auria, Y.Combemale, C.Moronvalle and A.Jacques 322
Higher-mode cutoff in elliptical dielectric waveguides (Comment). J.Citerne 13
Holographic measurement of refractive-index profile of optical fibre preform. P.L.Chu and D.Peri 876
Hydraulic pressure buckling in plastic coated optical fibre. K.Nakagawa, M.Takeshima and F.Ebisawa 838
Index matching fluids for long wavelengths (1.2-1.6 μm) fibre-optic applications (Comment). M.Fox and M.R.Dennis 651
Index profile determination in transition region of optical fibre preform. D.Peri and P.L.Chu 916
Interference filter all-fibre directional coupler for w.d.m.. H.F.Mahlein, H.Michel, W.Rauscher, A.Reichelt and G.Winzer 584
Kaleidoscope micro-optic star coupler. R.Ishikawa, K.Kaede, H.Nishimoto, K.Minemura and S.Matsushita 248
Leaky ray correction factors for elliptical multimode fibres. K.F.Barrell and C.Pask 532
Material dispersion zero in infra-red waveguides. K.Nassau 924
Measurement of refractive-index profiles in optical-fibre preforms by spatial-filtering technique. I.Sasaki, D.N.Payne and M.J.Adams 219
Microlens tipped on a single-mode fibre end for InGaAsP laser coupling improvement. Y.Murakami, J-I.Yamada, J-I.Sakai and T.Kimura 321
Modal dispersion of optical fibres with a composite (alpha)-profile graded-index core. A.Weierholt e75
Modified silicone as new type of primary coat for optical fibre. T.Yamanishi, K.Yoshimura, S.Suzuki, S.Seikai and N.Uchida 100
Moulded multifibre connectors using rectangular multirod arrangement. T.Satake and H.Murata 281
Multi-glass-rod optical-fibre splicers made by drawing technique. S.Nagasawa and H.Murata 136
Multilayer multimode optical fibre. R.Petrović 562
N-point processing of optical fibre backscatter signals. R.D.Jeffery and J.L.Hullett 822
Near-field correction factors for elliptical fibres. J.J.Ramskov Hansen, M.J.Adams, A.Ankiewicz and F.M.E.Sladen 580
Near-field distributions in selectively excited elliptical optical fibres. D.Yevick and B.Stoltz 210
Near-field intensity and modal power distribution in multimode graded-index fibres. O.G.Leminger and G.K.Grau 678
Nondestructive measurement of axially nonsymmetric refractive-index distribution of optical fibre preforms. T.Okoshi, M.Nishimura and M.Kosuge 722
Novel proof-tester for optical glass fibres. P.W.France 117
Observation of tubular modes in multimode graded-index optical fibres. P.Facq, P.Fournet and J.Arnaud 648
Optical cable fault location using correlation technique. K.Okada, K.Hashimoto, T.Shibata and Y.Nagaki 629
Optical fibre magnetic field sensors. A.Dandridge, A.B.Tveten, G.H.Jr.Sigel, E.J.West and T.G.Giallorenzi 408
Optical time domain reflectometry by photon counting. P.Healey and P.Hensel 631
Optimal excitation of multimode graded-index fibres in d.m.d. and d.m.a. measurements. J.Saijonmaa, A.B.Sharma and S.J.Halme 690
Optimised structure for preparing long ultra-low-loss single-mode fibres. B.J.Ainslie, C.R.Day, J.Rush and K.J.Beales 692
Perturbation theory for the evaluation of the normalised cutoff frequencies in radially inhomogeneous fibres. J.P.Meunier, J.Pigeon and J.N.Massot 27
Polarisation characteristics in long length v.a.d. single-mode fibres. K.Okamoto, Y.Sasaki, T.Miya, M.Kawachi and T.Edahiro 768
Polarisation characteristics in long length v.a.d. single-mode fibres (Comment). K.Okamoto, Y.Sasaki, T.Miya, M.Kawachi and T.Edahiro 954

Polarisation-independent optical circulator coupled with multimode fibres. T.Matsumoto 8
Polarisation-maintaining single-mode fibre cable design. L.Jeunhomme and M.Monerie 921
Polarisation mode dispersion measurements in long single mode fibres. M.Monerie, P.Lamouler and L.Jeunhomme 907
Polarisation optical time domain reflectometry. A.J.Rogers 489
Precisely moulded plastic splices for optical fibres. T.Kurokawa, T.Yoshizawa and Y.Katayama 911
Pulse broadening compensation in fibre-optical links. A.B.Puc and G.L.Yip 162
Pulse broadening in long-span dispersion-free single-mode fibres at 1.5 μm. A.Kawana, T.Miya, N.Imoto and H.Tsuchiya 188
Refracted power technique for cutoff wavelength measurement in singlemode waveguides. V.A.Bhagavatula, W.F.Love, D.B.Keck and R.A.Westwig 695
Rotation detection by optical fibre laser gyro with easily introduced phase-difference bias. K.Hotate, Y.Yoshida, M.Higashiguchi and N.Niwa 941
Simple self-centring technique for mounting microsphere coupling lens on a fibre. M.L.Dakss and B.Kim 463
Simplified parameter-based analysis of single-mode optical guides. W.J.Stewart 380
Single-ended fibre strain and length measurement in frequency domain. R.Kashyap and M.H.Reeve 689
Single-mode fibre fractional wave devices and polarisation controllers. H.C.Lefevre 778
Single-mode fibre optic directional coupler. R.A.Bergh, G.Kotler and H.J.Shaw 260
Single-mode fibre pressure sensitivity. A.M.Smith 773
Single-mode optical fibre switch. C.M.Miller, R.B.Kummer, S.C.Mettler and D.N.Ridgway 783
Single-polarisation single-mode optical fibre with refractive-index pits on both sides of core. T.Okoshi and K.Oyamada 712
Spectral- and length-dependent losses in optical fibres investigated by a two-channel backscatter technique. A.J.Conduit, A.H.Hartog and D.N.Payne 77
Subpicosecond measurement of response of optical fibres. J.Piasecki 498
Temporal frequency dependence of modal noise in fibres. E.G.Rawson, R.E.Norton and J.W.Goodman 301
Thermal phase noise in coherent optical-fibre systems. B.Culshaw and S.A.Kingsley 97
Transmission characteristics of 116.3 km and 65.1 km graded-index v.a.d. fibres at 1.55 μm and 1.3 μm. T.Edahiro, M.Kawachi, S.Sudo and H.Nagai 478
Transmission loss in low grade $SiCl_4$ v.a.d. fibres. H.Suda, K.Chida and M.Nakahara 802
Transmission properties of 30.4 km v.a.d. fibre. S.Sudo, H.Okazaki, M.Nakahara and M.Horiguchi 280
Triple-ball connector using fibre-bead location. D.B.Payne and C.A.Millar 11
Ultimately low OH content v.a.d. optical fibres. T.Moriyama, O.Fukuda, K.Sanada, K.Inada, T.Edahiro and K.Chida 698
Ultra wide bandwidth v.a.d. fibre. M.Nakahara, S.Sudo, N.Inagaki, K.Yoshida, S.Shibuya, K.Kokura and T.Kuroha 391 e644
Vector wave characteristics of radially inhomogeneous waveguide modes. M.Hashimoto 494

OPTICAL MEASUREMENT

Analysis and measurement of modal noise in an optical fibre. B.Daino, G.De Marchis and S.Piazzolla e75
Current sensing with metal-coated multimode optical fibres. G.L.Tangonan, D.I.Persechini, R.J.Morrison and J.A.Wysocki 958
Fibre refractive-index profiling by modified near-field scanning. P.V.H.Sabine, F.Donaghy and D.Irving 882

OPTICAL RECEIVERS

Optical receiver sensitivity improvement by a semiconductor laser preamplifier. Y.Yamamoto and H.Tsuchiya 233

OPTICAL SENSORS

Rotation detection by optical fibre laser gyro with easily introduced phase-difference bias. K.Hotate, Y.Yoshida, M.Higashiguchi and N.Niwa 941

OPTICAL STORES

Optical memory readout by superluminescent diode with integrated photodetector. M.-C.Amann, A.Kuschmider and J.Boeck 58

OPTICAL SWITCHING

Active Q-switching of lateral field coupling control d.h. laser. H.Ito, K.Gen-ei and H.Inaba 846
Integrated astable optical multivibrator using Mach-Zehnder interferometric optical switches. H.Ito, Y.Ogawa and H.Inaba 593
Mechanical fibre optic switching using p.v.d.f. bimorph. T.Ebato, T.Kajiwara and S.Kobayashi 829

OPTICAL TRANSMISSION

1 x 2 optical switch using new type of pentagonal prism. R.Watanabe and K.Asatani 257
8 Gbit/s optical transmission with t.j.s. GaAlAs laser and p-i-n detection. R.Tell and S.T.Eng 497
Baseband characteristics of long-wavelength l.e.d. systems. D.Gloge, K.Ogawa and L.G.Cohen 366
Calculation of impulse response of multimode optical fibre. P.L.Chu 429
Duobinary transmission with p-i-n f.e.t. optical receivers. M.J.O'Mahony 752
Effect of laser noise on analogue fibre optic systems. H.B.Kim, R.Maciejko and J.Conradi 919
Efficient generation of near-i.r. stimulated light scattering in optical fibres pumped in low-dispersion region at 1.3 μm. K.Washio, K.Inoue and T.Tanigawa 331
Fibre optic analogue transmission experiment for high-definition television signals using semiconductor laser diodes. K.Asatani, K.Sato, K.Maki and T.Miki 536
Field measurement set for attenuation and bandwidth of optical links. R.Auffret, L.Pophillat and Y.Kervarrec 798
Frequency dependence of Rayleigh backscattering in bidirectional optical systems at 0.83 and 1.3 μm. J.Conradi and I.S.Few 414
Frequency stabilisation of semiconductor lasers for heterodyne-type optical communication systems. T.Okoshi and K.Kikuchi 179
Intermode phase scanning for recovering phase-modulated signals on multimode optical fibres. P.R.Ball and B.Culshaw 259
Modal noise and optical feedback in high-speed optical systems at 0.85 μm. C.Baack, G.Elze, B.Enning and G.Walf 592
Moulded multifibre connectors using rectangular multirod arrangement. T.Satake and H.Murata 281
Nonblocking 8 x 8 optical matrix switch for fibre-optic communication. J.Minowa, Y.Fujii, Y.Nagata, T.Aoyama and K.Doi 422
Novel method for transmitting images through monomode fibres. J.Piasecki and A.Barthelemy 420
Novel supervisory channel for fibre optic transmission systems. P.Cochrane and J.A.Kitchen 624
OPSEF: An optical sensor for measurement of high electric field intensity. Y.Hamasaki, H.Gotoh, M.Katoh and S.Takeuchi 406
Retiming circuit for n.r.z. signals in 1.12 Gbit/s optical transmission system. B.Enning 815
Simple self-centring technique for mounting microsphere coupling lens on a fibre. M.L.Dakss and B.Kim 463
Simple structure high isolation multi/demultiplexer. T.Tanaka, H.Serizawa and Y.Tsujimoto 869
Superimposed pulse modulation for fibre optic analogue video transmission using semiconductor laser diodes. K.Sato and K.Asatani 538
Transmission characteristics of 116.3 km and 65.1 km graded-index v.a.d. fibres at 1.55 μm and 1.3 μm. T.Edahiro, M.Kawachi, S.Sudo and H.Nagai 478
Waisted-rib optical waveguides in GaAs. D.N.Macfadyen, C.R.Stanley and C.D.W.Wilkinson 440

OPTICAL WAVEGUIDES

Cutoff frequencies of vector wave modes in cladded inhomogeneous optical fibre. M.Hashimoto 806
Graded monomode fibres and planar waveguides. R.A.Sammut and A.W.Snyder 32
Low temperature diffusion process for fabricating optical waveguides in glass. C.W.Pitt, A.A.Stride and R.I.Trigle 701
Perturbation theory for the evaluation of the normalised cutoff frequencies in radially inhomogeneous fibres. J.P.Meunier, J.Pigeon and J.N.Massot 27

OPTICS

Analysis of geodesic lenses by beam propagation method. J.van der Donk and P.E.Lagasse 292
Coherence of injection phase-locked AlGaAs semiconductor laser. S.Kobayashi and T.Kimura 668
Electro-optical polarisation control on single-mode optical fibres. M.Kubota, T.Oohara, K.Furuya and Y.Suematsu 573
Faraday effect in single-mode optical fibre using an injection laser light source. A.M.Smith 206
Index matching fluids for long wavelength (1.2-1.6 μm) fibre-optic applications. C.M.Melliar-Smith, P.D.Lazay, G.A.Pasteur, E.A.Chandross and D.L.Wood 403
Integrated astable optical multivibrator using Mach-Zehnder interferometric optical switches. H.Ito, Y.Ogawa and H.Inaba 593
Model for return-beam-induced noise generation in GaAlAs semiconductor lasers. Y.Hirose and Y.Ogura 202
New class of one-bit digital autocorrelator. T.W.Cole 86
Nonblocking 8 x 8 optical matrix switch for fibre-optic communication. J.Minowa, Y.Fujii, Y.Nagata, T.Aoyama and K.Doi 422
Novel method for high resolution measurement of laser output spectrum. T.Okoshi, K.Kikuchi and A.Nakayama 630

Optical time domain reflectometry by photon counting. P.Healey and P.Hensel 631
Optimal excitation of multimode graded-index fibres in d.m.d. and d.m.a. measurements. J.Saijonmaa, A.B.Sharma and S.J.Halme 690
Photoelastic channel optical waveguides in epitaxial GaAs layers. L.D.Westbrook, P.J.Fiddyment and P.N.Robson 169
Semiconductor laser output modulated in GHz frequency region observed by image tube streak camera. M.Izutsu, H.Haga and T.Sueta 531
Simple optical wavelength meter in 700-1200 nm wavelength region. K.Sano, K.Okada and K.Hashimoto 912
Single-mode fibre fractional wave devices and polarisation controllers. H.C.Lefevre 778
Single-step continuous-tone computer-generated holograms. V.Srinivasan, C.P.Wong and M.L.Wang 213
Slab waveguide star coupler for multimode optical fibre. K.Nosu and R.Watanabe 608

OPTIMAL CONTROL

Solution of $X=A_1X+XA_2+D$, $X(0)=C$ and receding horizon problem. E.H.El-Konyaly, A.Sobaih and I.El-Dokany 657

OPTOELECTRONIC DEVICES

Near-infra-red absorption using InGaAsP sources. H.Temkin and A.K.Chin 437

OSCILLATION

Picosecond pulse generation in semiconductor lasers using resonance oscillation. P.Torphammar and S.T.Eng 587

OSCILLATORS

Broadband varactor-tuned GaAs f.e.t. oscillator. C.Rauscher 534
Free space video detection of harmonic content of 100 GHz impatt oscillator. J.R.Birch 799
High efficiency 90 GHz InP Gunn oscillators. J.D.Crowley, J.J.Sowers, B.A.Janis and F.B.Fank 705
Novel sinusoidal oscillator employing grounded capacitors. R.Senani 62
Novel sinusoidal oscillator employing grounded capacitors (Comment). R.Senani 863
Novel sinusoidal oscillator employing grounded capacitors (Comment). V.Singh 757
Parametric interactions when resonator reactances are varied in antiphase. B.Z.Kaplan 343
Single element controlled oscillator without external capacitors. V.P.Pyara and S.S.Jamuar 607

PARAMETRIC DEVICES

Certain ineffective parametric interactions. B.Z.Kaplan 26

PARTICLE BEAMS

Ion beam co-ordinate monitor. W.J.Szajnowski, M.S.Hodgart and K.G.Stephens 674
Ion beam oxidation of Nb-based Josephson junctions. R.Herwig 850
Neutralised ion beam milling: anomalous sputter yield behaviour. C.W.Pitt and S.P.Singh 721

PASSIVE FILTERS

Sidelobe suppression of s.a.w. resonant filter using twin-turn reflectors. M.Hikita, Y.Kinoshita, H.Kojima and T.Tabuchi 784

PATTERN RECOGNITION

Algorithms for computation of relative neighbourhood graph. R.B.Urquhart 556
Algorithms for computing relative neighbourhood graph (Comment). G.T.Toussaint 860
Computation of multiweight. K.Maitree and S.Kondo 933
Detecting instability in concavity trees. B.K.Marlow and B.G.Batchelor 138
More about a thinning algorithm. C.Arcelli, L.P.Cordella and S.Levialdi 51 e240

PERTURBATION THEORY

Perturbation theory for the evaluation of the normalised cutoff frequencies in radially inhomogeneous fibres. J.P.Meunier, J.Pigeon and J.N.Massot 27

PHASE-SHIFT KEYING

Influence of multipath fading in 4Φ-C.P.S.K. systems. T.T.Cung, M.Lecours and H.T.Huynh 733
Novel p.s.k. tanlock loop. A.H.Makarious and P.G.Farrell 957
Performance degradation of two-link binary c.p.s.k. system incorporating direct phase regenerator. N.A.Mathews and A.Riris 650

PHASE SHIFTERS

Voltage controlled monolithic s.a.w. phase shifter using m.z.o.s. structure. S.Urabe and S.Uki 777

PHOTOCONDUCTING DEVICES

Extrinsic photoconductivity in platinum-doped silicon. W.P.Bickley, D.V.Eddolls and E.F.Maher 898

PHOTODETECTORS

InGaAsP/InGaAs heterojunction p-i-n detectors with low dark current and small capacitance for 1.3 - 1.6 μm fibre optic systems. F.Capasso, R.A.Logan, A.Hutchinson and D.D.Manchon 893
Optical memory readout by superluminescent diode with integrated photodetector. M.-C.Amann, A.Kuschmider and J.Boeck 58
Very low noise photodetector system using p-i-n diode and baseband parametric upconvertor. D.J.Roulston 595

PHOTODIODES

InGaAs avalanche photodiode with InP p-n junction. H.Kanbe, N.Susa, H.Nakagome and H.Ando 163
InP/InGaAsP avalanche photodiodes with new guard ring structure. F.Osaka, K.Nakazima, T.Kaneda, T.Sakurai and N.Susa 716
p-i-n/f.e.t. hybrid optical receiver for longer-wavelength optical communication systems. D.R.Smith, R.C.Hooper, K.Ahmad, D.Jenkins, A.W.Mabbitt and R.Nicklin 69
Samll area InGaAs/InP p-i-n photodiodes: fabrication, characteristics and performance of devices in 274Mb/s and 45 Mb/s lightwave receivers at 1.31 μm wavelength. T.P.Lee, C.A.Burrus, A.G.Dentai and K.Ogawa 155

PHOTOELECTRIC DEVICES

8 Gbit/s optical transmission with t.j.s. GaAlAs laser and p-i-n detection. R.Tell and S.T.Eng 497
Impact ionisation in multilayered heterojunction structures. R.Chin, N.Jun.Holonyak, G.E.Stillman, J.Y.Tang and K.Hess 467
InGaAs avalanche photodiode with InP p-n junction. H.Kanbe, N.Susa, H.Nakagome and H.Ando 163
InP/InGaAsP avalanche photodiodes with new guard ring structure. F.Osaka, K.Nakazima, T.Kaneda, T.Sakurai and N.Susa 716
Integrated $In_{0.53}Ga_{0.47}As$ p-i-n f.e.t. photoreceiver. R.F.Leheny, R.E.Nahory, M.A.Pollack, A.A.Ballman, E.D.Beebe, J.C.DeWinter and R.J.Martin 353
Low leakage current and saturated reverse characteristic in broad-area InGaAsP diodes. F.Capasso, R.A.Logan, P.W.Foy, S.Sumski and D.D.Manchon 241

PHOTOTRANSISTORS

High sensitivity InP/InGaAs heterojunction phototransistor. J.C.Campbell, A.G.Dentai, C.A.Burrus and J.F.Ferguson 713

POLARISATION

Crosspolarisation characteristics of linear comb-line microstrip antennas. A.K.Brown 743
Effect of edge region on crosspolar performance of dichroic plate. R.Cahill and E.A.Parker 710
Effect of profile errors with large correlation diameter on axisymmetric antenna crosspolarisation. J.A.Jervase and S.I.Ghobrial 663
Ice-crystal depolarisation measurements at 28.6 GHz with simultaneous 16.5 GHz polarisation diversity radar observations. Y.M.M.Antar, A.Hendry, J.J.Schlesak, R.L.Olsen and R.C.Bérubé 808
In-line fibre-optic polariser. W.Eickhoff 762

Polarisation characteristics in long length v.a.d. single-mode fibres. K.Okamoto, Y.Sasaki, T.Miya, M.Kawachi and T.Edahiro 768
Polarisation characteristics in long length v.a.d. single-mode fibres (Comment). K.Okamoto, Y.Sasaki, T.Miya, M.Kawachi and T.Edahiro 954
Polarisation-maintaining single-mode fibre cable design. L.Jeunhomme and M.Monerie 921
Polarisation mode dispersion measurements in long single mode fibres. M.Monerie, P.Lamouler and L.Jeunhomme 907
Single-mode fibre fractional wave devices and polarisation controllers. H.C.Lefevre 778
Single-polarisation single-mode optical fibre with refractive-index pits on both sides of core. T.Okoshi and K.Oyamada 712
Uplink adaptive depolarisation cancellation in a ground-to-satellite link. M.Nouri and M.R.Braine 68

PRINTED CIRCUITS

Single-row routeing and planarity. J.J.Narraway and K.-M.So 219

PULSE-CODE MODULATION

Improved digital automatic gain control for p.c.m. signals. J.E.Flood and J.M.Fonseca 589

PULSE GENERATION

Applications of dual-gate GaAs m.e.s.f.e.t.s. for fast pulse shape regeneration systems. W.Filensky, F.Ponse and H.Beneking 214
Bandwidth limited picosecond optical pulse generation from actively mode-locked AlGaAs diode laser. H.Ito, H.Yokoyama and H.Inaba 620
Generation and detection of short-duration unipolar stress pulses using poled PVF_2 films. S.Kovnovich and E.Karnik 776
Generation of nanosecond high-voltage pulses with high repetition rate. M.Kowatsche and J.Lafferl 196
Optoelectronic regenerative pulser. T.C.Damen and M.A.Duguay 166
Picosecond pulse generation in semiconductor lasers using resonance oscillation. P.Torphammar and S.T.Eng 587
Simple picosecond pulse generation scheme for injection lasers. C.Lin, P.L.Liu, T.C.Damen, D.J.Eilenberger and R.L.Hartman 600

QUANTISATION

Minimum-distortion functional for one-dimensional quantisation. H.V.Poor 23

RADAR

Development of pulsed self-oscillating mixer. M.G.Somekh, W.Richmond, J.Moroz and M.J.Lazarus 597
New direction-of-motion Doppler detector. M.J.Lazarus, F.R.Pantoja, M.Somekh, S.Novak and S.Margison 953
New realisation of maximum likelihood receiver for low-angle tracking radar. S.Haykin, J.Reilly and D.Taylor 288

RADAR CROSS-SECTIONS

Analysis of r.c.s. diagram of target in Tchebyshev polynomial space. G.Chassay and J.Saillard 652

RADIATION AND RADIATION EFFECTS

Circularly polarised radiation from narrow wall slots in rectangular waveguide. D.R.Hill 559
Effects of radiation on doped silica core optical fibres. A.Rosiewicz, M.H.Gray, J.Irven, J.G.Titchmarsh and P.W.Black 866
Field probe for measuring both amplitude and phase of antenna radiation patterns. D.E.N.Davies and S.M.Vakil 873
High radiation effects in X-ray lithography. Z.Znamirowski and W.Czarczynski 178
Measurement of extinction cross-section of single particles at 100 GHz. D.J.Harris and T.M.Teo 500
New microstrip slot radiator for medical applications. I.J.Bahl, S.S.Stuchly and M.A.Stuchly 731
New technique for efficient pattern computation of aperture and reflector antennas. R.Mittra and W.L.Ko 549
Radiation characteristics of helix antenna with parasitic elements. H.Nakano and J.Yamauchi 687
Reflection coefficient optimisation at feed of parabolic antenna fitted with vertex plate. H.Cory and Y.Leviatan 945
Stationary phase method for far-field computation of defocused reflector antennas. M.H.A.J.Herben, R.Middelkoop and F.J.J.Gielkens 519

RADIO LINKS

Optimum antenna separation for space diversity in l.o.s. radio links over flat ground. J.A.Garcia-Lopez and V.Casares-Giner 717

RADIOCOMMUNICATION

Spectral shaping of digitised speech for mobile radio applications. P.M.Petrović 363

RADIOWAVE PROPAGATION

A source of thermocouple error in radiofrequency electric fields. D.P.Chakraborty and I.A.Brezovich 853
Earth-space rain-cell modelling through SIRIO propagation data. E.Matricciani 81
Frequency dependence of effective path length in prediction of rain attenuation statistics. H.N.Kheirallah, J.P.Knight, R.L.Olsen, K.S.McCormick and B.Segal 448
Ice-crystal depolarisation measurements at 28.6 GHz with simultaneous 16.5 GHz polarisation diversity radar observations. Y.M.M.Antar, A.Hendry, J.J.Schlesak, R.L.Olsen and R.C.Bérubé 808
Median signal strength prediction for mobile radio propagation in London. J.D.Parsons, M.F.Ibrahim and R.J.Samuel 172
Spectra of amplitude scintillations in X-band satellite downlink. J.Haddon, P.Lo, T.J.Moulsley and E.Vilar 619

RECEIVERS

1.6 Gbit/s optical receiver at 1.3 μm with saw timing retrieval circuit. J-I.Yamada, J.Temmyo, S.Yoshikawa and T.Kimura 57
Numerical evaluation of logarithmic receiver thresholds. D.C.Schleher 875

RECEPTION

Reception of phase-locked l.f. and m.f. transmissions by receivers having ferrite-rod antennas. P.Knight 40

RECOMBINATION

Shallow trap spectroscopy in InP: Fe. J.Bonnafe, M.Castagne, J.Romestan, M.De Murcia and J.P.Fillard 313

RECURSIVE FILTERS

Recursive filters with uniform power distribution. R.P.Kurshan and A.M.Odlyzko 672

REFLECTOR ANTENNAS

Improved orbit utilisation by interferometric sidelobe suppression. M.J.S.Van Ommeren, M.H.A.J.Herben and J.Arnbak 937
Reflection coefficient optimisation at feed of parabolic antenna fitted with vertex plate. H.Cory and Y.Leviatan 945

REFRACTIVE INDEX PROFILES

Excitation of steady-state power distribution in parabolic-index fibres at Gaussian TEM_{00}-beam. E.G.Sauter and G.K.Grau 748
Index profile determination in transition region of optical fibre preform. D.Peri and P.L.Chu 916
Nondestructive measurement of axially nonsymmetric refractive-index distribution of optical fibre preforms. T.Okoshi, M.Nishimura and M.Kosuge 722

REPEATERS

Retiming circuit for n.r.z. signals in 1.12 Gbit/s optical transmission system. B.Enning 815

RESONATORS

Dielectric resonator dual modes filter. P.Guillon, Y.Garault and J.Farence 646
Intermodulation in X-cut lithium tantalate resonators. M.Planat, G.Theobald, J.J.Gagnepain and P.Siffert 174

SATELLITE LINKS

E.I.R.P. allocation for a nonlinear satellite channel with multiple transmit beams and carriers. J.Arnbak e75

Earth-space rain-cell modelling through SIRIO propagation data. E.Matricciani 81
Frequency dependence of effective path length in prediction of rain attenuation statistics. H.N.Kheirallah, J.P.Knight, R.L.Olsen, K.S.McCormick and B.Segal 448
Improved orbit utilisation by interferometric sidelobe suppression. M.J.S.Van Ommeren, M.H.A.J.Herben and J.Arnbak 937
Increasing power input to a single solar power satellite rectenna by using a pair of satellites. R.V.Gelsthorpe and P.Q.Collins 311
Spectra of amplitude scintillations in X-band satellite downlink. J.Haddon, P.Lo, T.J.Moulsley and E.Vilar 619
Statistical intensity of amplitude scintillations on earth-space X-band link. J.Haddon, P.Lo, T.J.Moulsley and E.Vilar 546
Television demodulator receiving signals by satellite. J.M.Adant and P.Delogne 401
Uplink adaptive depolarisation cancellation in a ground-to-satellite link. M.Nouri and M.R.Braine 68

SATELLITE RELAY SYSTEMS

E.I.R.P. allocation in single-destination f.d.m.a. satellite communication systems. P.M.Bakken and T.Maseng 6 e75

SCATTERING

Analysis of r.c.s. diagram of target in Tchebyshev polynomial space. G.Chassay and J.Saillard 652
Backscatter attenuation measurements in graded index fibres. M.Eriksrud, S.Lauritzen and N.Ryen 877
Backscattering in single-mode fibres. E.Brinkmeyer 329
Efficient generation of near-i.r. stimulated light scattering in optical fibres pumped in low-dispersion region at 1.3 μm. K.Washio, K.Inoue and T.Tanigawa 331
Frequency dependence of Rayleigh backscattering in bidirectional optical systems at 0.83 and 1.3 μm. J.Conradi and I.S.Few 414
Index matching fluids for long wavelength (1.2-1.6 μm) fibre-optic applications. C.M.Melliar-Smith, P.D.Lazay, G.A.Pasteur, E.A.Chandross and D.L.Wood 403
Mobility of holes in the quaternary alloy $In_{1-x}Ga_xAs_yP_{1-y}$. J.R.Hayes, A.R.Adams and P.D.Greene 282
N-point processing of optical fibre backscatter signals. R.D.Jeffery and J.L.Hullett 822

SCHOTTKY-BARRIER DEVICES

Deep level defects in Au/ZnSe Schottky diodes. P.Besomi and B.W.Wessels 794
Ideality and noise figure characteristics of r.f. sputtered millimetre GaAs diodes. Y.Anand, A.Christou and H.Day 581
Low noise GaAs varactor and mixer diodes prepared by molecular beam epitaxy. J.J.Harris and J.M.Woodcock 317
Micrometre-gate m.e.s.f.e.t.s. on laser-annealed polysilicon. J.Bernard, J.Frey, K.F.Lee and J.F.Gibbons 297
Schottky barrier height of Au on n-type $Ga_{1-x}Al_xSb$ ($0.0 \leq x \leq 0.65$). R.Chin, R.A.Milano and H.D.Law 626
Two-dimensional electron gas m.e.s.f.e.t. structure. D.Delagebeaudeuf, P.Delescluse, P.Etienne, M.Laviron, J.Chaplart and N.T.Linh 667
Unbiased InP detectors in the submillimetre wave region. T.Takada, T.Makimura and T.Ishibashi 765

SEMICONDUCTOR DEVICES AND MATERIALS

1.5-1.7 μm v.p.e. InGaAsP/InP c.w. lasers. G.H.Olsen, T.J.Zamerowski and N.J.Digiuseppe 516
5 GHz binary frequency division on GaAs. M.Cathelin, G.Durand, M.Gavant and M.Rocchi 535
Activation of low dose silicon implants in GaAs by multiply scanned electron beams. N.J.Shah, H.Ahmed, I.R.Sanders and J.F.Singleton 433
C.W. operation of GaInAsP/InP laser with chemically etched mirror. K.Iga and B.I.Miller 830
Correction of spreading resistance data obtained from bevelled shallow junctions. S.A.Abbashi and A.Brunnschweiler 507
Current/voltage characteristics of degenerated molybdenum and platinum Schottky diodes. J.Martinez, E.Calleja and J.Piqueras 183
Deep trapping centres in n-GaAs surface barrier diodes for nuclear radiation detection. S.J.Pearton, A.J.Tavendale and A.A.Williams 483
Effects of capacitance at crossover wirings in power GaAs m.e.s.f.e.t.s.. Y.Aono, A.Higashisaka and F.Hasegawa 417
Estimation of fringing capacitance of electrodes on s.i. GaAs substrate. A.Higashisaka and F.Hasegawa 411
GaInAsP/InP laser with monolithically integrated monitoring detector. K.Iga and B.I.Miller 342
Growth of $Ga_{0.47}In_{0.53}As$ on InP by low-pressure m.o. c.v.d.. J.P.Hirtz, J.P.Larivain, J.P.Duchemin, T.P.Pearsall and M.Bonnet 415
Growth-parameter dependence of deep levels in molecular-beam-epitaxial GaAs. R.A.Stall, C.E.C.Wood, P.D.Kirchner and L.F.Eastman 171
InP epitaxy with a new metalorganic compound. H.Renz, J.Weidlein, K.W.Benz and M.H.Pilkuhn 228
Modulating transistor: a new class of semiconductor device. G.I.Fursin 662
Ohmic contacts on n-GaAs produced by laser alloying of Ge films. G.Badertscher, R.P.Salathe and W.Luthy 113
Photo-f.e.t. method: high-resolution deep-level measurement technique using a m.e.s.f.e.t. structure. F.J.Tegude and K.Heime 22
Planar-doped barriers in GaAs by molecular beam epitaxy. K.J.Malik, T.R.Aucoin, R.L.Ross, K.Board, C.E.C.Wood and L.F.Eastman 836
Role of substrate in electrical properties of GaAs implanted layers. G.M.Martin, M.Berth and C.Venger 278
Semidistributed neuristor using plasma-coupled modulating transistors. V.A.Skorik and G.I.Fursin 676
Short-channel polysilicon-gate m.o.s.f.e.t.s fabricated by c.w. argon laser annealing of arsenic-implanted source and drain. T.C.Teng, J.D.Merritt, J.Velez, J.Peng and L.Palkuti 477
Use of Ga in metal-GaAs contacts to eliminate large As loss peaks. T.Sebestyen, I.Mojzes and D.Szigethy 504

SEMICONDUCTOR JUNCTIONS

Photo-f.e.t. method: high-resolution deep-level measurement technique using a m.e.s.f.e.t. structure. F.J.Tegude and K.Heime 22

SEMICONDUCTOR LASERS

Simultaneous feedback control of bias and modulation currents for injection lasers. F.S.Chen 7

SEMICONDUCTORS

Ballistic electron motion in GaAs at room temperature. L.F.Eastman, R.Stall, D.Woodard, N.Dandekar, C.E.C.Wood, M.S.Shur and K.Board 524
Ballistic electron transport in a nonparabolic band. J.B.Socha and G.J.Rees 872
Band-to-band tunnelling current in $Ga_{0.47}$ $In_{0.53}$ As p-n junctions. T.P.Pearsall 771
C/V measurements on m.i.s. structures on n-InSb formed by room temperature reactive deposition of Si_3N_4. F.Olcaytug, K.Riedling and W.Fallmann 677
Calculations of the intrinsically higher temperature stability of electronic devices made from quaternary alloys. A.R.Adams 177
Characterisation of multiple-scan electron beam annealing method. R.A.McMahon, H.Ahmed, R.M.Dobson and J.D.Speight 295
Dielectric constant of semi-insulating gallium arsenide. R.E.Neidert 244
Evidence for alloy scattering from pressure-induced changes of electron mobility in $In_{1-x}Ga_xAs_yP_{1-y}$. A.R.Adams, H.L.Tatham, J.R.Hayes, A.N.El-Sabbahy and P.D.Greene 560
GaAs n^+-p^--n^+ ballistic structure. M.S.Shur and L.F.Eastman 522
Impact ionisation in multilayered heterojunction structures. R.Chin, N.Jun.Holonyak, G.E.Stillman, J.Y.Tang and K.Hess 467
InGaAs avalanche photodiode with InP p-n junction. H.Kanbe, N.Susa, H.Nakagome and H.Ando 163
Low temperature thermal annealing of arsenic implanted silicon. P.D.Scovell and J.M.Young 614
Mobility of holes in the quaternary alloy $In_{1-x}Ga_xAs_yP_{1-y}$. J.R.Hayes, A.R.Adams and P.D.Greene 282
Open ampoule diffusion in InP. P.N.Favennec, L.Henry, M.Gauneau, H.L'Haridon and G.Pelous 832
Orientation dependence of ballistic electron transport and impact ionisation. H.Shichijo, K.Hess and G.E.Stillman 208
Photoelastic channel optical waveguides in epitaxial GaAs layers. L.D.Westbrook, P.J.Fiddyment and P.N.Robson 169
Redistribution of chromium in semi-insulating GaAs: Cr during laser annealing. M.H.Badawi, B.J.Sealy and J.B.Clegg 554
Schottky barrier height of Au on n-type $Ga_{1-x}Al_xSb$ ($0.0 \leq x \leq 0.65$). R.Chin, R.A.Milano and H.D.Law 626
Space charge limited current in an insulator at high fields. Y.K.Sharma 896
Temperature dependence of threshold and electrical characteristics of InGaAsP-InP d.h. lasers. N.K.Dutta, R.J.Nelson and P.A.Barnes 653

SEMICONDUCTORS (II-VI)

n-channel m.i.s.f.e.t.s. in epitaxial HgCdTe/CdTe. G.M.Williams and E.R.Gertner 839

SEMICONDUCTORS (III-V)

Channelled substrate buried heterostructure InGaAsP/InP laser emitting at 1.55 μm. S.Takahashi, H.Saito and G.Iwane 922
Channelled substrate lasers prepared by combination of organometallic pyrolysis and liquid-phase epitaxy. J.P.Noad, C.M.Look and A.J.Springthorpe 685

Dual wavelength surface emitting InGaAsP l.e.d.s.. T.P.Lee, C.A.Burrus and A.G.Dentai 845
Growth conditions to achieve mobility enhancement in $Al_xGa_{1-x}As$-GaAs heterojunctions by m.b.e.. H.Morkoc, L.C.Witkowski, T.J.Drummond, C.M.Stanchak, A.Y.Cho and B.G.Streetman 753
I.C.-compatible completely planar GaAs m.e.s.f.e.t.s. by selective diffusion. N.Arnold, H.Daembkes and K.Heime 923
InGaAsP/InGaAs heterojunction p-i-n detectors with low dark current and small capacitance for 1.3 - 1.6 μm fibre optic systems. F.Capasso, R.A.Logan, A.Hutchinson and D.D.Manchon 893
Low-threshold high-T_0 constricted double heterojunction AlGaAs diode lasers. D.Botez and J.C.Connolly 942
Method for reproducible l.p.e. growth of GaInAsP. M.Janson and A.Josefsson 879
Microwave power amplification with InP f.e.t.s.. M.Armand, J.Chevrier and N.T.Linh 906
O.M. V.P.E. growth of AlGaSb and AlGaAsSb. C.B.Cooper, R.R.Saxena and M.J.Ludowise 892

SENSITIVITY

Pole sensitivity of all-pole lowpass LC ladder networks. J.K.Fidler 856

SEQUENTIAL CIRCUITS AND MACHINES

Easily testable sequential machines with extra inputs and extra outputs. S.R.Das, Z.Chen and Y.L.Dai 119

SIGNAL PROCESSING

4-bits digitally driven integrated amplitude modulator for data processing. M.Papuchon, C.Puech and A.Schnapper 142
Adaptive crosstalk cancellation for crosspolarised digital transmissions. P.Sobieski and P.Delogne 385
An improvement for the t.l.m. method. P.Saguet and E.Pic 247
Automatic aperture performance measurement for high speed analogue-digital convertors. K.Gardner and P.T.Johnson 741
Block adaptive prediction of colour television signals. H.Gharavi 226
Class of block codes for the Gaussian channel. D.E.Lazić 185
Complex residue number arithmetic for high-speed signal processing. W.K.Jenkins 660
Δ-entropy and rate distortion bounds for generalised Gaussian information sources and their applications to image signals. W.Szepanski 109
Design of s.a.w. convolver for processing m.s.k. modulated waveforms. H.Engan, K.A.Ingebrigtsen and A.Rønnekleiv 908
Discrete cosine transform processor using a c.c.d. programmable transversal filter. N.Kapur, J.Mavor and M.A.Jack 139
Efficient algorithm for determination of a.r. part of a.r.m.a. model. G.Carayannis, N.Kalouptsidis and D.Manolakis 656
Error-free coefficient realisation of recursive part via input-partitioned filter structure. C.L.Nikias 236
Error performance of frequency-hopped d.p.s.k. system. K.Yamada and K.Daikoku 305
Error-rate measurements for s.f.s.k. with band limitation. H.Singh and T.T.Tjhung 64
Ion beam co-ordinate monitor. W.J.Szajnowski, M.S.Hodgart and K.G.Stephens 674
Mean square error of s.s.b.a.m. class 4 partial response data signals due to slope, sag and ripple group delay components. L.J.Millott and B.M.Smith 492
Method for signal processing with transfer function coefficients dependent only on timing. Y.P.Tsividis 796
New class of one-bit digital autocorrelator. T.W.Cole 86
Nonlinear acoustoelectroluminescence. A.B.Sherman, A.A.Dobrovolsky and V.V.Lemanov 37
Optical receiver sensitivity improvement by a semiconductor laser preamplifier. Y.Yamamoto and H.Tsuchiya 233
Penalties of hard decision in signal detection. T.C.Tozer and J.Kollerstrom 199
Power spectra of HDBn signals. D.Drajić and G.Petrović 289
Power spectrum of scrambled signal. G.Petrović 147 e240
Relationship between system delay and transmission rate in time-encoded speech. D.C.Mason and D.M.Balston 128
Retiming circuit for n.r.z. signals in 1.12 Gbit/s optical transmission system. B.Enning 815
S.A.W. implementation of whitening filters for satellite digital communications. J.Henaff and M.Feldmann 124
Sampled-data recursive integrator for ultra-low-frequency wideband phase shifter. M.Emura, Y.Fukui and S.Yoneda 330
Stability of linear predictive descriptions of curves used in handwriting. Y.K.Ha and I.H.Witten 909
Storage correlator as an adaptive inverse filter. D.Behar, G.S.Kino, J.E.Bowers and H.Olaisen 130
Sub-Nyquist sampling process in presence of noisy sampling signal. M.Sarhadi and C.S.Aitchison 350
Time scale independent signal transmission. L.Faltin 439
Use of a programmable filter for inverse filtering. D.Behar, H.Olaisen, G.S.Kino, D.Corl and P.M.Grant 88

SILICON

Effectiveness of charged vacancies in diffusion of implanted boron in silicon. F.Runovc 49
Extrinsic photoconductivity in platinum-doped silicon. W.P.Bickley, D.V.Eddolls and E.F.Maher 898
Photoacoustic effect in laser annealing. K.Hoh 931
Pulsed electron-beam annealing of phosphorus-implanted silicon. T.Inada, T.Sugiyama, N.Okano and Y.Ishikawa 54
Temperature dependence of storage time in silicon p^+-n-n^+ switching diodes and reduction of harmonic distortion. A.Rosen, R.U.Martinelli and M.Caulton 66

SILICONES

Modified silicone as new type of primary coat for optical fibre. T.Yamanishi, K.Yoshimura, S.Suzuki, S.Seikai and N.Uchida 100

SIMULATION

Application of decision feedback equaliser in an environment with narrowband interfering signals. C.K.Pauw 787
Brune-section simulation circuits using two operational amplifiers. T.Inoue, F.Ueno and Y.Fukuda 781
Construction of optimal low-rate convolutional codes. G.Whale 767
Model for return-beam-induced noise generation in GaAlAs semiconductor lasers. Y.Hirose and Y.Ogura 202
Sampling theorem application to s.a.w. diffraction simulation. T.Kodama 460
Slotline-microstrip transition on iso/anisotropic substrate: a more accurate design. A.Podcameni and M.L.Coimbra 780
Various approximating functions for cascade or ladder simulating RC active networks. R.Leuenberger 309

SOLAR CELLS

Cadmium telluride/Langmuir film photovoltaic structures. I.M.Dharmadasa, G.G.Roberts and M.C.Petty 201
Optimisation of p^+ doping level of n^+-p-p^+ bifacial b.s.f. solar cells by ion implantation. J.Eguren, J.Del Alamo and A.Luque 633
Surface passivation of inversion layer m.i.s. solar cells. Y.W.Lam, M.A.Green and L.W.Davies 707

SOLID-STATE MICROWAVE CIRCUITS

Treatment of noise-figure calculations in microwave transistor amplifiers. G.P.Young and J.O.Scanlan 17

SPECTRAL ANALYSIS

Error rate performance for s.f.s.k. with cochannel and intersymbol interference. J.Cruz and R.S.Simpson 515
Estimation of a sinusoid in uncorrelated noise using adaptive line enhancer. V.U.Reddy 473
Power spectra of d.p.s.k. signals for data transmission. D.Drajić and G.Petrović 251
Power spectra of HDBn signals. D.Drajić and G.Petrović 289
Recursive filters with uniform power distribution. R.P.Kurshan and A.M.Odlyzko 672

SPEECH PROCESSING

Estimating the pitch period of voiced speech. E.Ambikairajah, M.J.Carey and G.Tattersall 464
Further results on relationship between system delay and transmission rate in time encoded speech-type systems. L.F.Turner, E.Frangoulis and A.Alcaim 947

SPEECH RECOGNITION

Further results on relationship between system delay and transmission rate in time encoded speech-type systems. L.F.Turner, E.Frangoulis and A.Alcaim 947
L.P.C. speech recognition with random reference correlation. A.Cohen and S.Beker 885
Relationship between system delay and transmission rate in time-encoded speech. D.C.Mason and D.M.Balston 128

SPUTTERING

Neutralised ion beam milling: anomalous sputter yield behaviour. C.W.Pitt and S.P.Singh 721

Performance of sputtered SiO_2 film as acoustic antireflection coating at sapphire/water inerface. J.Kushibiki, T.Sannomiya and N.Chubachi 737

STABILITY

High frequency stability of laser diode for heterodyne communication systems. F.Favre and D.Le Guen 709
High frequency stability of near-perfect active phase compensated integrators. K.K.Tuladhar 888
Necessary conditions for absolute stability of nonlinear multivariable regulators. B.Porter 392
Necessary conditions for absolute stability of nonlinear regulators. B.Porter 181
Stability of certain time-varying nonlinear systems. S.Mossaheb 190

STOCHASTIC SYSTEMS AND CONTROL

Comparison of two iterative estimation procedures. P.Stoica 754
Effect of dead time on closed-loop regulation. C.C.Hang 133
New reinforcement algorithm in learning automata. D.Maravall 623

SURFACE-ACOUSTIC-WAVE DEVICES

1.6 Gbit/s optical receiver at 1.3 μm with saw timing retrieval circuit. J-I.Yamada, J.Temmyo, S.Yoshikawa and T.Kimura 57
800 MHz s.a.w. timing filter for optical fibre transmission system. J.Minowa, K.Nakagawa, K.Okuno, Y.Kobayashi and M.Morimoto 35
Adjustable magnetostatic surface-wave multistrip directional coupler. J.P.Castera and P.Hartemann 195
Combined triple-transit and bulk-wave suppression in s.a.w. delay line. D.J.Gunton 149 e240
Design of s.a.w. convolver for processing m.s.k. modulated waveforms. H.Engan, K.A.Ingebrigtsen and A.Rønnekleiv 908
Efficient miniature s.a.w. convolver. B.J.Darby, D.J.Gunton, M.F.Lewis and C.O.Newton 726
Generation of surface acoustic waves by means of a c.w. laser. E.A.Ash, E.Dieulesant and H.Rakouth 470
Harmonic suppression in surface-acoustic-wave devices using jogged multistrip couplers. R.J.Murray, R.F.Mitchell and J.Schofield 356
Measurement of s.a.w. device stripe/period ratio using optical diffraction. C.W.Chapman and G.W.Judd 952
Nonlinear acoustoelectroluminescence. A.B.Sherman, A.A.Dobrovolsky and V.V.Lemanov 37
Nonlinear interaction of s.a.w.s. in piezoelectric crystals with secondary electrons. A.A.Dobrovolsky, V.V.Lemanov, A.B.Sherman, Yu.M.Gal'Perin and V.I.Kozub 243
PVF_2 transducers for Rayleigh waves. F.Mattiocco, E.Dieulesaint and D.Royer 250
Resonant s.a.w. filter using surface shear wave mode on $LiTaO_3$ substrate. M.Hikita, Y.Kinoshita, H.Kojima and T.Tabuchi 446
S.A.W. device reflectors weighted by combination of withdrawn and segmented lines. W.J.Tanski 793
S.A.W. implementation of whitening filters for satellite digital communications. J.Henaff and M.Feldmann 124
S.A.W. monolithic acoustoelectronic oscillator. Yu.V.Gulyaev, I.M.Kotelyansky, A.V.Medved and R.A.Mishkinis 114
Sampling theorem application to s.a.w. diffraction simulation. T.Kodama 460
Sidelobe suppression of s.a.w. resonant filter using twin-turn reflectors. M.Hikita, Y.Kinoshita, H.Kojima and T.Tabuchi 784
Storage correlator as an adaptive inverse filter. D.Behar, G.S.Kino, J.E.Bowers and H.Olaisen 130
Velocity, electromechanical coupling factor and acoustic loss of surface shear waves propagating along x-axis on rotated Y-cut plates of $LiNbO_3$. H.Kojima, Y.Kinoshita, M.Hikita and T.Tabuchi 445
Voltage controlled monolithic s.a.w. phase shifter using m.z.o.s. structure. S.Urabe and S.Uki 777

SWITCHED CAPACITOR NETWORKS

Evaluation of transfer functions of ideal s.c. networks in z-domain using standard linear symbolic or semisymbolic network analysis programs. E.Wehrhahn 801
Novel bottom-plate stray-insensitive voltage inverter switch. D.Herbst and B.J.Hosticka 636
Pseudopower in switched-capacitor filters. M.K.Li 813
Simple method for analysis of a class of switched-capacitor filters. G.Müller and G.C.Temes 852
Switched-capacitor lowpass filter without active components. S.Manetti and A.Liberatore 883

SWITCHES

Clock-steering synthesis using spectral techniques. P.D.Picton 409
Electrofluorescent colloid light switch. B.R.Jennings and P.J.Ridler 833

SWITCHING AND SWITCHING CIRCUITS

Bistable optical fibre switch. C.Dähne and A.L.Harmer 647
Easily testable sequential machines with extra inputs and extra outputs. S.R.Das, Z.Chen and Y.L.Dai 119
Single-mode optical fibre switch. C.M.Miller, R.B.Kummer, S.C.Mettler and D.N.Ridgway 783
Switching in m.i.s.m. and m.i.s.i.m. structures. M.Darwish and K.Board 577

TELECOMMUNICATION

800 Mbit/s optical transmission experiments with dispersion-free fibres at 1.5 μm. J-I.Yamada, S.Machida, T.Mukai and T.Kimura 115
Alternative burst transmission technique for digital telephone reticulation. R.A.Court 583
C.P.S.K. receiver performances in presence of carrier-frequency offset. M.Č.Stefanović 182
Dependence of modal noise on source coherence and fibre length. H.Olesen 217
Line coding and burst transmission in the local network. H.B.Groen 165
Power spectrum of scrambled signal. G.Petrović 147 e240

TELEPHONY

Line coding and burst transmission in the local network. H.B.Groen 165
New digital automatic gain control for p.c.m. signals. J.E.Flood and J.M.Fonseca 96

TELEVISION

Double-stimulas quality rating method for television digital codecs. T.A.White and J.W.Allnatt 714
Subjective assessment method for television digital codecs. J.W.Allnatt 450
Television demodulator receiving signals by satellite. J.M.Adant and P.Delogne 401

THIN-FILM DEVICES

Cadmium telluride/Langmuir film photovoltaic structures. I.M.Dharmadasa, G.G.Roberts and M.C.Petty 201

THYRISTORS

Predicting the surge capability of power thyristors. A.Silard, M.Bodea and M.Luca 325

TRANSDUCERS

Generation and detection of short-duration unipolar stress pulses using poled PVF_2 films. S.Kovnovich and E.Karnik 776
Investigations on a new force-frequency measuring gauge. K.Grantcharov, M.Borissov, D.Detchev, L.Spassov and E.Yossifov 71
PVF_2 transducers for Rayleigh waves. F.Mattiocco, E.Dieulesaint and D.Royer 250
Thick-film strain gauges and pressure transducers. Z.H.Meiksin and W.D.Humbel 242
Tuning of transducer elements in transducer array. P.R.Saseendran Pillai and C.S.Sridhar 606

TRANSFER FUNCTIONS

All-pole filter with predistorted attenuation characteristic. D.Rabrenović and V.Jovanović 950
Determining transfer functions, especially at high frequencies. R.A.Zakarevicius 508
Evaluation of transfer functions of ideal s.c. networks in z-domain using standard linear symbolic or semisymbolic network analysis programs. E.Wehrhahn 801
High-gain decentralised control of interconnected dynamical systems. A.Bradshaw 216
Method of designing filters with shaped passband response. H.Spriggs and C.Nightingale 267
Mixed time/frequency domain approach to model reduction (Comment). J.Hickin 338
Novel active filters using amplifier pole. P.V.Ananda Mohan 378 e683
Stable reduced-order Padé approximants using stability-equation method. T.C.Chen, C.Y.Chang and K.W.Han 345

Stable reduced order Padé approximants using stability equation method (Comment). V.Singh 820
Switched-capacitor biquads based on switched-capacitor transconductance. S.M.Faruque, J.Vlach and T.R.Viswanathan 63
Synthesis of active RC multiport voltage transfer functions with reduced number of operational amplifiers (Comment). B.B.Stamenković 333
Synthesis of nonlinear functions using continued fraction expansion. A.Cichocki 431
Transfer function deviations due to resistor-s.c. equivalence assumption in switched-capacitor simulations of LC ladders. K.Martin and S.Sedra 387
Transfer functions with equiripple passband and very low Q-factor for economical active filters (Comment). M.Biey and A.Premoli 74
Transitional multiple-pole transfer functions for active-filter design. V.S.Stojanović and V.D.Pavlović 21

TRANSFORMS

Transform-domain spectrum extrapolator for efficient picture transmission. N.Kumar, N.B.Chakraborti and A.K.Mukherjee 198

TRANSISTORS

10 GHz/10 W internally matched flip-chip GaAs power f.e.t.s.. Y.Mitsui, M.Kobiki, M.Wataze, K.Segawa, M.Otsubo and T.Ishi 205
Applications of dual-gate GaAs m.e.s.f.e.t.s. for fast pulse shape regeneration systems. W.Filensky, F.Ponse and H.Beneking 214
Calculations of the intrinsically higher temperature stability of electronic devices made from quaternary alloys. A.R.Adams 177
Early voltage uniqueness test for bipolar junction transistors. B.L.Hart 703
Elimination of emitter edge dislocations in silicon planar n-p-n transistors. N.D.Stojadinović and R.S.Popović 842
Emitter-collector breakdown voltage versus gain for various n-p-n collector doping levels. D.J.Roulston and M.Depey 803
GaAs gigabit logic circuits using normally-off m.e.s.f.e.t.s.. T.Mizutani, N.Kato, S.Ishida, K.Osafune and M.Ohmori 315
Generation of nanosecond high-voltage pulses with high repetition rate. M.Kowatsche and J.Lafferl 196
Semidistributed neuristor using plasma-coupled modulating transistors. V.A.Skorik and G.I.Fursin 676

TRANSMISSION LINES

An improvement for the t.l.m. method. P.Saguet and E.Pic 247
Approximate formulas for frequency dependence of microstrip parameters. H.F.Pues and A.R.van de Capelle 870
Approximate solution for propagation modes on lossy multiconductor transmission lines in inhomogeneous media. S.S.Bedair and M.I.Sobhy 914
Finite boundary corrections to coplanar stripline analysis. V.Fouad Hanna 604
Graphical method for conduction loss calculation of TEM transmission lines. J.Majer 638
Propagation of m.f. signals along mine tunnel containing an axial wire and water trough. T.U.Nelson 834

TRANSPORT PROCESSES

Ballistic electron motion in GaAs at room temperature. L.F.Eastman, R.Stall, D.Woodard, N.Dandekar, C.E.C.Wood, M.S.Shur and K.Board 524
Ballistic electron transport in a nonparabolic band. J.B.Socha and G.J.Rees 872
Characterisation of multiple-scan electron beam annealing method. R.A.McMahon, H.Ahmed, R.M.Dobson and J.D.Speight 295
Controlling deep transient depletion of an m.o.s. capacitor. T.P.Pedron, J.P.Lanteri, M.Garrigues and J.J.Urgell 367
Effect of p-doping on carrier lifetime and threshold current density of 1.3 μm GaInAsP/InP lasers by liquid-phase epitaxy. W.Ng and Y.Z.Liu 693
Electron dynamics in P-Si m.o.s.f.e.t. inversion channels. J.Zimmermann, R.Fauquembergue, M.Charef and E.Constant 664
Evidence for alloy scattering from pressure-induced changes of electron mobility in $In_{1-x}Ga_xAs_yP_{1-y}$. A.R.Adams, H.L.Tatham, J.R.Hayes, A.N.El-Sabbahy and P.D.Greene 560
GaAs n^+-p^--n^+ ballistic structure. M.S.Shur and L.F.Eastman 522
Impact ionisation in multilayered heterojunction structures. R.Chin, N.Jun.Holonyak, G.E.Stillman, J.Y.Tang and K.Hess 467
Improved microprocessor-controlled pedestrian data-acquisition system. S.S.Mudaly 3
Laser annealing of low dose Se-implanted GaAs studied by d.l.t.s.. N.G.Emerson and B.J.Sealy 512
Measurement of refractive-index variation with free carrier density and temperature for 1.6 μm GaInAsP/InP lasers. K.Stubkjaer, Y.Suematsu, M.Asada, S.Arai and A.R.Adams 895
Mobility of holes in the quaternary alloy $In_{1-x}Ga_xAs_yP_{1-y}$. J.R.Hayes, A.R.Adams and P.D.Greene 282
Orientation dependence of ballistic electron transport and impact ionisation. H.Shichijo, K.Hess and G.E.Stillman 208
Shallow trap spectroscopy in InP: Fe. J.Bonnafe, M.Castagne, J.Romestan, M.De Murcia and J.P.Fillard 313
Simple method for evaluating electronic properties at silicon-sapphire interface. P.Gentil 617
Space charge limited current in an insulator at high fields. Y.K.Sharma 896
Two-dimensional electron gas m.e.s.f.e.t. structure. D.Delagebeaudeuf, P.Delescluse, P.Etienne, M.Laviron, J.Chaplart and N.T.Linh 667

TRAPS

Deep level defects in Au/ZnSe Schottky diodes. P.Besomi and B.W.Wessels 794
Shallow trap spectroscopy in InP: Fe. J.Bonnafe, M.Castagne, J.Romestan, M.De Murcia and J.P.Fillard 313

TUNNELLING

Band-to-band tunnelling current in $Ga_{0.47}$ $In_{0.53}$ As p-n junctions. T.P.Pearsall 771

ULTRASONICS

Bond integrity evaluation using transmission scanning acoustic microscopy. D.A.Sinclair and E.A.Ash 880
Dark field acoustic microscopy. D.A.Sinclair and I.R.Smith 627
High resolution acoustic probe. W.Dürr, D.A.Sinclair and E.A.Ash 805
Planar acoustic microscope lens using Rayleigh to compressional conversion. G.W.Farnell and C.K.Jen 541
Reflector antenna profile measurement using ultrasound. C.G.Parini and P.J.B.Clarricoats 544
Single lens transmission scanning acoustic microscope. A.I.Morozov and M.A.Kulakov 596

VAPOUR DEPOSITION

Fabrication of completely OH-free v.a.d. fibre. F.Hanawa, S.Sudo, M.Kawachi and M.Nakahara 699
Fabrication of low-loss and wide-bandwidth v.a.d. optical fibres at 1.3 μm wavelength. M.Nakahara, K.Chida, F.Hanawa, S.Sudo and M.Horiguchi 102
O.M. V.P.E. growth of AlGaSb and AlGaAsSb. C.B.Cooper, R.R.Saxena and M.J.Ludowise 892
Transmission loss in low grade $SiCl_4$ v.a.d. fibres. H.Suda, K.Chida and M.Nakahara 802
Ultimately low OH content v.a.d. optical fibres. T.Moriyama, O.Fukuda, K.Sanada, K.Inada, T.Edahiro and K.Chida 698

VARACTORS

GaAs varactors for linear tuning characteristics. A.Colquhoun, E.Kohn and W.J.Rabe 736

WAVE PROPAGATION

Adiabatic method for fibres with nonseparable index profiles. A.Barthelemy and J.Arnaud 193
Analysis of geodesic lenses by beam propagation method. J.van der Donk and P.E.Lagasse 292
Asymptotic behaviour of TE_{11} mode coupling in circular apertures. T.S.Bird 529
Attenuation measurements performed by backscattering technique. B.Costa, B.Sordo, U.Menaglia, L.Piccari and G.Grasso 352
Corrugated waveguide monopulse feed. R.D.Elliott and P.J.B.Clarricoats 324
Detailed error estimates for first order WKB calculation method. G.Jacobsen and J.J.Ramskov Hansen 540
Differential propagation delay in optical multifibre cables. E.F.Andersen 389
Effect of hydroscopic water on dielectric constant of dust at X-band. S.I.Ghobrial 393
Frequency-dependent solution of suspended microstrip line with tuning septums. K.Sachse and J.Citerne 264
H-plane coupling between rectangular microstrip antennas. C.M.Krowne and A.R.Sindoris 211
Magnetostatic bulk wave propagation in a multilayered structure. S.N.Bajpai and N.C.Srivastava 269
Multilayer multimode optical fibre. R.Petrović 562
Near-field correction factors for elliptical fibres. J.J.Ramskov Hansen, M.J.Adams, A.Ankiewicz and F.M.E.Sladen 580
Near-field distributions in selectively excited elliptical optical fibres. D.Yevick and B.Stoltz 210
Propagation in rectangular tunnel with imperfectly conducting walls. J.R.Wait 521
Propagation of m.f. signals along mine tunnel containing an axial wire and water trough. T.U.Nelson 834

Propagation of magnetostatic surface waves in multiple magnetic layer structures. L.R.Adkins and H.L.Glass 590
Simplified parameter-based analysis of single-mode optical guides. W.J.Stewart 380
Single-mode fibre optic directional coupler. R.A.Bergh, G.Kotler and H.J.Shaw 260
Stress dependences of longitudinal wave velocity in magnetostrictive metallic-glass ribbon. K-Y.Hashimoto, M.Yoshida, M.Yamaguchi and H.Kogo 425
Subpicosecond measurement of response of optical fibres. J.Piasecki 498

WAVEGUIDES

Asymptotic behaviour of TE_{11} mode coupling in circular apertures. T.S.Bird 529
Circularly polarised radiation from narrow wall slots in rectangular waveguide. D.R.Hill 559
Comparison of pulse responses of step-index fibres. A.B.Sharma, J.Saijonmaa and S.J.Halme 557
Corrugated waveguide monopulse feed. R.D.Elliott and P.J.B.Clarricoats 324
Determination of modal amplitudes by resolution of radiation patterns. N.Sridhar, T.K.Sen and G.P.Srivastava 12
Effect of edge region on crosspolar performance of dichroic plate. R.Cahill and E.A.Parker 710
First higher-mode cutoff in two-layer elliptical fibre waveguides. S.R.Rengarajan and J.E.Lewis 263
Frequency-dependent solution of suspended microstrip line with tuning septums. K.Sachse and J.Citerne 264
Higher-mode cutoff in elliptical dielectric waveguides (Comment). J.Citerne 13
Imaginary Smith chart for evanescent-mode structures. D.E.De Jersey 93
New analytical model for rectangular image guide. Ph.Gelin, S.Toutain and J.F.Legier 442
Open-circuited coaxial lines as standards for microwave measurements. B.Bianco, A.Corana, L.Gogioso, S.Ridella and M.Parodi 373
Propagation in rectangular tunnel with imperfectly conducting walls. J.R.Wait 521
Reflection and radiation of flanged circular dielectric rod. C.Fray, N.Khayata and A.Papiernik 740
Refracted power technique for cutoff wavelength measurement in singlemode waveguides. V.A.Bhagavatula, W.F.Love, D.B.Keck and R.A.Westwig 695
Slab waveguide star coupler for multimode optical fibre. K.Nosu and R.Watanabe 608
Thick-film fabrication techniques for millimetre-wave dielectric waveguide integrated circuits. M.R.Inggs and N.Williams 245
Vector wave characteristics of radially inhomogeneous waveguide modes. M.Hashimoto 494
Waisted-rib optical waveguides in GaAs. D.N.Macfadyen, C.R.Stanley and C.D.W.Wilkinson 440

X-RAYS

High radiation effects in X-ray lithography. Z.Znamirowski and W.Czarczynski 178